INFORMATION TO USERS

This material was produced from a microfilm copy of the original document. While the most advanced technological means to photograph and reproduce this document have been used, the quality is heavily dependent upon the quality of the original submitted.

The following explanation of techniques is provided to help you understand markings or patterns which may appear on this reproduction.

- 1. The sign or "target" for pages apparently lacking from the document photographed is "Missing Page(s)". If it was possible to obtain the missing page(s) or section, they are spliced into the film along with adjacent pages. This may have necessitated cutting thru an image and duplicating adjacent pages to insure you complete continuity.**
- 2. When an image on the film is obliterated with a large round black mark, it is an indication that the photographer suspected that the copy may have moved during exposure and thus cause a blurred image. You will find a good image of the page in the adjacent frame.**
- 3. When a map, drawing or chart, etc., was part of the material being photographed the photographer followed a definite method in "sectioning" the material. It is customary to begin photoing at the upper left hand corner of a large sheet and to continue photoing from left to right in equal sections with a small overlap. If necessary, sectioning is continued again — beginning below the first row and continuing on until complete.**
- 4. The majority of users indicate that the textual content is of greatest value, however, a somewhat higher quality reproduction could be made from "photographs" if essential to the understanding of the dissertation. Silver prints of "photographs" may be ordered at additional charge by writing the Order Department, giving the catalog number, title, author and specific pages you wish reproduced.**
- 5. PLEASE NOTE: Some pages may have indistinct print. Filmed as received.**

Xerox University Microfilms

300 North Zeeb Road
Ann Arbor, Michigan 48106

75-26,938

BOSTOCK, Charles Alexander, 1939-
MINIMIZING COSTS IN WELL FIELD DESIGN IN
RELATION TO AQUIFER MODELS.

The University of Arizona, Ph.D., 1975
Hydrology

Xerox University Microfilms, Ann Arbor, Michigan 48106

COPYRIGHTED

BY

CHARLES ALEXANDER BOSTOCK

1975

MINIMIZING COSTS IN WELL FIELD DESIGN IN
RELATION TO AQUIFER MODELS

by

Charles Alexander Bostock

A Dissertation Submitted to the Faculty of the
DEPARTMENT OF HYDROLOGY AND WATER RESOURCES
In Partial Fulfillment of the Requirements
For the Degree of

DOCTOR OF PHILOSOPHY
WITH A MAJOR IN HYDROLOGY

In the Graduate College
THE UNIVERSITY OF ARIZONA

1 9 7 5

THE UNIVERSITY OF ARIZONA

GRADUATE COLLEGE

I hereby recommend that this dissertation prepared under my
direction by Charles Alexander Bostock
entitled Minimizing Costs in Well Field Design in
Relation to Aquifer Models
be accepted as fulfilling the dissertation requirement of the
degree of Doctor of Philosophy

Eugene S. Simpson
Dissertation Director

25 April 1975
Date

Charles R. Bostock
Dissertation Director

19 May 1975
Date

After inspection of the final copy of the dissertation, the
following members of the Final Examination Committee concur in
its approval and recommend its acceptance:*

Eugene S. Simpson
J. W. Dunsen
William H. Dunsen
Donald R. Davis

25 April 1975
" " "
28 " "
28 April 1975

*This approval and acceptance is contingent on the candidate's
adequate performance and defense of this dissertation at the
final oral examination. The inclusion of this sheet bound into
the library copy of the dissertation is evidence of satisfactory
performance at the final examination.

STATEMENT BY AUTHOR

This dissertation has been submitted in partial fulfillment of requirements for an advanced degree at The University of Arizona and is deposited in the University Library to be made available to borrowers under rules of the Library.

Brief quotations from this dissertation are allowable without special permission, provided that accurate acknowledgment of source is made. Requests for permission for extended quotation from or reproduction of this manuscript in whole or in part may be granted by the copyright holder.

SIGNED: Charles A. Bestock

ACKNOWLEDGMENTS

This research was supported in part by the Canadian Department of Environment, Inland Waters Branch. It was also supported by the U. S. Office of Water Resources, Grant A-0240 ARIZ. The author is grateful to Professors Eugene S. Simpson and Theodore G. Roefs for their guidance and encouragement during the course of this work.

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	viii
ABSTRACT	x
1. INTRODUCTION	1
Previous Work	2
State of the Art	6
Deficiencies in the State of the Art	7
Objectives and Assumptions of Study	8
Nomenclature	9
Definitions	10
2. WELL-FIELD DESIGN: GENERAL CONSIDERATIONS	13
Categories of Aquifer Conditions	13
Category Chosen for Analysis	14
Decision Variables	15
Operation Decision Variables	15
Planning Decision Variables	16
Aquifer Cell Response Model	16
Formulation of Well Density-Capacity Analysis	20
Choice of Grid Geometry	20
Pumping Lift Components	21
Pumping Energy and Well Failure Costs	22
Well Component Costs	26
Main Steps in Analysis	28
Illustrative Example: Homogeneous Aquifer Case	30
Discussion of Results and Conclusions	36
Comparison with Previous Methods	36
Application and Extension of the Method	39
Conclusions	39
3. AQUIFER RESPONSE MODEL: HOMOGENEOUS CASE	41
Mathematical Definition of Aquifer Response Model	42
Finite Difference Solution	49
Analytical Solution	59
Discussion of Results	63
Comparison of Finite Difference and Analytic Solutions	63
Dupuit Assumptions	64
Delayed Drainage	66

TABLE OF CONTENTS--continued

	Page
Pump Operating Characteristics	67
Surface Recharge	67
Conclusions	68
4. HETEROGENEOUS PERMEABILITY	69
Form of PDF	69
Average Value Calculation	71
Discretization of Expected Value Calculation	72
Inter-Cell Flow	74
Two Extremes of Heterogeneity Distribution	75
Inter-Cell Flow Bounds	76
Illustrative Example	79
Discussion of Results	80
Accuracy of PDF Mean	86
Maximum Non-Simultaneous Pumping Time	89
Multiple Design Possibility	91
Homogeneity within Cells	92
Conclusions	93
5. AQUIFER RESPONSE MODEL: HETEROGENEOUS CASE	95
Circular Representation of Cell Group Models	96
Cylindrical Sink Model	96
Satellite Cell Component	100
Model Formulation	103
Accuracy Check of Cylindrical Sink Model	107
Discussion of Results	111
Conclusions	112
6. DISCUSSION AND CONCLUSIONS	114
Practical Applications	114
Conditions in Bangladesh	114
Well Density-Capacity Combinations	115
Heterogeneity Among Aquifer Cells	116
Inter-Cell Flow	117
Vertical Permeability in Aquifer	118
Influence of Well Failures	118
Bayesian Decision Theory Application	119
Management and Maintenance	120

TABLE OF CONTENTS--continued

	Page
Recommendations for Further Work	121
Vertical Permeability in Aquifer	121
Optimal Depths for Well and Pump Intake	121
Aquifer Heterogeneity	122
Maximum Non-Simultaneous Pumping Period	122
Maintenance Costs	122
Conclusions	123
APPENDIX -- CIRCULAR APPROXIMATION OF POLYGONAL CELL BOUNDARIES	125
NOMENCLATURE	136
LITERATURE CITED	141

LIST OF ILLUSTRATIONS

Figure		Page
1	Grid geometries showing shapes of no-flow boundaries	17
2	Pumping lift components, pump intake drawdown and maximum available drawdown	19
3	Cost bounds for homogeneous aquifer	33
4	Net income bounds for homogeneous aquifer, with permeability equal to 4×10^{-4} [ft/sec]	34
5	Axial section through cylindrical aquifer model (vertical dimension greatly exaggerated)	44
6	Right half of axial section through cylindrical aquifer model, showing trace of cylindrical reference volume . .	46
7	Right-hand side of axial section through finite difference representation of aquifer model	51
8	Permeability intervals, showing interval probabilities . . .	73
9	Expected cost bounds for heterogeneous aquifer with mean permeability equal to 4×10^{-4} [ft/sec]	81
10	Expected net income for heterogeneous aquifer with mean permeability equal to 4×10^{-4} [ft/sec]	82
11	Comparison of net incomes, midway between pumping bounds, for homogeneous case and heterogeneous case	85
12	Hypothetical curves illustrating penalty cost calculation procedures	87
13	Expected net incomes for heterogeneous aquifers with mean permeability of 5×10^{-4} , 4×10^{-4} and 3×10^{-4} [ft/sec] . . .	88
14	Cylindrical sink model, approximation of hexagonal cell group for equilateral triangular, well location grid geometry	97

LIST OF ILLUSTRATIONS--continued

Figure		Page
15	Cylindrical sink model, approximation of square cell group for square, well location grid geometry	98
16	Cylindrical sink model, approximation of equilateral triangular cell group for hexagonal, well location grid geometry	99
17	Cylindrical sink model of nine square cells	101
18	Right-hand side of axial section through finite difference model of cylindrical sink model	105
19	Comparison of drawdowns produced by the circular models and by the square models	109
20	Circle, hexagon, square and equilateral triangle having equal areas, and superimposed for comparison	128

ABSTRACT

Costs associated with well field design are minimized with respect to the well density-capacity combination chosen to meet groundwater demand. The method does not take into account either water benefits or transmission lines for water and power. It does take into account lateral variations in aquifer permeability. All of the wells are equally spaced in a grid pattern and have the same design. Costs associated with each well are divided by the ground surface area of the aquifer cell that contributes groundwater to the well. The resulting cost is averaged over all wells in the field. The average cost per unit area provides a basis for comparing well field costs produced by different well density-capacity combinations.

Costs are due to (1) well construction, pump equipment and replacement of worn-out parts; (2) pumping energy consumption; and (3) maintenance. Maintenance costs due to supervisory personnel and well reconditioning are neglected because data are lacking. Well construction and replacement costs are amortized to equal annual payments over the estimated lifetime of each component. Pumping energy costs depend on pumping schedules. If a well density-capacity combination results in well failure for some cells before the end of a pumping schedule, a penalty cost equal to the value of the water deficit is added to the pumping cost.

A particular category of aquifer conditions was chosen to illustrate the method. The aquifer is unconfined and, with the exception of permeability, is uniform laterally. Groundwater mining occurs during the annual pumping season. An annual wet season fully recharges the aquifer between pumping seasons.

The method is developed in two parts. In the first part, it is defined and illustrated using the assumption of a homogeneous aquifer. In addition, all wells are required to operate simultaneously at equal discharge rates. Under these conditions, each well is surrounded by a no-flow boundary in the aquifer. These boundaries form aquifer cells which are all of equal size.

In the second part, the influence of non-uniform permeability is examined. The permeability within each cell is assumed to be homogeneous, but different cells can have different permeabilities. The frequency distribution of permeabilities in the aquifer is defined by a probability density function (pdf). The sample population of cell permeabilities, realized after well construction, is assumed to have the same frequency distribution as the parent pdf, regardless of well spacing and number of wells.

Examined are inter-cell flow effects due to (1) possible distributions of heterogeneous permeability, and (2) non-simultaneous pumping. For the length of pumping season and aquifer conditions assumed in the illustrative example, inter-cell flow effects were found to be negligible. The maximum duration of non-simultaneous pumping period, such that inter-cell flow effects are negligible, can be calculated.

The design method can be used to estimate profit that might be foregone due to proceeding with construction under uncertainty with respect to the predicted frequencies of cell permeabilities. This opportunity loss was estimated quantitatively in subsequent work, using Bayesian decision theory.

The method defined in the illustrative example is considered to be applicable to aquifer and climatic conditions such as those found in Bangladesh. There, the delta of the Ganges and Brahmaputra Rivers forms an extensive, flat-lying, and unconfined aquifer. Much rain falls in the summer, while the winters may be too dry for growing crops.

CHAPTER 1

INTRODUCTION

Groundwater consumption for human use has increased steadily through history but the increase was most rapid after 1900 as a result of (1) increased demands resulting from expansion of irrigation and industry, and rising standards of living; (2) improvement of pumps; (3) improvements in construction and finishing of wells; and (4) reduction in cost of power from electricity, gas and oil (Encyclopedia Britannica, 1967). Development of, and demand for, high production rate wells added to the problems of well interference and aquifer depletion, with resulting risk of waste in well construction investment and of unnecessary pumping lift costs. Continued development of techniques for more efficient groundwater production requires research in the following three general areas: (1) groundwater flow behavior, (2) groundwater resource evaluation, and (3) methods for choosing well locations and capacities.

This study is directed to the problem of choosing locations and capacities of wells in well field design. The objective is to minimize construction, replacement, and pumping costs subject to meeting groundwater demand and subject to limitations imposed by aquifer properties. The influence on well field design, of benefits from groundwater produced, is excluded from the scope of this study. The influence of complex pipe

networks for distributing pumped groundwater to points of use is also excluded from the scope of this study.

Previous Work

The usual method of well field design involves assessing available geologic and hydrologic information, followed by aquifer testing and predicting aquifer response, before selecting proposed locations and capacities for new production wells. Even after a new production well has been constructed, its maximum production rate cannot be reliably estimated without running a pump test in the well. This is due mainly to the variability and uncertainty of aquifer transmissivity in space. Consequently, well locations and capacities selected before aquifer testing are generally considered to be of little value in the practical business of constructing wells. However, aquifer response models can be useful for indicating the general spatial relationships that should exist among wells of given production rates and under assumed aquifer conditions in order to achieve efficient and effective groundwater extraction.

Theis (1957) and later, Hantush (1961), combined well pumping costs with connecting transmission line costs. Theis (1957) derived an equation for estimating the cost-minimizing spacing between two pumping wells of given production rate and connected by a pipeline. With assumed homogeneous aquifer properties, as the wells are spaced farther apart, pumping cost due to well interference in the aquifer decreases, while pipeline cost increases. Using the modified non-equilibrium formula of Cooper and Jacob (1946) for aquifer response prediction, the first

derivative, with respect to spacing of the sum of these two costs, was equated to zero, to yield an expression for cost-minimizing spacing between the two wells. No constraints were expressed in the formulation of the expression.

Hantush (1961) extended the method initiated by Theis (1957). He derived cost-minimizing well spacing formulations not only for the non-leaky aquifer (Theis, 1935), but also for the leaky aquifer (Hantush, 1956), the non-uniform thickness aquifer (Hantush, 1962a) and the unconfined aquifer having sloping base (Hantush, 1962b). With confined aquifers, the amount of dewatering must not be great enough to cause significant change in transmissivity. He used time averaged drawdown over the pumping period in the cases of the first two aquifer models. The solution formulations can be applied to any specified small number of wells with specified discharge rates, specified connecting water and power transmission line geometry and specified sizes of pipe in each pipeline. (Geometry here refers to geometric figure shape, independent of spacing scale.) An example is solved for three wells at apices of a triangle. All of these spacing formulae assume homogeneous distributions of aquifer properties.

Rushton (1974) provided a method for estimating the relationship among (1) the volume of water that can be removed from storage in an aquifer during a given time period, (2) the transmissivity and storage properties of an aquifer with assumed homogeneous distribution of properties and extensive lateral area, and (3) the combination of discharge rates and spacing of wells located according to a uniform, square

grid. The aquifer response model consists of an impermeably bounded cylinder of aquifer having a well concentric with the axis of the cylinder. The model represents a single well from the well field grid, surrounded by its square cell of aquifer.

Deininger (1970) considered optimization of well capacities for specified well locations and no connecting pipelines. The aquifer response model is given by the Theis equation (Theis, 1935), which requires the assumption of a homogeneous distribution of aquifer properties. Of two solutions given by Deininger (1970), one maximizes well field production using a linear programming model; the other minimizes pumping energy cost using a quadratic programming model. The linear program employs the linear relationship that exists between well discharge rate from any point in the aquifer and drawdown at any point in the aquifer, according to the Theis equation. The drawdown in any well in the aquifer is a linear function of the discharge rates of all the wells in the field. The linear program chooses a combination of well discharge rates that maximizes production from the well field subject to the maximum drawdown constraint at each well and at specified points around the well field boundary. The quadratic program also employs this linear relationship between well discharge rates and aquifer drawdown. The pumping cost at any well is assumed to be proportional to the pumping rate at the well multiplied by the pumping lift. Consequently, pumping cost for the well field is a quadratic function of the pumping rates of all wells in the field, and can be minimized by using a quadratic program.

Maddock (1972) has further developed this concept of optimizing well field production with respect to mutual interference among the wells. An "algebraic technologic function" is derived which predicts drawdown at any well and at specified points in time as a linear function of the pumping rates at all of the wells in the aquifer. The function is derived for an aquifer model having finite boundaries, and heterogeneous transmissivity and storage coefficients. Assuming that the water cost per season at a well is directly proportional to the product of the quantity of water pumped from the well during the season and the drawdown incurred at the well, a quadratic program is formulated to minimize the production cost of groundwater from all of the wells. The constraints are that water demand must be met and the upper limit to the pumping capacity of each well may not be exceeded. In a later paper (Maddock, 1974), a nonlinear technologic function is derived for unconfined aquifers, that is, aquifers whose transmissivities vary with drawdown. The associated program for minimizing groundwater production costs is quadratic, cubic or of higher order, depending on the degree of accuracy desired in the calculations.

Pipelines and networks for distributing pumped groundwater to points of use, are a major factor in well field design. Their construction cost is high and proportional to pipeline length. From a review of developments in pipeline design (Raman, 1970; Kally, 1969 and 1971; Liang, 1971; and Deb and Sarkar, 1971), it is evident that the methods described for designing of complex pipe networks require predesignation of both locations of water entry points and rates of entry at each entry

point. Thus, minimizing costs in well field design in conjunction with the influence of complex pipe networks would require a search approach involving evaluation of trial designs.

The many references on aquifer response providing background material for a study such as this are too numerous to mention here. The interested reader is referred to the following selected references. Analytic response models are presented by Muskat (1946), Hantush (1964) and Witherspoon and others (1967). Numeric response models are presented by Freeze (1969), Neuman and Witherspoon (1971) and Prickett and Lonnquist (1971). Selected references on individual well design and construction methods are Johnson, Inc. (1966), Walton (1970) and Ahrens (1970). Nelson and Busch (1967) give well costs for pumping irrigation water in central Arizona.

State of the Art

The state of the art in detailed well field design formulations may be briefly summarized as follows. Hantush (1961) provided equations for minimizing pumping costs plus transmission line construction costs with respect to well spacing. Use of the equations requires specification of well discharge rates, geometry of well locations and a pipe size for each pipeline connecting wells to the destination point. The aquifers are assumed to be homogeneous. Maddock (1972, 1974) provided a method for minimizing well field pumping costs from wells subject to meeting water demand and not exceeding the upper limit to the pumping capacity for each cell. The method allows use of distributed parameter models and consequently can incorporate aquifer heterogeneity. In both

of the above methods, either pumping rates are specified or well locations are specified before minimization.

Rushton (1974) gave a procedure for estimating a suitable combination of spacing and sizes of wells in a square grid well field, in order to mine a given volume of groundwater over a given time period. In this method, both the well locations and pumping rates vary in the cost minimization. No costs are included in the method.

Deficiencies in the State of the Art

Two deficiencies in the state of the art may be observed. First, for the problem of designing a large number of wells having the same design capacity and located in a uniform grid, so that a given quantity of water can be produced in a given time period, no method has been formulated for estimating variation of costs as a function of the number and capacity of wells to be installed. With larger wells spaced farther apart, there is more risk of exceeding maximum available drawdown with consequent reduction in water supply rate. Second, there is need to estimate the consequences of uncertainty in the distribution of hydraulic properties of real aquifers in terms of the resulting cost penalties of bad guesses. The consequences estimated for the various possible outcomes will assist the well field designer in deciding whether or not to obtain more information about the true distribution of properties in the aquifer. Good or bad luck in the chance selection of a well location having a higher or lower transmissivity, or available drawdown, may eclipse economies expected from well field designs of estimated minimum

cost, that were based on assumed uniform distribution of aquifer properties.

Objectives and Assumptions of Study

In response to the two deficiencies of the state of the art, a particular form of well field design is assumed, in which the wells are located on a uniform grid pattern of points, and all of the wells are of identical design. It is assumed, in addition, that probability density functions (pdf's) are available for describing the uncertainty in aquifer heterogeneity at the well locations. The objectives of this study are the following:

1. To develop a method for comparing uniform grid well field costs for alternative, well density-capacity combinations required to meet a given groundwater demand.
2. To include in the method an estimate of the influence which uncertainty in the lateral variations of aquifer permeability has on uniform grid well field costs.

The following assumptions and provisions are general to the overall well density-capacity analysis method of this study. Predicted benefits from groundwater may influence well field design. The effects of these benefits are excluded from the scope of this study. The effect of water and power transmission lines are excluded from the analysis beyond specifying a well pump outlet pressure common to all wells. Also excluded are maintenance costs due to well supervision and to well reconditioning over and above capital costs for replacement of worn-out

parts. It is further assumed that the economic loss due to a cutback in production, resulting from reaching maximum drawdown constraint, is directly proportional to the water volume deficiency below design demand. The stochastic nature of aquifer recharge is approximated by cyclical patterns of rectangular shape.

Other assumptions apply to portions of the analysis and are defined as needed. The aquifer response models employed in the analysis require some idealistic assumptions. Limitations arising from these assumptions are later, in part, overcome by applying the model to conditions bounding reality in order to obtain a realistic range of possible results.

Nomenclature

All symbols are defined where they first appear in the text and again in Nomenclature. Symbol quantity dimensions are [M] for mass, [L] for length, and [T] for time. Square brackets are used only to enclose dimension symbols. Rectangular coordinates (Standard Mathematical Tables, 1970, p. 369) define points in space using coordinates x [L], y [L] and z [L], where z is measured positive upwards and where, if the x -axis points east, then the y -axis points north. Cylindrical coordinates (Standard Mathematical Tables, 1970, p. 369) define points in space concerning groundwater flow with respect to a well. Thus, r [L] is horizontal distance from vertical axis of a well, θ [L/L] is radian angle measured counter-clockwise from a plane through vertical axis, and z [L] is vertical distance above the horizontal datum plane. The t [T] coordinate signifies an instant in time. When it is desired to emphasize that

a symbol quantity is a function of space and/or time, these coordinates are enclosed in round brackets and follow immediately after the symbol. At other times, when the meaning is clear from context, space-time coordinates as well as dimensions are dropped from function symbols. Thus, for example, either $h(r,\theta,z,t)$ [L] or simply h ; both represent the value of piezometric head in length units at the general point (r,θ,z,t) in space and time. Brackets of the form $\{ \}$ designate hierarchy of arithmetic operations. Adjacent symbols are always multiplied, while slash, /, denotes division. Multiplication always precedes division.

Definitions

Piezometric head at any point in the aquifer is defined as the sum of elevation head, z [L], equal to the distance above some datum elevation, plus pressure head, $\{p(x,y,z,t) - p_0\}/\rho g$ [L], where p [M/LT²] is absolute pressure, p_0 is atmospheric pressure, ρ [M/L³] is density of water and g [L/T²] is acceleration due to gravity. More briefly,

$$h = z + \{p - p_0\}/\rho g.$$

Viewing an aquifer as a system, the state of the system may be defined as the distribution of piezometric head within the aquifer. The inputs and outputs to the system are, respectively, aquifer recharge and discharge. Natural recharge and discharge depend in part on the state of the system, while artificial recharge and discharge are controlled by man.

Aquifer response refers to changes in state of piezometric head within the aquifer. Aquifer response models are used to predict changes in state for given changes in inputs and outputs of the aquifer system.

These models incorporate best known and estimated values of physical properties of the aquifer.

The physical properties are permeability, specific storage and specific yield. The term "field permeability" is used here to indicate the aquifer permeability as seen by a well, that is, the aquifer transmissivity divided by the saturated thickness of the aquifer.

This study defines a well field design as a well density-capacity combination for wells located in a two-dimensional grid or a one-dimensional line. The basic decision variables in well field design are locations and capacities of wells. Locations and capacities of wells are chosen by the well field designer from a range of feasible pumping patterns that he considers to be satisfactory in relation to the water demand.

Well pumping patterns are patterns in space, quantity and time, as indicated by well locations and pumping quantity schedules for each well. Positive pumping refers to well recharge while negative pumping refers to well discharge. Feasibility of a pumping pattern depends on aquifer response to it. Future aquifer response to any proposed pumping pattern depends on the aquifer's physical properties, the present distribution of head in the aquifer, as well as on the future space-time configuration of other recharge-discharge inputs and outputs not included in the pumping pattern.

In Chapter 2, the well density-capacity analysis method is formulated. Basic to the method is the consideration of one well and its appropriately sized cell of aquifer. To begin with, the entire aquifer

is assumed to be homogeneous. Chapter 3 describes a response model for an aquifer cell. The model is cylindrical in shape, co-axial with the well, and has impermeable sides and base. In Chapter 4, the analysis is extended to include aquifer heterogeneity. Average well field costs are calculated with respect to a pdf defining frequencies of different permeabilities among aquifer cells. Chapter 5 presents an extension of the cell model. This extension allows estimating inter-cell flow due to heterogeneous permeability among adjacent cells. In Chapter 6, the results of the study are discussed, areas for further work are suggested and conclusions are stated.

CHAPTER 2

WELL-FIELD DESIGN: GENERAL CONSIDERATIONS

The purpose of this chapter is to develop a method for comparing well field costs due to various well density-capacity combinations required to meet a specified groundwater demand rate from a given well field area. Basic to the method are (1) the assumption of a uniform grid well-field design in the aquifer area of interest, and (2) cost analysis of a single well and its appropriately sized cell of aquifer. The size of the cells is determined by the well spacing in the uniform grid. The cost due to any well is divided by its cell area to give its costs per unit area. Costs are so expressed as a basis for comparing different well density-capacity combinations for meeting a given demand expressed as a depth of water over the ground surface. By using costs per unit area, comparisons can be made without regard to the number of wells in the field corresponding to each combination.

Categories of Aquifer Conditions

One may envision several categories of aquifer conditions for well-field design involving choice of well density versus well capacity. A first category involves a well field having well locations according to a two-dimensional grid in a laterally extensive, unconfined aquifer. The aquifer is pumped during an annual dry season and fully recharged during an annual wet season by rain or flood water. In this case, costs can be expressed as annual costs per unit ground surface area for an indefinite

period. An example of this category is the flood plain aquifer of the Ganges and Brahmaputra Rivers in Bangladesh. Another category is a two-dimensional grid well field on a laterally extensive aquifer which is to be mined over some period of years. In this case, pumping costs increase each year and the period of analysis is the estimated time to depletion of the aquifer. This type of situation may be found in arid parts of the southwestern United States. A third category is a one-dimensional grid of wells located parallel to a linear recharge source such as a river. Annual recharge cycles would be probable, allowing use of annual costs per unit length along the river. Well density-capacity analysis differs for each of these, and other possible categories of aquifer conditions. However, many aspects of analysis are common to all categories. This study is directed to the development of a well field design method for the first category of aquifer conditions given above.

Category Chosen for Analysis

The category of aquifer conditions chosen for analysis can be defined more precisely as follows. The aquifer is unconfined, allowing for areally uniform recharge from ground surface. The well field operates during an annual dry season, mining stored groundwater from the aquifer. A rainy or flood season, during which the wells are shutoff, follows the dry, pumping season and recharges the aquifer to its original static water level. The pumping-recharge cycle repeats the following year and so on, indefinitely.

Decision Variables

The decision variables of interest here are those which specify the design and the future operation commitments of a well field, and which also affect the total costs and reliability of the well field in relation to the aquifer yield capability. In the following section, a set of decision variables is defined in order to analyze well field designs for the category of aquifer conditions chosen above.

Operation Decision Variables

Operation decision variables deal with the manner in which well field production requirements are to be met after the well field has been constructed and is in operation. Practical considerations related to water use usually require that wells be capable of producing at an instantaneous discharge rate several times larger than their long-term average rate. Accordingly, as a first trial, one might define two operation decision variables as first, long-term average production rate from each well, and second, maximum instantaneous discharge rate from each well. So defined, the number of operation decisions would be twice the number of wells. This definition is awkward because it depends on the as yet unspecified number of wells and also because it may involve a large number of decision variables.

Uniform grid well field. If we assume that the aquifer is laterally-extensive and laterally-uniform in its properties, then a uniform grid well-field design is appropriate. By a uniform grid, we mean that all wells are of the same capacity and equi-distant from one another. The three possible uniform grid geometries are equilateral

triangular, square and hexagonal (see Figure 1). We defer discussion leading to selection of one of these uniform grid geometries until later. Note that the term "geometry" here refers to relative well locations, but without specifying scale.

Let us assume three operation decision variables on an areally uniform basis as follows: (1) total seasonal demand, D [L], is the total, areally uniform depth of water to be pumped during the demand season; (2) maximum length of demand season is $t_{\max}$ [T]; (3) maximum instantaneous demand rate is D_i [L/T]. So defined, the operation decision variables are only three in number.

Planning Decision Variables

Planning decision variables are those that specify the well field design; that is, the location and capacity of each well. By constraining design to any one of the uniform grids, we can reduce the number of planning decisions from twice the number of wells to the following three: (1) uniform grid geometry; (2) well density, N_w [well/L²], the number of wells per unit area; and (3) well design discharge rate, or capacity, Q_c [L³/T] (the minus sign is, for convenience, dropped from Q_c). The product of N_w and Q_c must, of course, equal D_i . This further reduces the number of planning decisions to two, these being: (1) grid geometry; and (2) well density-capacity combination, N_w and Q_c .

Aquifer Cell Response Model

Feasible operation decision variable values are subject to limitations due to aquifer characteristics of transmissivity, storage,

Equilateral Triangular Grid
Hexagonal No-flow Boundaries

Square Grid
Square No-flow Boundaries

Hexagonal Grid
Equilateral Triangular No-flow Boundaries

Figure 1. Grid geometries showing shapes of no-flow boundaries.

recharge and maximum available drawdown. Maximum available drawdown, $s_{b \text{ max}}$ [L], is the depth of drawdown in the well, from initial static water level down to the pumping level that will produce maximum, total discharge from the well. This pumping level is theoretically at the level of the bottom of an unconfined aquifer, but in practice it is generally above the aquifer bottom (see Figure 2). These aquifer characteristics also affect pumping costs. In order to estimate limitations on operation decisions as well as the magnitude of pumping lift energy costs, a simplified aquifer response model will be assumed.

The aquifer response model is laterally homogeneous and isotropic, of infinite areal extent, of uniform thickness and horizontal. The initial water table is also horizontal. The wells are assumed to fully penetrate the aquifer thickness. In addition, all wells in the infinite uniform grid commence and continue pumping simultaneously at identical discharge rates. Under these assumptions, a "cell" of aquifer having a no-flow boundary surrounds each well (see Figure 1 and also Appendix). A no-flow boundary is defined as a surface in the aquifer, perpendicular to which the head gradient is zero. Every cell associated with any one grid geometry has the same shape and size. Each well is located at the center of a cell. Since drawdown in each well is the same as in all of the other wells, any well from the field in an impermeably walled cell can represent the aquifer response model. N_w specifies the size of this single-cell model.

The assumption of simultaneous pumping of all wells at identical discharge rates is a major limiting assumption and bears further clarification. The cell boundaries are located at maximum distance from

Figure 2. Pumping lift components, pump intake drawdown and maximum available drawdown.

s_f	Friction loss in pump bowls, column and head; includes velocity head acquired in pump.
s_p	Pressure head at pump outlet.
s_0	Static lift, from initial static water level to pump outlet elevation.
s_a	Head loss in aquifer, assumed to be single valued.
s_w	Well loss across well screen and along well casing to pump intake.
s_{max}	Maximum drawdown from initial static water level to pump intake.
$s_{b\ max}$	Maximum available drawdown, from initial static water level to lowest possible pump setting for maximum well production.
(a)	Elevation plus pressure head at pump outlet.
(b)	Pump outlet elevation head.
(c)	Initial static water elevation in well.
(d)	Theoretical water head in aquifer, just outside well screen; assumed to be single valued, a variable in time as pumping continues.
(e)	Total head at pump intake screen, a variable in time.
(f)	Water surface elevation in well, a variable in time.
(g)	Pump intake elevation, point of maximum drawdown.
(h)	Lowest pump intake setting, for maximum production from well.

Figure 2. Pumping lift components, pump intake drawdown and maximum available drawdown.

their nearest wells. The effects of operating the well pumps stochastically are damped in passing through the aquifer to the cell boundaries. A "moving average" of the stochastic pumping effects is sensed at the cell boundaries. Thus, provided that the average pumping rates over time intervals of short duration are simultaneously equal at all wells, there will be no inter-cell groundwater flow, and the assumptions of the aquifer response model will hold true. How long the non-simultaneous pumping intervals can be, is discussed further at the end of Chapter 4.

Formulation of Well Density-Capacity Analysis

To this point, the well field design model consists of a typical well located at the center of its aquifer cell. Dividing any cell cost by the ground surface area over the cell reduces the cell cost to a unit area cost. Since all cells are assumed to be identical, this provides a basis for comparing total well field cost due to different well density-capacity combinations without regard to the number of wells involved with each combination. The problem now is to formulate the method of obtaining cell costs for a given well density-capacity combination.

Choice of Grid Geometry

It can be shown (see Appendix) that pumping costs associated with any practical well density-capacity decision are negligibly influenced by the choice of any one of the three grid geometries shown in Figure 1. For a given N_w , the equilateral triangular grid, which produces hexagonal aquifer cells, is most efficient with respect to drawdown pumping costs. The square grid with square cells, and the hexagonal grid with equilateral triangular cells, follow in respective

order of decreasing pumping efficiency. However, the difference in total costs resulting between use of the most efficient and the least efficient grid geometries is, for practical purposes, negligible. Grid geometry can be chosen externally to this cost analysis, according to such factors as existing access road geometry and land subdivision geometry. Let us, therefore, exclude grid geometry from further consideration in this cost analysis.

Pumping Lift Components

Let us define five components of pumping lift as follows: (1) s_0 [L] is the pumping lift to ground surface (assumed to be at pump outlet elevation) from initial static water level in well; (2) s_a [L] is the head loss in aquifer (assumed to be single valued) below initial static water level; (3) s_w [L] is the head loss across the well screen and along well casing to pump screen; (4) s_f [L] is the pump efficiency head loss due to friction in pump bowls, column and pump head, and including velocity head at pump outlet; and (5) s_p [L] is the pump outlet pressure head (see Figure 2).

In this analysis, we assume that s_0 is a predetermined constant. A mathematical solution to the aquifer response model presented later will be used to estimate maximum and minimum bounds on s_a . We neglect s_w in this study. With most turbine pumps used in high capacity wells, s_f varies with pumping lift and condition of pump. However, to simplify the analysis, we will approximate pump efficiency by a constant fraction, E . Expressed algebraically, pump efficiency head loss will, therefore, be

$$s_f = \{s_0 + s_a + s_p\}/E - \{s_0 + s_a + s_p\} . \quad (2.1)$$

Since this analysis considers all wells to be the same, then s_p must be the same for all wells, regardless of their position in a pipeline network. s_p can be set equal to some constant, assumed to be representative of pipeline network pressure, or, if the wells discharge into irrigation ditches, then s_p equals atmospheric pressure, or zero.

Pumping Energy and Well Failure Costs

Cost bounding pumping schedules. Future pumping patterns in time are practically impossible to predict because they are stochastic. If they could be predicted, their complexity would require time-consuming analysis for aquifer response and pumping costs. Therefore, it is useful to choose for analysis a set of reasonable pumping schedules that will provide approximate bounds to pumping costs. Let us employ simple pumping schedules of the following kind. The wells pump at a constant, steady rate from the beginning of the pumping season until some predetermined, pumping termination time, at which time the wells are shutoff for the remainder of the season.

A pumping schedule may or may not, depending on aquifer properties, result in well failure. Well failure means that "drawdown to pump intake" has been reached in the wells, requiring that they be shutoff for a period of time so that water level recovery in the aquifer around the well can take place. Drawdown to pump intake, $s_{\max}$ [L], can be defined as the difference in elevation between initial static water level in well and elevation of top of pump intake screen (see Figure 2). The effect of well failure and resulting intermittent well operation is

to reduce the average production rate from the well. This reduced average production rate cannot exceed the production rate that would result if, instead of pumping the wells intermittently, the drawdown were held at $s_{\max}$, and the quantity of water that would run into the wells were continuously pumped out. For the purpose of bounding possible pumping costs accruing to fulfillment of the operation decisions, we adopt pumping schedules of the following kind. We adopt pumping schedules that involve constant, steady pumping for the duration of the predetermined pumping time, or, if and when the wells fail, drawdown is held at $s_{\max}$, and water is continuously pumped out of the wells at whatever rate it will run into them from the aquifer, for the remainder of the predetermined pumping time.

The lowest pumping cost will result if the wells are operated continuously at the lowest possible rate, barring well failure, subject to meeting D by $t_{\max}$, this rate being equal to $D/t_{\max}$. The wells may fail at this rate with the result that D is not met by $t_{\max}$. It is useful to attach a penalty cost to any water deficit below D . Let the value of water per unit volume at pump outlet be V [$\$/L^3$], a constant. Since V will surely be greater than the pumping cost per unit volume, we can let the penalty cost be equal to the value of the water deficiency, had it not occurred. However, with such a penalty cost, we may not have the minimum cost bound, for pumping at a somewhat higher rate early in the pumping season, bringing about earlier well failure, might enable D to be met exactly by $t_{\max}$ (or at least a greater percentage of D), thereby reducing the water deficit cost. The value of this true, cost minimizing, initial pumping rate would have to be found by a search

technique, involving at least several additional computer runs of the aquifer response model. Therefore, in order to simplify, and to save costs, we adopt the pumping schedule previously defined, recognizing that it produces the true lower bound on pumping costs only barring well failure, but under well failure conditions it produces an approximate lower bound. That is, let the wells pump continuously at rate $D/t_{\max}$ until time $t_{\max}$. If well failure occurs, drawdown is held at $s_{\max}$ and available water is pumped. A cost penalty is added to the pumping costs, equal to the value of the water deficit, were it eliminated.

On the other hand, the highest pumping cost will result if the wells are operated continuously at the highest possible rate, D_i , until D has been accumulated at time $t_{\min} = D/D_i$ [T]. If well failure occurs before $t_{\min}$, a water deficit will exist at time $t_{\min}$. Note that if initial pumping were begun late in the season, at time $t_{\max} - t_{\min}$, there would be no time left to make up this deficit. Also, intermittent pumping after well failure will result in a somewhat lower average pumping rate than that due to the constant drawdown condition at $s_{\max}$, causing a greater deficit and hence greater penalty cost. However, for simplicity, we assume a pumping schedule that results in an approximate upper bound on pumping energy costs, as follows. The wells operate at rate D_i for the period $t_{\min}$. If well failure occurs, drawdown is held at $s_{\max}$ and available water is pumped until $t_{\min}$ is reached, then the wells are shut off. To the pumping costs is added a cost penalty equal to the value of the water deficit, were it eliminated.

Pumping cost expression. An expression for total, seasonal pumping energy cost per well may be defined as follows. Let pumping

energy cost be directly proportional to the total energy consumed in pumping against $\{s_0 + s_a + s_f + s_p\}$, this energy being expressed in units $[L^4]$, which represent a volume of water raised through a vertical distance. Let c $[\$/L^4]$ be the constant of proportionality between pumping energy consumed and pumping cost. Pumping energy cost is equal to the product of c and the time integral of instantaneous well discharge rate multiplied by instantaneous pumping lift. Let t $[T]$ represent any time instant during the pumping season, and after time zero when static water level conditions prevailed in the aquifer. Let $-Q_w(t)$ $[L^3/T \text{ well}]$ be the instantaneous well discharge rate at time t . Without the minus sign, Q_w would indicate a well recharge rate. Then seasonal pumping energy cost up to time t is equal to

$$c \int_0^t |Q_w| \{s_0 + s_a + s_f + s_p\} dt \text{ } [\$/\text{well}] .$$

Substituting Equation (2.1) gives

$$\{c/E\} \left\{ \int_0^t |Q_w| s_a dt + \{s_0 + s_p\} \int_0^t |Q_w| dt \right\}$$

for pumping energy cost to time t . The unknowns in this expression are

$$\int_0^t |Q_w| s_a dt \text{ and } \int_0^t |Q_w| dt.$$

Aquifer response models are presented in later chapters for evaluating these unknown integrals by numerical methods. Discrete time intervals are involved, $\Delta t_j = t_j - t_{j-1}$, $[T]$, where $j = 1$ for the first time interval and increases by one for each successive time interval. During each Δt_j , one of either well discharge rate, $-Q_{wj}$ $[L^3/T \text{ well}]$, or

aquifer drawdown, s_{aj} [L], must be specified, the model then solving for the unspecified variable. Let us assume that $-Q_{wj}$ is a specified constant in time, for all j , up until $s_{\max}$ has been reached. Up to this time, the model solves for s_{aj} . After $s_{\max}$ has been reached, s_{aj} is held constant, equal to $s_{\max}$, and the numerically declining values of $-Q_{wj}$ are determined for each succeeding Δt_j . Thus, total seasonal, pumping energy cost is equal to

$$\{c/E\} \left\{ \sum_{j=1}^{j \max} |Q_{wj}| s_{aj} \Delta t_j + \{s_0 + s_p\} \sum_{j=1}^{j \max} |Q_{wj}| \Delta t_j \right\} [$/well],$$

where pumping ceases for the remainder of the pumping season after $t_{j \max}$. This pumping energy cost may be expressed as a per unit area cost by multiplying it by N_w .

Well Component Costs

The two major well components contributing to well component costs are (1) the pump, including motor or engine, head, column and bowls; and (2) the well itself, including casing and well screen or strainer. In order to express the total of well component costs as an equal annual payment per well, each component cost is amortized, at an assumed interest rate, to an equivalent annual cost over its estimated lifetime. As a component wears out, it is assumed to be replaced immediately at its original purchase cost. Note that certain replacement costs are neglected. For example, replacement of pump bowls alone would entail additional labor costs which, in the original installation of the pump, were distributed over all parts of the pump. These additional replacement labor costs are neglected.

In the design of components for individual wells, the major variables are Q_c , $s_{\max}$ and s_p . The diameter of the pump bowls used in a well is the major factor influencing the choice of diameter for a well. The well screen design is another factor, but usually the bowls are the largest component which must pass down the well casing. The variable Q_c controls the diameter of pump bowls, and hence the well casing diameter, in addition to influencing the horsepower required of the pump motor. The variable $s_{\max}$ influences the number of bowl stages, the pump column length and the horsepower of the pump motor. The variable s_p influences the number of bowl stages and the pump motor horsepower.

Other variables affecting well design are aquifer conditions which are either not generally subject to manipulation by man, or can be optimized independently of this well field design analysis method. These other aquifer conditions are of three kinds: physical, technologic and economic. Examples of physical aquifer conditions are transmissivity, storativity and static lift. Technologic conditions relate to available drilling and well construction techniques. Economic conditions refer to all well component costs, delivered and installed at well site. For these other aquifer conditions, each feasible combination of Q_c , $s_{\max}$ and s_p will have some corresponding pump and well design deemed optimal by the designer, with a corresponding cost for construction and replacement of worn out components as discussed earlier. Let us name this cost "well component cost," and for given sets of physical, technologic and economic aquifer conditions, express it as a function of Q_c , $s_{\max}$ and s_p .

A value for $s_{\max}$ to be used in the well component cost function may be obtained as follows. We recall that the ground surface area per

well is $1/N_w = Q_c/D_i$ [L^2/well], and that the pumping time duration at maximum rate is $t_{\min} = D/D_i$. Knowing $1/N_w$, Q_c and $t_{\min}$, in addition to those aquifer physical properties and hydrologic states which are relevant to the aquifer response model, we can use the model to calculate the maximum value of s_a for simultaneous pumping of all wells, that is, $s_{a \max}$ [L]. When $s_{a \max}$ equals $\{s_{b \max} - s_w\}$, then well failure is inevitable at the given density of wells and with the pumping schedule being tested. Since we are neglecting s_w , then the well field designer will set $s_{\max}$ equal to $s_{a \max}$. In this case, note that $s_{a \max}$ is always equal to or less than $s_{b \max}$. For the purpose of well field design, the aquifer model senses well failure only when s_a reaches $s_{b \max}$. Plugging simultaneous values of Q_c , $s_{\max}$ and s_p into a well component cost function will provide an estimate of well component annual cost per well. Multiplying this cost by N_w gives well component annual cost per unit ground surface area.

Main Steps in Analysis

A graph of annual costs per unit area versus well density-capacity planning decision values will help the well field designer choose a cost-minimizing well field design. A summary of the main steps in analysis for creating the graph follows:

1. Choose a set of trial values for the operation decision variables, D , $t_{\max}$ and D_i .
2. Choose several representative N_w and Q_c combination values over a practical range.

3. Using an aquifer cell response model solution such as presented later in this study, for each representative N_w and Q_c combination, determine maximum and minimum bounds on pumping energy consumption,

$$\left\{ \sum_{j=1}^{j \max} |Q_{wj}| s_{aj} \Delta t_j + \{s_0 + s_p\} \sum_{j=1}^{j \max} |Q_{wj}| \Delta t_j \right\} [L^4/\text{well}] .$$

At the same time, record values of $\sum_{j=1}^{j \max} |Q_{wj}| \Delta t_j$, the total water pumped per well, for calculating water deficit penalty costs, if well failure occurred. Also record $s_{\max}$ equal to $s_{a \max}$ for use in the well component cost function. Multiply the above bounds by cN_w/E [$\$/\text{well}/L^6$] to obtain bounds on annual pumping cost per unit area.

4. The water deficit penalty cost is

$$V\{D - N_w \sum_{j=1}^{j \max} |Q_{wj}| \Delta t_j\} [L^2] .$$

If well failure did not occur for a particular pumping schedule, then the above expression for penalty cost will sum to zero, since the total water pumped per well will then be equal to D/N_w .

5. By substituting simultaneous values of Q_c , $s_{\max}$ and s_p into the well component cost function and multiplying the result by N_w , we obtain annual well component cost per unit area.
6. Add the annual costs per unit area due to well component costs, pumping energy cost bounds, and water deficit penalty for each

corresponding N_w and Q_c combination and plot the results graphically.

7. For each set of operation decision variables to be examined, repeat the procedure.
8. The well spacing parameters for each of the uniform grids, as shown in Figure 1, may be calculated using the following formulae. For the equilateral triangular grid which produces hexagonal boundaries, $b^2 = 2/\{\sqrt{3} N_w\}$. For the square grid, which produces square boundaries, $1^2 = 1/N_w$. For the hexagonal grid, which produces equilateral triangular boundaries, $p^2 = 4/\{3\sqrt{3} N_w\}$.

Illustrative Example: Homogeneous Aquifer Case

A detailed knowledge of the aquifer cell response modeling technique described in the next chapter is not needed to follow the main steps of the well density-capacity analysis presented here. A consistent set of arbitrary aquifer conditions serve to illustrate the method.

Physical aquifer conditions used in the aquifer response model are the following. Permeability, K [L/T], is homogeneous and isotropic at 4×10^{-4} [ft/sec]. Specific yield, S_y , is .15, being constant. Static lift, s_0 , is 20 [ft]. Initial saturated thickness of aquifer is 200 [ft]. Maximum available drawdown, $s_{b \max}$, is 160 [ft].

Using a c value of 2.30×10^{-7} [\$/ft⁴], and an E value of .75, gives c/E equal to 3.06×10^{-7} [\$/ft⁴] for pumping energy cost. V is constant at 2.00×10^{-4} [\$/ft³].

Two cost functions yield representative well component costs.

Without the pump component, the well cost function is

$$560.Q_C^{.780} \text{ [$/year well]} .$$

The pump component cost function is

$$400. + 2.25\{Q_C - .713\}\{s_{\max} + 12.\} \text{ [$/year well]} .$$

The units of Q_C are $[\text{ft}^3/\text{sec well}]$, and of $s_{\max}$ are $[\text{ft}]$. Multiplying these well component costs per well by N_w gives well component costs per unit ground surface area. Pump outlet pressure, s_p , is zero, and so neglected in these cost functions.

These well component cost functions represent well component costs that could result from a particular, assumed set of aquifer conditions consistent with this illustrative example. A computer program was written to generate well component costs as a function of the variables, Q_C , $s_{\max}$ and s_p , for assumed aquifer conditions including aquifer thickness, properties of granular material, and depth of overburden. The well penetrates the full aquifer thickness, and the wells are gravel packed. Well and pump component costs and estimated lifetimes were taken from Nelson and Busch (1967). Some additional costs and related information were obtained from Cook Well Strainer Co. (1965, 1966) and from Tipton and Kalmbach, Inc. (1960). The above cost function expressions resulted from fitting curves to output data from the well cost computer program.

A summary of results from main steps in analysis follows:

1. Trial values of operation decision variables are $D = 5 \text{ [ft]}$,
 $t_{\max} = 1.725 \times 10^7 \text{ [sec]} \text{ or } 200 \text{ [days]}$, and $D_1 = 8.70 \times 10^{-7} \text{ [ft/sec]}$.

2. Representative Q_c values are 1.5, 2.5, 3.5, 4.5, 5.5 and 6.5 [ft³/sec well]. Respective N_w values follow from $N_w = D_i/Q_c$.
3. Maximum and minimum bounds on annual pumping energy cost per unit area are plotted on Figure 3. They have been added to the corresponding well component costs on Figure 3. Respective values of total water pumped per well are 8.63×10^6 , 1.438×10^7 , 2.01×10^7 , 2.59×10^7 , 3.10×10^7 and 3.35×10^7 [ft³]. Water deficit values per well are 0, 0, 0, 0, 6.56×10^5 and 3.91×10^6 [ft³]. Finally, respective values of $s_{\max} = s_{a \max}$ are 62, 82, 109, 152, 160 and 160 [ft].
4. Results from the well component cost functions per unit area are plotted on Figure 3. Figure 4 shows net income per unit area, the difference between income, at rate V , from water obtained, and total well component plus pumping energy costs.

Discussion of example results. The following discussion concerns the shapes of the curves shown in Figure 3. For brevity, Q_c and N_w combinations are represented by Q_c alone, but the reader should keep in mind the relationship between Q_c and N_w as shown across the top of Figure 3. Note that with increasing Q_c , the rate of decrease of N_w decreases. This, in part, explains the change in slope of the well cost curve (curve 1) from downward to the right between $Q_c = 1.5$ and 2.5, to upward to the right between $Q_c = 3.5$ and 4.5. The return to a downward slope to the right of $Q_c = 4.5$ is due to well drawdown reaching $s_{b \max}$ so that the pump columns extend no deeper in the wells, for increasing Q_c . Curve 2 shows the well and pumping costs with the minimum pumping cost

Figure 3. Cost bounds for homogeneous aquifer.

- ① Well cost.
- ② Well and pumping cost, minimum bound.
- ③ Well and pumping cost, maximum bound.
- ④ Well, maximum pumping, and failure costs.

Figure 3. Cost bounds for homogeneous aquifer.

Figure 4. Net income bounds for homogeneous aquifer,
with permeability equal to 4×10^{-4} [ft/sec].

- ① Maximum net income, for minimum pumping bound.
- ② Minimum net income, for maximum pumping bound.

Figure 4. Net income bounds for homogeneous aquifer, with permeability equal to 4×10^{-4} [ft/sec].

schedule. This schedule results in no well failure cost. Pumping costs increase smoothly from the lowest to the highest well capacities.

Curve 3, with the maximum pumping cost schedule, shows higher pumping costs than curve 2. As in curve 2, they increase smoothly up to $Q_c = 4.5$. However, at higher well capacities, they become more level, tending to decrease because of well failure and the resulting smaller volumes of water to be pumped. Curve 4 shows the effect of adding the penalty cost due to the water deficit resulting from well failure.

It is interesting to note the change of slope in going from curve 3 to curve 4 at $Q_c = 4.5$. The trend of curve 3 between $Q_c = 1.5$ and 4.5 is for a positive rate of change of total costs. However, in going to a well failure situation at $Q_c = 5.5$, the rate of change of total costs is negative. This suggests that when $s_{\max}$ approaches $s_{b \max}$, at larger well capacities, then the cost of adding more pump column is not worth the value of the additional water obtainable by the pump column addition. In this case, there would be a maximum economical pump setting below which additional benefits do not justify additional costs. This maximum, economical pump setting may be above or below $s_{b \max}$, depending on the aggregate effect of all aquifer conditions. The change of slope mentioned at the beginning of this paragraph would appear to indicate that at least for some Q_c values in the illustrative example, the maximum economical pump setting depth is above $s_{b \max}$.

Figure 4 shows the maximum and minimum bounds on net income. These bounds envelop the range of possible net incomes resulting from all possible stochastic, but simultaneous well pumping schedules that meet D by $t_{\max}$. Note that the cost analysis method says nothing about where the

net income is most likely to occur between the bounds. This is left for further analysis, or up to the judgment of the designer. Since those maintenance costs which have not been accounted for in the cost analysis method tend to increase with the number of wells to be maintained, the cost minimizing well field design from Figures 3 or 4 is at $Q_c = 3.5$.

Discussion of Results and Conclusions

Comparison with Previous Methods

Similarities between the method of the present study and the method of Hantush (1961) can be observed: (1) both methods assume homogeneous aquifer properties, and (2) they both assume simultaneous well operation. The method of Maddock (1972) is dissimilar in that it can involve a heterogeneous aquifer, given the areal distribution of aquifer properties. The wells, in his method, in general, operate non-simultaneously. The method of Rushton (1974) is similar in that it defines a well field design by a well density-capacity combination for wells located according to a uniform square grid.

Differences among the three methods can be compared under headings listed below. The particulars labelled (a) relate to the method of the present study; those labelled (b) relate to the method of Hantush (1961); those labelled (c) relate to the method of Maddock (1972); and those labelled (d) relate to the method of Rushton (1974).

Cost minimization:

(a) The sum of well construction and replacement costs plus pumping costs is minimized with respect to well density-capacity

combination. The minimum is found by comparing trial well field design costs.

(b) The sum of pipeline length costs plus pumping costs is minimized with respect to well spacing. The minimum is found directly by the classical calculus procedure.

(c) Pumping costs are minimized with respect to pumping schedules at individual wells. The minimum is found using a quadratic programming model which is coupled to an aquifer response model by means of an algebraic technologic function.

(d) No monetary costs are involved.

Design decisions specified before analysis:

(a) Whether a two-dimensional or a one-dimensional well grid will be used is specified before analysis, along with a single, constant, pipeline pressure head value (pipeline design is neglected).

(b) The number of wells and their individual capacities, the geometry of well locations, the geometry of the connecting pipeline network (having tree-type design, that is, no loops are allowed) and the geometry of connecting powerlines, are specified before analysis.

(c) Well locations are specified before analysis. The effect of pipeline pressure head at pump outlets on cost minimizing pumping schedules is neglected.

(d) The design decisions are the same as in (a).

Size of well field:

(a) The method is applicable to any number of wells and any size of aquifer area, subject to the assumptions of the method.

(b) The method is theoretically applicable to any finite number of wells in an infinite aquifer. The method was demonstrated (Hantush, 1961) in an illustrative example involving three wells.

(c) The method is theoretically applicable to any finite number of wells in either an infinite or finite aquifer. It was demonstrated (Maddock, 1972) in an illustrative example using three wells in a finite heterogeneous aquifer.

(d) Same comment applies as for (a).

Constraints:

(a) The minimum cost is constrained with respect to well failure by the addition of a penalty cost in proportion to the water deficit.

(b) The method is unconstrained and the minimum cost design would be infeasible if there were insufficient available drawdown to enable production goals to be met.

(c) The constraints are that seasonal production targets for the well field must be met and there is an upper limit to the pumping capacity [L^3] for each well that may not be exceeded.

(d) Design is constrained by the time allowed for pumping and by physical aquifer conditions.

Sensitivity analysis:

(a) The method shows actual costs over a range of designs, which indicate the sensitivity of costs to alternative designs other than the particular one that minimizes costs.

(b) The method gives the minimum cost well spacing directly, with no indication of cost sensitivity to changes in well spacing.

(c) Sensitivity of pumping costs to changes in pumping schedules from the cost minimizing ones is not considered by Maddock (1972).

(d) The method shows how volume of water recoverable varies with changes in length of pumping time and well density-capacity combination.

Application and Extension of the Method

Sensitivity analysis can be performed with respect to such variables as the operation decision variables and aquifer properties. Sensitivity analysis requires repetition of the calculations for each different set of conditions to be evaluated.

As the wells penetrate deeper into the aquifer, pumping costs decrease at a rate which is at first high, but decreases to zero at some great depth. Conversely, well construction costs increase with depth of penetration. There must be a cost minimizing depth of aquifer penetration. Also, there must be a maximum economical well depth as well as depth of pump setting, as discussed earlier, both of which depend on the economic value of the water pumped. It would appear that the method developed in this chapter could be extended to involve partial penetration analysis.

Conclusions

The first objective of this study, as stated in Chapter 1, is to develop a method for comparing uniform grid well field costs for alternative, well density-capacity combinations required to meet a given groundwater demand. In Chapter 2, such a method has been developed for a particular category of aquifer conditions chosen for analysis. The main

features of the method for the particular category are applicable to other categories of aquifer conditions as well.

The main features of the method are the following: (1) it involves a uniform grid of identically designed wells in the aquifer area of interest, and (2) it involves the design of one well and the related size of aquifer cell. The main assumptions of the method are the following: (1) the aquifer properties are homogeneous, and the aquifer storage, recharge and piezometric head conditions are practically the same for each cell; and (2) the wells operate simultaneously at equal discharge rates so that groundwater flow between aquifer cells will be negligible.

The most limiting assumption of the method is that of aquifer homogeneity. In Chapter 4, an extension of the method is described for taking into account lateral permeability variations within the aquifer. But first, in Chapter 3, a cell model is developed in order to predict aquifer response for the homogeneous aquifer case. This cell model is also useful in the heterogeneous aquifer case.

CHAPTER 3

AQUIFER RESPONSE MODEL: HOMOGENEOUS CASE

The purpose of this chapter is to develop an aquifer response model solution estimating the values of (1) total seasonal pumping energy consumption per well in terms of water volume raised through a pumping lift head, $\int_0^t |Q_w| s_a dt$ [L^4/well]; (2) total water volume pumped per well during pumping season, $\int_0^t |Q_w| dt$ [L^3/well], which is of interest, if well failure occurs; and (3) maximum drawdown in the well, $s_{\max}$ [L], in order to know what length of pump column and how much pump horsepower are required, for the well component cost function.

The following are requirements for the aquifer response model in order to be used in the analysis presented in Chapter 2. It must (1) have an impermeable outer boundary, (2) include the effect of changing transmissivity due to aquifer dewatering, (3) involve variable pumping rates in order to account for well failure, and (4) be fast enough, in terms of computer time required for solution, to allow sensitivity analysis with respect to changes in decision variables and to aquifer properties. In this chapter a solution for such a model is developed. Vertical flow components and delay time between lowering of the water table and release of water from storage are both neglected in the solution. Implications of this negligence, on the validity of the solution, are discussed at the end of this chapter. The assumptions

and theoretical techniques which are employed in the model solution have all been used previously by other authors to solve different models. The original contribution of this chapter lies in the selection of useful techniques and their application to obtain a solution to the required model. The solution obtained is not available from previous literature.

This chapter has four sections. In the first section, the aquifer response model is defined in terms of partial differential equations. The second section gives the solution to the model by using finite differences. In the third section, an analytic solution, for constant pumping rates, is presented. It is useful as a check on the finite difference solution results at early pumping time. In the last section, the usefulness and limitations of the solutions are discussed.

Mathematical Definition of Aquifer Response Model

In describing the aquifer model, note that up to this point, the aquifer model consists of any well from the field, located at the center of an impermeably walled, aquifer cell. The cell shape is polygonal in horizontal cross-section, such as hexagonal, square or equilateral triangular. If it were circular, flow to the well would be radial. This would result in a more concise model solution and shorten the computations. The Appendix compares drawdowns in a well pumping at the center of cells having different polygonal shapes but equal area. Drawdowns due to hexagonal, square and equilateral triangular boundaries are compared to the drawdown due to a circular boundary. At corresponding times after pumping started, the circular boundary produces the smallest drawdown, then come hexagonal, square and equilateral triangular boundaries, in

order of increasing drawdown. In each case, for a particular well discharge rate and aquifer transmissivity, departure of polygonal boundary drawdowns from drawdown produced with the circular boundary in time approached a constant, maximum value, this being smallest for the hexagonal boundary and largest for the equilateral triangular boundary. All of the maximum departures were found to be negligible for aquifer properties typical of well fields. Therefore, we can approximate any of the three polygonal cell boundary shapes by a circular boundary shape enclosing the same horizontal area.

Consider a cylindrical coordinate system with z -axis vertical, and horizontal radial plane. The aquifer model is a vertical cylinder of unconfined aquifer co-axial with the z -axis as shown on Figure 5. The horizontal base of the aquifer cylinder lies in the z equals zero plane. A well of radius r_w [L] is co-axial with the cylinder axis. The fully penetrating well screen extends throughout the initial saturated thickness, m_0 [L], of the aquifer cylinder. The screen offers no impedance to flow between the aquifer and the well. The field permeability, K , of the aquifer is homogeneous and isotropic. Compressibility of both water and aquifer are neglected, and aquifer storativity is equal to S_y . S_y is constant, occurs instantaneously, with decline in head, and is equal to connected porosity. The vertical cylindrical side, at radius r_e [L], and the horizontal base of aquifer cylinder are both impermeable. The upper boundary of saturated portion of aquifer is a "free surface," represented by the function $z_s(r,t)$ [L]. The free surface is a surface at atmospheric pressure. The water level in the well is $h_w(t)$ [L], where t is time since discharge of well started.

Figure 5. Axial section through cylindrical aquifer model (vertical dimension greatly exaggerated).

The following paragraphs develop a differential equation of groundwater flow for the model used here. A general statement of the continuity equation for fluid flow is that for some defined reference volume in a flow region, the mass of fluid flow entering the reference volume minus mass flow of fluid leaving reference volume equals the time rate of change of mass stored in reference volume. When the fluid is incompressible, as it is assumed to be here, mass may be replaced by volume.

Consider a cylindrical, annual reference volume, co-axial with the aquifer cylinder. This reference volume is bounded by the following surfaces: r , where $r_w \leq r < r_e$; $r+dr$, where $r < r+dr \leq r_e$; $z = 0$ and $z = z_s$. dr is a small element along the r -axis as shown on Figure 6. Let Q_r [L^3/T well] represent the total flow rate of fluid crossing a vertical cylindrical surface at radius r in the aquifer. Q_r is positive when flow is directed in the positive r direction. Let the piezometric head at any point in the flow system be $h(r,z,t)$.

Darcy's law may be stated as follows:

$$Q = - K \iint_A \nabla h \cdot \hat{n} dA \quad (3.1)$$

where A = some surface area defined within the region of flow;

Q = the total net flow rate across this surface, defined as positive in the positive r direction;

∇h = the head gradient across dA ; and

$\hat{n}$ = the unit normal to dA and directed in the same sense as the positive net flow direction of Q .

Figure 6. Right half of axial section through cylindrical aquifer model, showing trace of cylindrical reference volume.

For a case of radial symmetry, as shown on Figure 6, Equation (3.1) may be rewritten as follows to give the flow entering the reference volume.

$$Q_r = 2\pi r \int_0^{z_s} \left\{ -K \frac{\partial h}{\partial r} \right\} dz = -2\pi K r \int_0^{z_s} \frac{\partial h}{\partial r} dz .$$

Let $\int_0^{z_s} \frac{\partial h}{\partial r} dz = z_s \overline{\frac{\partial h}{\partial r}}$, where $\overline{\frac{\partial h}{\partial r}}$ is the average of the components of the head gradient in the r direction, averaged over the vertical section at radius r from $z = 0$ to $z = z_s$. Thus, the volume flow entering the reference volume is

$$Q_r = -2\pi K r z_s \overline{\frac{\partial h}{\partial r}} ,$$

and the volume flow leaving the reference volume is

$$\begin{aligned} Q_{r+dr} &= -2\pi K \{r+dr\} \left\{ z_s \overline{\frac{\partial h}{\partial r}} + \frac{\partial}{\partial r} \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} dr \right\} \\ &= -2\pi K \left\{ r z_s \overline{\frac{\partial h}{\partial r}} + r \frac{\partial}{\partial r} \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} dr + z_s \overline{\frac{\partial h}{\partial r}} dr + \frac{\partial}{\partial r} \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} \{dr\}^2 \right\} . \end{aligned}$$

The time rate of change of volume stored in the reference volume is

$$Q_r - Q_{r+dr} = 2\pi r dr S_y \frac{\partial z_s}{\partial t} .$$

Cancelling pairs of numerically equal terms of opposite sign and neglecting terms in $\{dr\}^2$ gives

$$2\pi K \left\{ r \frac{\partial}{\partial r} \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} dr + z_s \overline{\frac{\partial h}{\partial r}} dr \right\} = 2\pi r dr S_y \frac{\partial z_s}{\partial t} .$$

Dividing through by $2\pi K dr$ gives

$$r \frac{\partial}{\partial r} \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} + \left\{ z_s \overline{\frac{\partial h}{\partial r}} \right\} = r \frac{S_y}{K} \frac{\partial z_s}{\partial t} , \text{ or}$$

$$\frac{1}{r} \frac{\partial}{\partial r} \left\{ r z_s \overline{\frac{\partial h}{\partial r}} \right\} = \frac{S_y}{K} \frac{\partial z_s}{\partial t} . \quad (3.2)$$

This is the differential equation for the model described.

Applying the Dupuit assumptions to Equation (3.2) renders it more tractable to solution. Dupuit assumed (Todd, 1959, p. 79) that (1) the velocity of flow is proportional to the tangent of the hydraulic gradient instead of the sine, and (2) the flow is horizontal and uniform everywhere in a vertical section. By assumption (2), vertical components of head gradient are zero and therefore the "Dupuit head," symbolized by $h(r,t)$ [L], must equal the assumed height of the free surface everywhere on a vertical section. Also by assumption (2), $\frac{\partial h}{\partial r}$ is the assumed value of $\overline{\frac{\partial h}{\partial r}}$.

Applying the Dupuit assumptions to Equation (3.2) results in the expression

$$\begin{aligned} \frac{1}{r} \frac{\partial}{\partial r} \left\{ r h \frac{\partial h}{\partial r} \right\} &= \frac{S_y}{K} \frac{\partial h}{\partial t}, \text{ or} \\ \frac{1}{r} \frac{\partial}{\partial r} \left\{ r \frac{\partial h^2}{\partial r} \right\} &= \frac{2S_y}{K} \frac{\partial h}{\partial t}. \end{aligned} \quad (3.3)$$

This is the approximate differential equation for the aquifer response model.

Defining the boundary conditions and initial conditions as follows completes the mathematical definition of the model. The boundary condition on surface $r = r_e$ and $z = 0$ is that no flow crosses these surfaces. Thus, on $r = r_e$, in terms of exact head, $\frac{\partial h}{\partial r} = 0$, and in terms of approximate head,

$$\frac{\partial h}{\partial r} = 0. \quad (3.4)$$

Impermeability of aquifer base is implicit in the derivation of the differential Equation (3.2), and this characteristic carries through to the

approximate differential Equation (3.3). The pertinent boundary condition on the free water surface is that no flow crosses it; this also is implicit in the derivation of Equation (3.2) and carries through to Equation (3.3). The boundary condition along the well bore is that $-K2\pi r_w z_s \frac{\partial h}{\partial r}$ must equal well recharge rate, $Q_w(t)$. Applying the Dupuit assumptions, this boundary condition becomes

$$\begin{aligned} -K2\pi r_w h_w \frac{\partial h}{\partial r} \bigg|_{r_w} &= Q_w, \text{ or} \\ r_w \frac{\partial h^2}{\partial r} \bigg|_{r_w} &= \frac{Q_w}{-\pi K}. \end{aligned}$$

Since r_w is very small relative to r_e , we may make the following substitution

$$\lim_{r \rightarrow 0} \left(r \frac{\partial h^2}{\partial r} \right) = \frac{Q_w}{-\pi K}. \quad (3.5)$$

The sign of Q_w is negative when it represents well discharge, so that the above limit is positive for a discharging well. Finally, the initial condition is

$$h(r,0) = m_0. \quad (3.6)$$

Finite Difference Solution

This section presents a finite difference numerical solution to Equation (3.3), subject to the boundary conditions given by Equations (3.4) and (3.5) and to the initial condition, Equation (3.6). Both space and time are divided into finite differences in the aquifer cell response model. The model solves for unknown heads in the aquifer and unknown

discharge if head in well is specified. It starts with given initial head conditions, and advances through consecutive time steps solving for the unknown heads in each time step. Letting transmissivities for any time step be approximated by those of the immediately preceding time step results in finite difference equations which are linear in the unknown heads. Consequently, the equations may be solved for the unknown heads by the Gauss elimination method.

The model comprises a number of concentric annuli of aquifer surrounding the well, such as Figure 7 shows in cross-section. Since the head gradient due to well pumping is approximately proportional to the logarithm of r , the relative thicknesses of the annuli are made proportional to the logarithmic base, e , raised to the exponent r . However, in Figure 7, the annuli are shown all having equal thickness in order to simplify labelling the diagram.

Next, let us consider the nodes of the aquifer cell model. Each annulus contains one node. In general, finite difference model nodes can represent points, lines or surfaces in space. If the differential equations used in any model are expressed explicitly in three independent space variables, such as (x,y,z) or (r,θ,z) , then the finite difference model nodes represent points in space. If only two independent space variables, such as (x,y) or (r,z) are involved explicitly in the equations, then the nodes represent, respectively, straight lines parallel to the z -axis and circles in the place of θ , concentric with the z -axis. When x or r is the only explicit space variable in the equation, then the nodes represent, respectively, planes parallel to the y - and z -axes, and cylindrical surfaces co-axial with the z -axis. In the aquifer cell

Figure 7. Right-hand side of axial section through finite difference representation of aquifer model.

response model employed here, use of radial symmetry of flow, and the Dupuit assumptions, results in Equations (3.3) to (3.6), which have only one explicit, independent space variable, r . The resulting finite difference model nodes are, therefore, cylindrical surfaces co-axial with the z -axis and well, one node being located within each annulus. The nodes are spaced in proportion to e^r in just the same manner as the annuli thicknesses; however, Figure 7 shows them as being uniformly spaced for simplicity.

The aquifer cell finite difference model can contain any number, n , of annuli; Figure 7 shows 8 annuli. The annuli and their nodes are referenced by the subscript i . The inner and outer boundaries of each annulus are designated by subscripts, $i - \frac{1}{2}$ and $i + \frac{1}{2}$, respectively. The smallest annulus, which includes the well, is numbered 1. Its inner boundary, designated by the subscript $\frac{1}{2}$, has zero radius, that is, it coincides with the z -axis. Node 1 coincides with the well radius. Storage within the well, above aquifer specific yield, is neglected. The outer boundary, denoted by $n + \frac{1}{2}$, of the outermost, n -th, annulus, coincides with the model's outer cylindrical boundary of no-flow. The head, $h_{i,j}$ [L], within the i -th annulus, is constant over the j -th time interval, Δt_j . S_{yi} refers to the specific yield of the i -th annulus, while K_i refers to the permeability between node i and node $i + 1$.

Digital computers do not reference stored quantities explicitly by mixed number subscripts, but require integer subscripts. Since it is necessary to reference the radii of both nodes and annuli boundaries, where the latter have mixed number subscripts in terms of i , we make all

subscripts on r into integers by multiplying the subscripts expressed in terms of i by 2 and refer to them by the subscript k (see Figure 7).

The following formula gives annuli nodes and boundary radii such that they are spaced in proportion to e^r . The first expression is with i subscripts, while in the second, k subscripts replace the i subscripts.

$$r_{\frac{1}{2}} = 0, \quad r_i = r_w \left\{ \frac{r_e}{r_w} \right\}^{\left\{ \frac{i-1}{n-\frac{1}{2}} \right\}},$$

where $i = 1, 1\frac{1}{2}, 2, 2\frac{1}{2}, \dots, n + \frac{1}{2}$.

$$r_1 = 0, \quad r_k = r_w \left\{ \frac{r_e}{r_w} \right\}^{\left\{ \frac{k-2}{2n-1} \right\}}, \quad (3.7)$$

where $k = 2, 3, \dots, 2n + 1$. To avoid confusion, we will continue with i subscripts in developing the finite difference equations.

It is easier to develop the finite difference equations for the model used here by beginning with considerations of mass balance in a given annulus, than by starting with the partial differential equations (3.3) to (3.6) and going straight to the corresponding finite difference equations. As a check, it will subsequently be shown that the finite difference equations resulting from basic considerations do represent the partial differential equations (3.3) to (3.6).

Let us begin by defining transmissivity, $T_{i,j}$ [L^2/T], between node i and node $i+1$, and during time interval Δt_j , by the following formula

$$T_{i,j} = K_i \sqrt{h_{i,j} \times h_{i+1,j}} \quad (3.8)$$

Equation (3.8) gives transmissivity between the nodes i and $i+1$ as being equal to permeability between them multiplied by an effective saturated thickness equal to the geometric mean of the saturated thickness at nodes i and $i+1$. The geometric mean gives more accurate results than the arithmetic average, especially when dealing with steep gradients near pumping centers (Prickett and Lonquist, 1971). However, since the nodes of the model used here are spaced proportionally to e^r , in order to approximately equalize head differences between nodes, and since head differences between adjacent nodes are small relative to the head values themselves (except in cases of very low permeability or extreme dewatering), then arithmetic averages of adjacent heads will generally be nearly equal to the geometric means. Since it is faster to compute the arithmetic averages than the geometric means, it may be advantageous to use the former, in order to save computer costs. In any case, the latter, geometric means were used in the model here. Switching to arithmetic means is a simple task.

With regard to further nomenclature, note that when either subscript i or j is dropped from $h_{i,j}$, then i and j are implied, that is, h implies $h_{i,j}$. If values other than i and j are intended, then these values are explicitly subscripted to h , for example, head in the $i + 1$ -th annulus during time interval Δt_{j-1} is $h_{i+1,j-1}$.

Recharge from ground surface can be included as follows. This component of flow into any i -th annulus is symbolized by q_i [L^3/T]. For the first annulus, which contains the well, the well pumping rate is simply a negative recharge rate. Thus, during any Δt_j , $q_1 = Q_{wj}$.

The principle of conservation of mass can be simply stated as "total flow in, minus total flow out, equals change of storage inside." For any time interval, Δt_j , and any i -th annulus, the following relationships are evident.

$$\text{Total flow in} = -2\pi r_{i-\frac{1}{2}} T_{i-1,j} \left\{ \frac{h_{i-1}-h}{r_i-r_{i-1}} \right\} \Delta t_j + q_i \Delta t_j \quad (3.9)$$

$$\text{Total flow out} = -2\pi r_{i+\frac{1}{2}} T_{i,j} \left\{ \frac{h_{i+1}-h}{r_{i+1}-r_i} \right\} \Delta t_j \quad (3.10)$$

$$\text{Change of storage inside} = \pi \{ r_{i+\frac{1}{2}}^2 - r_{i-\frac{1}{2}}^2 \} S_{yi} \{ h_{i-1} - h \} \quad (3.11)$$

$T_{i,j}$ is an unknown in the j -th time interval. However, from the previous time step when head values are known, $T_{i,j-1}$ is known. Therefore, let $T_{i,j}$ be approximated by $T_{i,j-1}$. By assembling the conservation of mass equation using Equations (3.9), (3.10) and (3.11), substituting $T_{i,j-1}$ for T_i and simplifying, the following set of equations may be obtained.

$$A_i h_{i-1} + B_i h + C_i h_{i+1} = D_i h_{j-1} - \frac{q_i}{2\pi} \quad (3.12)$$

for $i = 1, 2, 3, \dots, n$;

$$\text{where } A_i = \left\{ \frac{r_{i-\frac{1}{2}}}{r_i - r_{i-1}} \right\} T_{i-1,j-1} ;$$

$$B_i = -(A_i - D_i + C_i) ;$$

$$C_i = \left\{ \frac{r_{i+\frac{1}{2}}}{r_{i+1} - r_i} \right\} T_{i,j-1} ;$$

$$D_i = -\left\{\frac{r_{i+1/2}^2 - r_{i-1/2}^2}{2\Delta t_j}\right\} S_{yi} .$$

In order to satisfy the boundary conditions given by Equations (3.4) and (3.5), we can set

$$K_n = 0 \quad (3.13)$$

and

$$q_1 = Q_w , \quad q_i = 0 , \quad \text{for } i = 2, 3, \dots, n . \quad (3.14)$$

In order to satisfy the initial condition given by Equation (3.6), we can set

$$h_{i,0} = m_0 , \quad \text{for } i = 1, 2, 3, \dots, n . \quad (3.15)$$

With these substitutions made, Equation (3.12), together with Equations (3.13), (3.14) and (3.15) form the finite difference aquifer cell model. $h_w(t_j) = h_1$, and $Q_j = q_1$. All terms on the right-hand side of Equation (3.12) are known, while only the heads on the left-hand side are unknown. Note that $A_1 = 0$, because $r_{1/2} = 0$, and that $C_n = 0$, because $K_n = 0$, and hence, $T_{n,j-1} = 0$. This agrees with there being no annuli corresponding to $i = 0$ and $i = n+1$.

Let us now show that Equations (3.12) to (3.15) are the finite difference equations corresponding to the partial differential equations (3.3) to (3.6). We can begin by expressing Equation (3.3) in finite difference form. For this purpose, it is useful to write it as follows:

$$\partial\{rKh\frac{\partial h}{\partial r}\} = r\partial r S_y \frac{\partial h}{\partial t} . \quad (3.16)$$

On the right-hand side, we let the radius of the i -th node, r_i , be given by $\{r_{i+1/2} + r_{i-1/2}\}/2$. This substitution gives more accurate results

than those from retaining the simple r_i value, when the area per node increases with r , as it does in the model employed here. Kh , evaluated between node i and node $i+1$, becomes $T_{i,j-1}$ by letting $T_{i,j-1}$ approximate $T_{i,j}$ as before. Thus, for the i -th annulus,

$$\begin{aligned} & r_{i+\frac{1}{2}} T_{i,j-1} \left\{ \frac{h_{i+1}-h}{r_{i+1}-r_i} \right\} - r_{i-\frac{1}{2}} T_{i-1,j-1} \left\{ \frac{h-h_{i-1}}{r_i-r_{i-1}} \right\} \\ &= \left\{ \frac{r_{i+\frac{1}{2}} + r_{i-\frac{1}{2}}}{2} \right\} \{ r_{i+\frac{1}{2}} - r_{i-\frac{1}{2}} \} S_{yi} \left\{ \frac{h-h_{j-1}}{\Delta t_j} \right\}. \end{aligned} \quad (3.17)$$

Simplifying Equation (3.17) and letting $i = 1, 2, \dots, n$, results in a set of equations identical to (3.12) with the q_i 's set to zero.

The cell no-flow outer boundary condition is satisfied by setting $K_n = 0$ in Equations (3.12) and (3.17). For the boundary condition at the well, we first express Equation (3.5) as follows:

$$\lim_{r \rightarrow 0} \{ rKh \frac{\partial h}{\partial r} \} = \frac{Q_w}{-2\pi}.$$

For the limiting value of r as r goes to zero, we take $r = r_{\frac{1}{2}}$. The corresponding value of Kh is $T_{1,j-1}$. Thus,

$$r_{\frac{1}{2}} T_{1,j-1} \left\{ \frac{h_2-h_1}{r_2-r_1} \right\} = \frac{Q_w}{-2\pi}. \quad (3.18)$$

It can be shown that Equation (3.12), together with Equation (3.14), satisfies the boundary condition of Equation (3.5) as expressed by Equation (3.18), as follows. The innermost annulus, which contains the well, is represented by the equation for $i=1$ in Equation (3.12). We allow that the storage in this first annulus is negligible with respect to

storage in the rest of the aquifer cell, so that insignificant change results if D_1 is set equal to zero. Thus, inserting $q_1 = Q_w$, $r_{1/2} = 0$, and $D_1 = 0$ into the equation for $i=1$, gives Equation (3.18). To this point it has been shown that Equation (3.12), together with Equations (3.13) and (3.14), are finite difference equations representing Equation (3.3) and its boundary conditions given by Equations (3.4) and (3.5). Finally, to include the initial condition given by Equation (3.6), the initial heads, $h_{i,0}$, of the finite difference equations were set equal to m_0 in Equation (3.15).

A computer program solves the set of Equations (3.12), together with (3.13), (3.14) and (3.15), for the unknown heads at each time interval, Δt_j , consecutively, beginning with Δt_1 , and continuing until the end of the pumping time is reached. If well failure occurs during pumping, then the equations for $i=1$ and 2 must be rearranged to solve for the unknown, q_1 , in terms of the known, $h_1 = h_{\min}$, where $h_{\min} = m_0 - s_{\max}$. Accordingly, these equations become, respectively,

$$\frac{1}{2\pi} q_1 + C_1 h_2 = D_1 h_{1,j-1} - B_1 h_{\min}$$

$$\{0\} q_1 + B_2 h_2 + C_2 h_3 = D_2 h_{2,j-1} - A_2 h_{\min} - \frac{q_2}{2\pi}$$

The remaining equations for $i = 3, 4, \dots, n$, remain unchanged after well failure.

Time increments, Δt_j , should be small to begin with, and may be longer as the shape of the cone of depression becomes more steady. One procedure for controlling time increments is to let the first be equal to, for example, 100 seconds, and succeeding time increments increase by the factor 1.2 (Prickett and Lonquist, 1971).

Analytical Solution

The analytical solution presented here serves as a check on the results of the finite difference solution, for early pumping times when dewatering of the aquifer is not severe, and before well failure has occurred. A further modification of Equation (3.3) is necessary in order to apply the analytical solution method to be used here. This solution method is after one given by Nind (1964) in lecture notes. The method given by Nind adapted the Theis equation (Theis, 1935) by means of the Dupuit assumptions to represent unconfined flow toward a single well in a horizontally infinite aquifer model. The solution presented here employs an analogous equation for a cylindrically bounded aquifer.

Multiply the right-hand side of Equation (3.3) by h/h to obtain

$$\frac{1}{r} \frac{\partial}{\partial r} \left\{ r \frac{\partial h^2}{\partial r} \right\} = \frac{S_y}{Kh} \frac{\partial h^2}{\partial t} . \quad (3.19)$$

If a constant, m , replaces h in the denominator of the right-hand side, then the resulting differential equation is solvable. Letting m represent an average value of h might allow this substitution to be interpreted as assuming constant aquifer transmissivity, Km , which for thick aquifers and early pumping times, is a reasonable assumption. However, solving for h^2 , and not for h , does partially account for aquifer dewatering and consequent change of aquifer transmissivity.

The average value of h in space, all the way out to r_e , even at early pumping times when the cone of depression is small, is

$$m_s = \{m_0 + Q_w t / \{\pi r_e^2 S_y\}\} [L]$$

If m replaces h , it must represent h not only in space but also in time.

Therefore, it is better to use the average value of h in both space and time, that is,

$$m = \{m_0 + Q_w t / \{2\pi r_e^2 S_y\}\} [L] \quad (3.20)$$

After substituting (3.20) into (3.19), the problem can be stated as follows:

Solve the differential equation

$$\frac{1}{r} \frac{\partial}{\partial r} \left\{ r \frac{\partial h^2}{\partial r} \right\} = \frac{S_y}{Km} \frac{\partial h^2}{\partial t} \quad (3.21)$$

subject to the boundary conditions

$$\left. \frac{\partial h^2}{\partial r} \right|_{r_e} = 0 \quad (3.22)$$

and

$$\lim_{r \rightarrow 0} \left\{ r \frac{\partial h^2}{\partial r} \right\} = \frac{Q_w}{-\pi K} = \frac{2Q_w m}{-2\pi Km} \quad (3.23)$$

and to the initial condition

$$h^2 = m_0^2 \quad \text{at } t = 0. \quad (3.24)$$

It should be remembered that m always equals the constant, $\{m_0 + Q_w t / \{2\pi r_e^2 S_y\}\}$, where t is the time at which a particular value of h^2 (where $h = h(r)$) is to be calculated from the solution. When water is being pumped out of the well, its discharge rate, Q_w , is negative.

This problem may be compared to another similar problem which was solved by Muskat (1946, p. 657). Using an expression similar to that given by Witherspoon and others (1967, p. 105), Muskat's problem and solution are as follows. Solve the differential equation

$$\frac{1}{r} \frac{\partial}{\partial r} \left\{ r \frac{\partial h}{\partial r} \right\} = \frac{S}{T} \frac{\partial h}{\partial t} ,$$

subject to the boundary conditions,

$$\left. \frac{\partial h}{\partial r} \right|_{r_e} = 0 , \text{ and } \lim_{r \rightarrow 0} \left\{ r \frac{\partial h}{\partial r} \right\} = \frac{Q_w}{-2\pi T} ,$$

and to the initial condition

$$h = h_0 \quad \text{at } t = 0 .$$

In this case only, S equals aquifer artesian storage coefficient, and T equals aquifer transmissivity. The initial static peizometric head, h_0 , is constant in space.

The solution is

$$P_D = -\{\ln(r_D) + \frac{1+4t_D}{2r_D^2} - \frac{3}{4} - 2 \sum_{n=1}^{\infty} \frac{J_0(\frac{x_n}{r_D}) \exp\{-\{\frac{x_n}{r_D}\}^2 t_D\}}{x_n^2 J_0^2(x_n)}\} \quad (3.25)$$

where $P_D = \frac{2\pi T\{h_0 - h\}}{Q_w} ,$

$$t_D = \frac{Tt}{r^2 S} ,$$

$$r_D = \frac{r_e}{r} , \text{ and}$$

$$J_1(x_n) = 0 .$$

J_0 and J_1 represent Bessel functions of the first kind, and respectively, orders zero and one.

Here, as throughout this report, negative values of Q_w represent well discharge.

The solution to the aquifer response model may be found by analogy with Muskat's problem and solution:

Replace h of Muskat's solution by h^2 .

$$\begin{array}{ccccccc} " & S & " & " & " & " & S_y. \\ " & T & " & " & " & " & Km. \\ " & Q_w & " & " & " & " & 2Q_w m. \\ " & h_0 & " & " & " & : & m_0^2. \end{array}$$

Then the desired solution to Equations (3.21) to (3.24) is Equation (3.25) but with

$$P_D = \frac{2\pi Km\{m_0^2 - h^2\}}{2Q_w m},$$

$$t_D = \frac{Kmt}{r^2 S_y},$$

$$r_D = \frac{r_e}{r}, \text{ and}$$

$$J_1(x_n) = 0.$$

Substituting $h_w = h$, and $r_w = r$, and simplifying yields the head at the well, at any instant of time, t ,

$$h_w = \{m_0^2 - \frac{Q_w}{K} P_D\}^{\frac{1}{2}}. \quad (3.26)$$

The corresponding aquifer drawdown, s_a , is $s_a = m_0 - h_w$.

Discussion of Results

Comparison of Finite Difference and Analytic Solutions

It is useful to be able to compare drawdown results from the finite difference solution with those from the analytic solution. At early times the results should be almost identical. Later, as dewatering progresses and $h(r)$ departs significantly from its average value in space and time, the results from the finite difference solution are expected to agree with the still unknown, true solution to Equations (3.3) to (3.6), more accurately than results from the analytical solution.

Computer programs were written for both of the approximate solutions. They are in FORTRAN IV programming language and were run on CDC 6400 computers. The results from the finite difference solution agree closely with those of the analytic solution at early times. At longer pumping times, the finite difference solution drawdown at the well is greater than that from the analytic solution. Presumably, this is because the finite difference solution does not involve the assumption of "constant transmissivity" (see Equation (3.19)), and so incurs greater reduction in transmissivity than the analytic solution, due to dewatering close to the well at long pumping time. Possible errors in the results, due to truncation in going to the finite difference equations and due to rounding-off of numbers in the computer, were judged by the writer to be negligible because of close agreement between the results from the finite difference and analytic solutions. However, it is suspected that round-off errors increase if h_1 approaches zero.

Dupuit Assumptions

Theory of groundwater flow involving the Dupuit assumptions has long been available, and has been discussed extensively by Muskat (1946). According to Jacob (1950), Dupuit's theory holds approximately for flow in unconfined systems whose range of depth of flow is also not too great. The following arguments are presented in support of the use of the Dupuit assumptions in obtaining a solution to the aquifer response model required here:

1. The aquifer permeability is assumed to be isotropic. That is, vertical permeability is large enough that flow of water from the water table downward to lower levels in the aquifer is not severely impeded.
2. For practical well spacings and for aquifer thicknesses usually penetrated by wells, the horizontal distance of flow is four or more times greater than the vertical distance of flow.
3. For the next argument, it is first necessary to express Equation (3.26) in a different form. Noting that $m_0 - h_w = s_a$, Equation (3.26) can be rearranged to read

$$s_a - \frac{s_a^2}{2m_0} = \frac{Q}{4\pi K m_0} \{2P_D\} .$$

This equation is similar to the Theis equation (Theis, 1935) except for the subtractive factor, $s_a^2/2m_0$. According to Jacob (1950, p. 385), when the Theis equation is modified by inclusion of the same subtractive factor, it may be used to calculate transmissivity and storage coefficients from pump tests of

unconfined aquifers, with fair assurance, when the drawdowns are as much as 25 percent of the initial depth of flow. The subtractive factor for the Theis equation can be derived using the same principles as used in the derivation of Equation (3.26). The only difference is that in the Theis model, the aquifer external boundary is at an infinite radial distance from the well, so that m always equals m_0 .

4. It was shown by Charny (1951) that the Dupuit theory will result in correct solutions for certain unconfined flow models involving a seepage face. In particular, the Dupuit assumptions predict the correct well drawdown for the special case involving all of the following conditions: (a) the flow is steady state through an unconfined, cylindrical, homogeneous aquifer with horizontal, impermeable base; (b) flow enters the aquifer from a surrounding, constant head reservoir; and (c) the well is co-axial with, and fully penetrates the aquifer cylinder, and it is pumped at a constant rate. The correct well drawdown is given, although the Dupuit assumptions take no account of the existence of a seepage face or of vertical components of flow. In the aquifer model of this chapter, the source of water is at the water table, not on the external boundary. However, there are some similarities between the two models. Both models relate transmissivity to Dupuit head. In the transient model, after several days of pumping, conditions close to the well are nearly in a steady state. In both models, the water table slope is steepest next to the well, and most of the flow through this region comes to the

well from beyond it. Consequently, if the Dupuit assumptions result in a solution that is correct in spite of the seepage face and vertical flow components in the steady state model, then the solution presented in this chapter must at least partially allow for these same phenomena which occur in the transient model.

Note that improved aquifer modelling techniques can be substituted in this well field design analysis method. For example, transient, unconfined groundwater flow models have been developed by Neuman and Witherspoon (1971), Cooley (1971, 1972), and Neuman (1972, 1973, 1974). While these models account for vertical flow components in their theory, their disadvantage as seen by the writer, is the additional computer time they require. Computer time can be an important factor when many cases must be analyzed.

Delayed Drainage

The aquifer response model assumes instantaneous release of water stored in the aquifer voids, with lowering of head; thus, it neglects the effect of delayed drainage. The effect of delayed drainage on well pumping level is most significant during the first few hours or days of pump operation. Thus, delayed drainage is a significant factor in analysis of pump tests of unconfined aquifers. When pumping continues for weeks or months, the rate of head drawdown in the aquifer becomes slow enough so that delayed drainage usually can, after several days, keep up with the rate of head decline. Under these circumstances, the effect of delayed drainage on the overall seasonal pumping cost is assumed to be negligible. However, pumping may not be continuous over

long periods of time. With intermittent daily well operation, previously dewatered parts of the aquifer close to the well are reflooded and then drained again at intervals of perhaps a few hours. In this case, delayed drainage might result in a significant increase in seasonal pumping cost over that which would occur if drainage were instantaneous. However, in the judgment of the writer, it would be most unlikely that intermittent well operation with delayed drainage, would produce a total seasonal pumping cost significantly greater than the maximum pumping cost bound given by the aquifer response model which assumes instantaneous release from storage.

Pump Operating Characteristics

With most types of pumps used in well fields, discharge rate and efficiency do not remain constant under varying head conditions. If curves of these operating characteristics of the pumps to be used are available, this information can be incorporated with the finite difference solution to give a more accurate estimate of pumping energy costs. However, such incorporation was not done in this study.

Surface Recharge

Suppose that the aquifer response model were modified so as to involve areally uniform recharge during the pumping season, and that a recharge rate versus time function could be estimated. The finite difference solution can represent such a model with designation of the q_i values for each annulus and each time increment, in accordance with the recharge function.

Conclusions

A solution to the aquifer response model whose requirements were stipulated at the beginning of this chapter has been found. Vertical flow components are neglected in the solution, but this should not affect the results unless the aquifer permeability is anisotropic, with a vertical permeability, let us say, less than one quarter of the horizontal permeability.

In the next chapter, the well field design method of Chapter 2 is extended to involve calculation of the average cost with respect to uncertainty in lateral variations of permeability among aquifer cells. The calculations require many numerical solutions of the aquifer response model. The reader will appreciate the advantage of computational speed as a property of the aquifer response model in this application.

CHAPTER 4

HETEROGENEOUS PERMEABILITY

The objective of this chapter is to take heterogeneous permeability in the aquifer into account in the well field design method. A homogeneous permeability value is assumed within each aquifer cell, but the values vary among different cells. Relative frequencies of the values are defined in accord with some probability density function (pdf), without regard for the locations of the permeability values among the cells. This enables calculation of average cost of wells, which evaluates a given well density-capacity combination.

The following implications arising from the method and assumptions are examined. Different permeability values among adjacent cells cause inter-cell flow. Bounds on its effects can be estimated. Non-simultaneous operation of the wells causes inter-cell flow. Its effects can be estimated. Well costs for all cell permeabilities are averaged in accord with their frequencies in order to evaluate a given design.

Form of PDF

Very few data are available on the pdf's applicable to real aquifers. Supkow (1972) postulated that there should be an exponential relationship between transmissivity of an alluvial aquifer and the area of the aquifer having the specified transmissivity. His reasoning was

based on Horton's laws of stream orders. The pdf of transmissivity, τ [L^2/T], over an entire aquifer was postulated to be

$$\begin{aligned} f(\tau) &= \frac{1}{\tau_m} e^{-\tau/\tau_m}, & \text{for } \tau > 0, \\ f(\tau) &= 0, & \text{otherwise, and} \\ \tau_m &= \text{mean transmissivity of the aquifer.} \end{aligned} \quad (4.1)$$

To support this hypothesis, Supkow showed that the 2500 nodal transmissivity values derived from the digital computer model of the Tucson aquifer gave a close fit with an exponential pdf, whose mean is the arithmetic mean of the transmissivity values used in the model. Each transmissivity value represented an area of one quarter section.

The method for well field design applies with any form of pdf. Therefore, the exponential pdf can be used to illustrate the method. The permeability values needed to calculate declining transmissivities with aquifer dewatering, are assumed to equal the initial transmissivities divided by initial saturated thickness. The frequency distribution of cell permeability values in the sample realized after well field construction, is assumed to be the same as in the parent pdf, regardless of the number of wells (and cells) in the field. The parent pdf for permeability is

$$\begin{aligned} f(K) &= \frac{1}{K_m} \{e^{-K/K_m}\}, & \text{for } K > 0, \\ f(K) &= 0, & \text{otherwise, and} \\ K_m &= \text{mean permeability of the aquifer.} \end{aligned} \quad (4.2)$$

Average Value Calculation

The average value of costs with respect to the permeability pdf can be calculated as shown below, and then plotted as in the illustrative example of Chapter 2.

Let the permeability be uniform within each aquifer cell, but different among cells. Let the permeability pdf, $f(K)$, for the cells be given by Equation (4.2). For constant decision variable values, each value of cell K will result in some well field cost, C [\$/year ft²], according to the procedure given in Chapter 2. We can express this cost, being a function of K , as $C(K)$. The average value of C over all K , $E_K(C)$, is given by the equation

$$E_K(C) = \int_{-\infty}^{+\infty} C(K)f(K)dK . \quad (4.3)$$

Since the designer is assumed to have no knowledge of the spatial distribution of permeability over the aquifer area, this equation provides an expected cost at every cell in the area. However, the sample of cell K values realized after well field construction is assumed to have the same distribution as the parent pdf. Therefore, when $E_K(C)$ from Equation (4.3) is multiplied by the number of cells in the aquifer area, it will give the theoretically true value of the total well field costs for the aquifer area. Since the spatial distribution of permeability is unknown, the expected cost at each cell in the aquifer area over which the pdf applies, equals the average cost.

Discretization of Expected Value Calculation

Since Equation (4.2) is continuous, with non-zero slope for positive, finite permeability values, there is an infinite number of possible aquifer cell permeability values, and a corresponding infinite, and intractable, number of possible cost outcomes to calculate. In order to reduce the calculations, the range of all possible permeability values can be divided into a tractable number of discrete intervals. Costs are assumed to be constant within each permeability interval, and to be equal to those resulting from the mid-interval permeability value. Let the probabilities, P_i , of the mid-interval permeabilities be given by the following formula:

$$P_i = \int_{K_i}^{K_{i+1}} f(K) dK = \{e^{-K_i/K_m} - e^{-K_{i+1}/K_m}\}, \quad (4.4)$$

where K_i = permeability at beginning of interval, and

K_{i+1} = permeability at end of interval.

The interval probabilities are shown on Figure 8, for an assumed mean permeability value of $K_m = 4 \times 10^{-4}$ [ft/sec]. Let the well field cost due to the i -th mid-interval permeability be C_i . Then the expected value of costs is

$$E(C) = \sum_i C_i P_i. \quad (4.5)$$

The uniform permeability distribution, considered in Chapter 2, is a special form of pdf, such that $P(K) = 1$ for K equal to the specified uniform value, and $P(K) = 0$ otherwise. $P(K)$ is the probability of K . Accordingly, only one permeability interval was needed, with $P_1 = 1$, and

Figure 8. Permeability intervals, showing interval probabilities.

its associated cost being C_1 . In terms of the analysis in this chapter, the expected value of costs for a given set of decision variable values in the example of Chapter 2, is

$$E(C) = C_1 \times P_1 = C_1 .$$

Inter-Cell Flow

Different permeabilities in adjacent cells will affect no-flow boundaries around each cell. Drawdown cones of depression in higher permeability cells are flatter, and reach their cell boundaries sooner, than those in lower permeability cells. In this analysis, all wells are assumed to operate simultaneously at the same pumping rates, unless well failure occurs. If well failure occurs in any well during a pumping interval, the well produces at whatever rate is possible with its drawdown held at its pump intake elevation. Under these conditions, heads at cell boundaries of lower permeability cells will be equal to or greater than cell boundary heads around higher permeability cells. As a result, some groundwater will flow across cell boundaries from lower permeability cells into adjacent higher permeability cells. Furthermore, drawdown in wells of lower permeability cells can reach maximum available drawdown limit before the same can happen in wells of higher permeability cells. As a consequence of earlier well failure, the total production from low permeability cells may be less than that from high permeability cells. Thus, inter-cell groundwater flow tends to improve the already better pumping economy and reliability of wells in higher permeability cells over those in lower permeability cells.

Two Extremes of Heterogeneity Distribution

An infinite number of spatial distributions of permeability belong to the exponential pdf. In order to calculate bounds on aquifer response associated with any of these distributions, two extreme cases are examined.

In the first case, permeability is distributed systematically across the aquifer. The permeability minimum is located on one side of the aquifer and permeability increases continuously (in accord with the pdf) to a maximum value on the other side of the aquifer. In the case of the exponential pdf used here, the minimum permeability value is zero, and the maximum value is at infinity. We assume that the exponential pdf can be truncated for all permeability values greater than some maximum, beyond which the probability is negligibly small in comparison to that of the lower permeability values. If the aquifer approaches infinite width, the permeability gradient of this extreme distribution approaches zero. In this case, the flow of groundwater between adjacent cells could be ignored, assuming the wells operate simultaneously. With negligible inter-cell flow, the aquifer response model in Chapter 3 can be used to calculate aquifer response for any cell permeability value.

At the other extreme, permeability is distributed randomly (in accord with the pdf) among the cells, though it is uniform within each cell. In this case, there could arise situations (a) where a cell of low permeability is surrounded by cells of high permeability, giving rise to inter-cell flow of water from the center cell to the outer cells; or

(b) where a cell of high permeability is surrounded by cells of low permeability, resulting in inter-cell flow in the opposite sense.

For bounding possible inter-cell flow effects, only situations (a) and (b) need be analyzed further. Let us consider next what permeability value in the surrounding cells will produce maximum inter-cell flow with respect to the center cell, in each of cases (a) and (b).

Inter-Cell Flow Bounds

In order to estimate the effects of inter-cell flow due to permeability differences between adjacent cells, consider the eight square cells surrounding any cell in a uniform square grid well field. Similar considerations apply to the other two possible uniform grid geometries. Suppose that the arithmetic average permeability of the eight surrounding cells is less than that of the central cell. One might expect a gain of water to the central cell from the eight surrounding cells. However, suppose that seven of the eight surrounding cells had a very low permeability, while the remaining cell (located opposite a side of the central cell, not a corner) had a permeability higher than the central cell. The average permeability of the eight surrounding cells could be less than that of the central cell, but the central cell would lose, not gain water, because the cells with very low permeability are, in effect, impermeable boundaries, while the single adjacent cell of higher permeability takes water from the central cell. Thus, the arithmetic average of surrounding cell permeability is not enough information to indicate the magnitude or the sense of inter-cell flow.

Finding a maximum bound on flow out of any cell under situation (a), above, is a comparatively simple matter. Let the eight square cells surrounding any cell of interest have infinite permeability, as if they were open bodies of water but with the same specific yield as the central cell. Then their cell boundary head will be the lowest possible, other conditions unchanged, and there will be maximum drainage out of the central cell for its particular permeability value. It is more useful to use a bound lower than the theoretical maximum, but sufficiently high to be almost never exceeded. That is, let the eight surrounding cells have a permeability equal to the highest probable, finite value expected for whatever aquifer is concerned.

Finding a maximum bound on flow into any cell under situation (b), above, is a more complicated matter. For some range of permeability values in the surrounding cells, the lower the permeability in the surrounding cells below that of the central cell, the greater the flow into the central cell. Below that range, flow into the central cell would decrease, until, if all surrounding cells had zero permeability, there would be no flow into the central cell. It, therefore, appears that there must be a surrounding cell permeability value between zero and whatever the central cell's value is, that results in maximum flow into the central cell. This value may depend on total pumping time, as well as on the central cell's permeability value. The only way seen, at present, for identifying the maximum bound for flow into the central cell is by some trial and error search technique. It will be shown later, in an example, that inter-cell flow has relatively minor effects on results.

Hence, for practical purposes, a reasonable guess of the appropriate lower permeability value of the eight square cells surrounding the central cell will be made.

Three cost estimates. For each set of decision variable values, there are now three cost estimates. The one for no inter-cell flow is included because it should lie between those for the conditions bounding inter-cell flow, and because the lower bound on costs is based on a reasonable approximation rather than rigorous analysis. Expected value calculations are performed for the three cases: (1) no inter-cell flow, (2) maximum inter-cell flow loss, and (3) maximum inter-cell flow gain, which are described as follows.

In the case of no inter-cell flow, every cell in the aquifer is conceptually surrounded by cells of nearly equal permeability. The aquifer response model for a single cell, as in Chapter 3, can be used to evaluate aquifer response.

In the case of maximum inter-cell flow loss, every cell in the aquifer is conceptually in situation (a), being surrounded by cells having the highest probable permeability value to be expected in the aquifer of concern. Expected costs are, therefore, calculated assuming maximum inter-cell flow loss out of each and every cell. Although the result is based on an impossible permeability distribution, it bounds the possible effects of inter-cell flow leaving any cell. An aquifer response model for estimating these effects is presented in Chapter 5.

In the third case, every cell in the aquifer is conceptually in situation (b), being surrounded by cells having a permeability value

somewhere between the particular cell's value and zero. As a guess, one might say halfway between the two. Expected values are, therefore, calculated assuming a reasonable approximation of inter-cell flow gain into any cell. Again, the result is based on an impossible permeability distribution, but it does lead to an approximate bound on the possible effects of inter-cell flow into any cell. The aquifer response model presented in Chapter 5 can be used to estimate aquifer response under these conditions.

Note that, in both of these inter-cell flow cases, (2) and (3), the bounds on expected costs represent the worst and best possible outcomes at any single cell in the aquifer. However, since the calculations are based on impossible spatial permeability distributions, they do not give the average cell cost for the whole area, as does the case, (1), where no inter-cell flow is assumed. Indeed, the average cell cost for the whole area, allowing for inter-cell flow, would lie well within the bounds, if situation (b) could be modelled exactly.

Illustrative Example

This illustrative example contains identical aquifer conditions to those contained in the example given in Chapter 2, with the exception of permeability. In the example of Chapter 2, permeability was homogeneous throughout the aquifer and given by the constant 4×10^{-4} [ft/sec]. In this example, permeability is distributed in terms of probability, according to Equation (4.2), with $K_m = 4 \times 10^{-4}$. For the expected value calculation according to Equation (4.5), Figure 8 shows

the permeability intervals and their respective probabilities, P_i , from Equation (4.4).

Aquifer response for each permeability interval was calculated, assuming a square, well grid geometry, as follows. For the case involving no inter-cell flow, the aquifer response model from Chapter 2 was used. For the case involving maximum, inter-cell flow loss from the central cell, the surrounding cells were assigned a permeability of 2.5×10^{-3} [ft/sec], and the aquifer response model given in Chapter 5 was used. For the case involving estimated maximum inter-cell flow gain to central cell, the surrounding cells were assigned a permeability of 1×10^{-4} . This value was assumed to be representative for inter-cell flow gains in the permeability ranges of higher probability.

The cost analysis was performed in the manner described in Chapter 2, and three expected costs were obtained for each pumping bound, as described in this chapter. The results are plotted in Figures 9 and 10.

Discussion of Results

In the illustrative example results plotted in Figure 9 and 10, the inter-cell flow curves are nearly the same as those based on the assumption of no inter-cell flow. Figure 9 shows that inter-cell flow costs do not vary from the assumed no inter-cell flow costs by more than plus or minus 3 percent. For the conditions of this example, therefore, we can neglect the influence of inter-cell flow due to non-uniform aquifer permeability.

Figure 9. Expected cost bounds for heterogeneous aquifer
with mean permeability equal to 4×10^{-4} [ft/sec].

- ① Well cost.
- ② Well and pumping cost, minimum bound.
- ③ Well, minimum pumping, and failure costs.
- ④ Well and pumping cost, maximum bound.
- ⑤ Well, maximum pumping, and failure costs.
- ... Each cell surrounded by highly competitive cells.
- Each cell surrounded by equally competitive cells.
- Each cell surrounded by poorly competitive cells.

Figure 9. Expected cost bounds for heterogeneous aquifer with mean permeability equal to 4×10^{-4} [ft/sec].

Figure 10. Expected net income for heterogeneous aquifer
with mean permeability equal to 4×10^{-4} [ft/sec].

- ① Maximum expected net income, for minimum pumping bound.
- ② Minimum expected net income, for maximum pumping bound.
- ... Each cell surrounded by highly competitive cells.
- Each cell surrounded by equally competitive cells.
- Each cell surrounded by poorly competitive cells.

Figure 10. Expected net income for heterogeneous aquifer with mean permeability equal to 4×10^{-4} [ft/sec].

It should be remembered in connection with inter-cell flow, that simultaneous well operation was assumed in the examples. The influence of inter-cell flow due to extreme non-simultaneous pumping has not been investigated in this analysis. For instance, if most wells in the field were to complete their pumping requirements early in the pumping season while a few scattered wells were late starters, the late-starting wells would begin pumping from already partially depleted cells due to inter-cell flow into the surrounding cells of early-starting wells.

The reader is here reminded that the minimum pumping bound means that all wells are pumped at the minimum possible rate during the entire pumping season to satisfy demand; whereas, the maximum pumping bound means that all wells are pumped at maximum capacity, continuously for a shorter period, until demand is satisfied. In reality, the wells will more likely operate at maximum capacity at intervals during the pumping season until demand is met; however, the pumping energy plus well failure cost for any such operating schedule will lie somewhere between the bounds recalled above.

Let us compare well field designs resulting from homogeneous and heterogeneous permeability assumptions. Although the method is general, the comparison is valid only for the particular set of conditions used in these examples. With regard to those maintenance costs which are excluded from this analysis, namely, those due to well supervision and to well reconditioning over and above capital costs for replacement of worn-out parts, it is generally accepted in the well industry that they increase more significantly with the number of wells to be maintained,

than they decrease with smaller well sizes. As a consequence, where other costs are about equal, lower well density and higher well capacity should be given preference in the choice of optimal well field design.

For this discussion, let us (1) assume that inter-cell flow effects can be neglected and refer only to the curves for no inter-cell flow, and (2) adopt for the design curve a curve lying halfway between the curves resulting from the two pumping bounds. Accordingly, the results on Figure 4 for the homogeneous case, and those on Figure 10 for the heterogeneous case, become as shown together on Figure 11, for comparison.

From Figure 11, for the homogeneous aquifer, the range of optimal designs appears to be from $Q_C^* = 2.5$ to 3.5 [ft^3/sec]. Considering the additional maintenance costs, the larger well capacity, lower well density design will be chosen, say $Q_C^* = 3.5$ [ft^3/sec], with a net income of 2.2×10^{-4} [$\$/\text{yr ft}^2$]. On the other hand, for the heterogeneous aquifer, the optimal design appears to be $Q_C^* = 2.5$ [ft^3/sec], with a net income of 1.0×10^{-4} [$\$/\text{yr ft}^2$]. In comparing these results it may be noted that while the mean permeabilities of the homogeneous and heterogeneous permeability distributions are the same, the exponential distribution is such that there will be a higher frequency of cell permeabilities below the mean than above it.

The heterogeneous aquifer design of $Q_C^* = 2.5$ is more conservative than the homogeneous aquifer design of $Q_C^* = 3.5$, with respect to well failure. Because of greater well density, the heterogeneous aquifer design will have higher maintenance costs than the latter design. The

Figure 11. Comparison of net incomes, midway between pumping bounds, for homogeneous case and heterogeneous case.

- ① Homogeneous case, $K = 4 \times 10^{-4}$ [ft/sec].
- ② Heterogeneous case, $K_m = 4 \times 10^{-4}$ [ft/sec].

Figure 11. Comparison of net incomes, midway between pumping bounds, for homogeneous case and heterogeneous case.

analysis shows a 17 percent increase in costs due to aquifer heterogeneity, mainly as a result of the associated increase in the incidence of well failure.

Accuracy of PDF Mean

Finally, we consider the consequence of inaccurate estimation of the mean, K_m , for the exponential pdf. The well field designer may be reasonably certain that the true mean lies somewhere between, for example, 3×10^{-4} and 5×10^{-4} [ft/sec]. He would like to know whether he should go ahead with a design based on his best estimate, say $K_m = 4 \times 10^{-4}$, or whether it would be worth obtaining more data for a closer estimate of the true mean. To this end, he can calculate and compare results for each of three cases. In the first case, $K_m = 3 \times 10^{-4}$; in the second case, $K_m = 4 \times 10^{-4}$; and in the third case, $K_m = 5 \times 10^{-4}$. To illustrate the calculation procedure, Figure 12 shows hypothetical curves for each mean. Figure 13 shows actual design curves from the illustrative example data where, as before, inter-cell flow has been neglected, and for each mean, a design curve halfway between those resulting from the two pumping bounds is adopted. Figure 12 was inserted because, in the illustrative example, it turned out that there was no penalty cost for a wrong guess of the mean value within the limits given above.

From Figure 12, the optimal design for K_{m1} is Q_{c1}^* , with a net income of v_1 . Similarly, for K_{m2} , we have Q_{c2}^* , with v_2 , and for K_{m3} , Q_{c3}^* with v_3 . If the assumed mean for design is K_{m2} , when the true mean is K_{m1} , net income will be w_1 , with a penalty cost for not designing for

Figure 12. Hypothetical curves illustrating penalty cost calculation procedures.

K_{m1}, K_{m2}, K_{m3}	Hypothetical net income curves for three different mean permeabilities.
$Q_{c1}^*, Q_{c2}^*, Q_{c3}^*$	Optimal well capacities for each curve.
v_1, v_2, v_3	Maximum net incomes associated with optimal well capacities for each mean permeability curve.
w_1, w_2	Net incomes with Q_2^* design, when true mean permeability is K_{m1} or K_{m3} , respectively.

Note: If the true mean lies between K_{m1} and K_{m3} , then the estimated maximum penalty cost due to designing for K_{m2} is $(v_1 - w_1)$.

Figure 12. Hypothetical curves illustrating penalty cost calculation procedures.

Figure 13. Expected net incomes for heterogeneous aquifers with mean permeability of 5×10^{-4} , 4×10^{-4} and 3×10^{-4} [ft/sec].

- ① Expected net income, for $K_m = 5 \times 10^{-4}$ [ft/sec].
- ② Expected net income, for $K_m = 4 \times 10^{-4}$ [ft/sec].
- ③ Expected net income, for $K_m = 3 \times 10^{-4}$ [ft/sec].

Figure 13. Expected net incomes for heterogeneous aquifers with mean permeability of 5×10^{-4} , 4×10^{-4} and 3×10^{-4} [ft/sec].

the true mean, of $(v_1 - w_1)$. Similarly, if K_{m3} were the true mean, the penalty cost would be $(v_3 - w_2)$. The designer can compare these cost penalties with the cost of obtaining a more accurate estimate of the true mean, in order to reach a decision. In Figure 13, the optimal design is $Q_c^* = 2.5$, for all three values of K_m . The respective net incomes are shown on Figure 13. With no penalty cost in the area of uncertainty for K_m , the designer can go ahead with the design based on $K_m = 4 \times 10^{-4}$, because a more accurate estimate of the true mean would provide no benefit but might be expensive to obtain.

A more thorough analysis of the consequences of uncertainty in the pdf for permeability can be made using Bayesian decision theory. Bostock and Davis (1975) described such an analysis.

Maximum Non-Simultaneous Pumping Time

A well that starts pumping late in the season may start with an already lowered initial static water level due to previous pumping from nearby wells. In such a case, pumping costs at the well could exceed the maximum bound for simultaneous pumping, and there would be a greater risk of well failure than if simultaneous pumping were required. We now consider the consequence of removing the simultaneous pumping requirement. An analysis procedure similar to the one defined in this chapter for the analysis of inter-cell flow effects due to heterogeneous permeability is proposed here for the analysis of inter-cell flow effects due to non-simultaneous pumping.

For extreme effects at any cell, of non-simultaneous pumping subject to the operating decisions defined in Chapter 2, there could arise

situations (c) where a cell whose pumping starts at the latest possible time in the pumping season, is surrounded by cells whose pumping is completed at the earliest possible time in the pumping season, giving rise to inter-cell flow of water from the center cell to the outer cell, or (d) where a cell whose pumping is completed at the earliest possible time in the pumping season, is surrounded by cells whose pumping starts at the latest possible time in the pumping season, resulting in inter-cell flow in the opposite sense. Since we are interested only in the maximum effects of non-simultaneous pumping at any cell, we can further assume that the surrounding cells always have the same permeability as the central cell. The remainder of the analysis is the same as for the heterogeneous aquifer case. Note that expected values are still calculated over all permeability values, but no inter-cell flow occurs due to permeability heterogeneity; it occurs only due to non-simultaneous pumping, in this analysis. A third analysis could be defined, in which the extreme effects of both permeability heterogeneity and non-simultaneous pumping are compounded, but it will not be discussed in this study.

In the writer's judgment, the inter-cell flow bounds on costs due to extreme non-simultaneous pumping will deviate further from the costs for no inter-cell flow than those due to extreme effects of heterogeneous permeability. This is because of the longer time span over which inter-cell flow can take place in the extreme non-simultaneous pumping case, compared to the simultaneous pumping but non-uniform permeability case. However, as pointed out in Chapter 2, the well field can be managed so as

to minimize this inter-cell flow effect, by keeping the average pumping rates of all the wells simultaneously equal, where the average is calculated over some maximum, safe non-simultaneous pumping time, t_s [T]. Note that, for cases (c) and (d), t_s has been assumed to be equal to $t_{\max}$, the maximum length of pumping season.

A possible approach to determining the maximum safe length of t_s can be defined as follows. A tolerable inter-cell flow cost is defined in terms of a tolerable deviation of the cost bounds from the no inter-cell flow case. The pumping periods defined in cases (c) and (d) for the center and surrounding cells are moved closer together in time, giving a smaller value of t_s . The cost analysis calculations are performed again. This procedure is repeated for successively smaller values of t_s until the maximum safe value of t_s is found such that the inter-cell flow cost bounds lie within their tolerable deviation from the costs for the no inter-cell flow case.

Multiple Design Possibility

Available data on an aquifer may indicate that some areas have greater probability of high permeability values than other areas. Areas of high permeability will generally sustain higher production rate wells, spaced correspondingly farther apart, than will areas of low permeability. It may be more efficient to take advantage of such information and to carry out separate well field design analyses using different pdf's, where permeability expectations are different. The results of analyses with different permeability pdf's for different parts of the aquifer may result in different well spacings. At the junction of grids

having different well spacings, clustering of wells should be minimized in order to minimize well interference. Some areas having a lower storage capacity may sustain a lower groundwater production rate per unit area, than other areas with higher storage capacity. Some aquifer areas may be uneconomical for any groundwater production, and left devoid of wells. The well field design analysis method is applicable to these cases, provided that inter-cell flow can be accounted for, or is negligible.

Homogeneity within Cells

Natural distributions of permeability and specific yield in granular aquifers are complex, sometimes over distances as small as a few yards. The assumption of homogeneous permeability and specific yield within each cell, therefore, bears some discussion. Two reasons for allowing it in the practical application of this well field design analysis method, are given in the following two paragraphs.

Aquifer drawdown pump test results, showing aquifer drawdown versus pumping time, represent some sort of integration of the real distribution of aquifer properties. The volume of aquifer over which such integration occurs depends on the pumping duration up to the time of drawdown observation. Note that the greater the radial distance between the well and any transmissivity or specific yield anomaly, the smaller the effect of such anomaly on drawdown at the well. Usual practice is to assign single values to the transmissivity and specific yield in the aquifer at each well. These single, or homogeneous, values are chosen

so as to be representative of the time drawdown characteristics at the well, as indicated by pump tests.

As previously stated, Supkow (1972) showed that the 2500 nodal transmissivity values used in the digital computer model of the Tucson basin aquifer gave a close fit with an exponential pdf. The aquifer area represented by each nodal transmissivity value was one quarter mile square. This area is of the same order of magnitude as the cell areas used in the well field design analysis.

Conclusions

(1) The well field design method which was developed in Chapter 2 has been extended to take into account uncertainty in the spatial distribution of permeability in the aquifer. The spatial distribution of permeability among cells in the aquifer area of interest is assumed to be in accord with a given probability density function.

(2) Inter-cell flow effects due to heterogeneous permeability, for the aquifer conditions and operating decisions assumed, were found to be negligible.

(3) Under the conditions of the illustrative example, the least cost well field design for the homogeneous aquifer with $K = 4 \times 10^{-4}$ [ft/sec] was $Q_c = 3.5$ [ft³/sec] with $N_w = 2.49 \times 10^{-7}$ [well/ft²]. The corresponding design for the heterogeneous aquifer with $K_m = 4 \times 10^{-4}$, was $Q_c = 2.5$ and $N_w = 3.48 \times 10^{-7}$. Well field cost with the heterogeneous distribution of permeability was 17 percent higher than with the homogeneous distribution.

(4) The well field cost analysis method was used in the example to calculate penalty costs (foregone benefits) due to lack of information on the true value of the mean, K_m , to be used in the exponential pdf. For the range of K_m examined, there were no penalty costs. Further work on this aspect of the method has been done by Bostock and Davis (1975).

(5) The heterogeneous analysis method can be extended to calculate a maximum safe time period over which non-simultaneous pumping can continue, without excessive effect on costs.

(6) Where previous knowledge of the spatial distribution of aquifer properties indicates different well field designs in different areas of the aquifer, such multiple design analysis can be performed using the method presented here, provided that inter-cell flow effects can be accounted for, or are negligible.

In the next chapter, the aquifer response model of Chapter 3 is extended to involve the effects on a central cell caused by extreme conditions in the surrounding cells.

CHAPTER 5

AQUIFER RESPONSE MODEL: HETEROGENEOUS CASE

The objective of this chapter is to extend the circular cell model of Chapter 3 to represent a group of cells consisting of a central cell and its surrounding, adjacent cells. The surrounding cells are added to the single cell response model in order to estimate the possible effects on costs of inter-cell flow, into or out of any cells in the aquifer area. In Chapter 4, two causes of inter-cell flow were analyzed. One cause is aquifer heterogeneity, the other cause is non-simultaneous pumping. Conditions in the surrounding cells which would produce maximum inter-cell flow from each of these causes were defined. This chapter provides a solution to the cell group model for each grid geometry that is capable of incorporating those conditions of heterogeneous permeability and non-simultaneous pumping which result in maximum inter-cell flow.

Requirements of the cell group model, in addition to those specified in Chapter 3 for the single cell model, are the following.

- (1) The surrounding cells all have the same permeability, and their wells operate simultaneously.
- (2) The permeability of the central cell and that of the surrounding cells can each be specified independently.
- (3) The pumping rate of the central cell and that of the surrounding cells can each be specified independently, and are each variable in time.

Circular Representation of Cell Group Models

We continue with the circular, radial flow model solution of Chapter 3, because it is computationally fast, and easily adapted to represent any of the three cell group models resulting from the three well location grid geometries. Other solutions could be used, but this one is adequate.

Cylindrical Sink Model

The circular cell model adaptation to represent each of the three different cell groups, related to each of the three grid geometries, resembles a doughnut-shaped ring of aquifer with the hole filled by a cylindrical cell similar to the model of Chapter 3 (see Figures 14, 15 and 16). The permeabilities of the central cell and surrounding doughnut are respectively homogeneous, but in general, are different. The central cell and doughnut are hydraulically connected, that is, there is no impermeable boundary between them. The model has the same total horizontal area as the particular cell group model, and is impermeably bounded around its outer circumference. Drawdown in the central cell is the unknown of primary concern. The doughnut surrounding the central cell provides a measure of inter-cell flow effect on the central cell's drawdown due to pumping in the adjacent, surrounding cells. Permeability of the doughnut equals permeability assigned to the surrounding cells. Pumping in the surrounding cells is modelled in the doughnut by a cylindrical sink of strength equal to the combined pumping from the surrounding cells, and located concentrically with the central well and doughnut. The diameter of the cylindrical sink is such that

Figure 14. Cylindrical sink model, approximation of hexagonal cell group for equilateral triangular, well location grid geometry.

Figure 15. Cylindrical sink model, approximation of square cell group for square, well location grid geometry.

Figure 16. Cylindrical sink model, approximation of equilateral triangular cell group for hexagonal, well location grid geometry.

the horizontal cross-section area enclosed by it is the same as that enclosed by lines joining all surrounding wells in the group of surrounding cells (see Figures 14, 15 and 16).

Satellite Cell Component

The cylindrical sink has a much larger surface area over which flow may enter than the wells which it replaces, and consequently, does not produce the radial convergence losses that wells produce. The effect of lack of convergence loss at the cylindrical sink is to give no indication of when the surrounding wells would reach their maximum available drawdown state and begin to decline in their production rate. In order to provide an estimate of this necessary information, a "satellite" cell model is solved in conjunction with the cylindrical sink model (see Figure 17). We will speak of the two components of the cylindrical sink model as the central cell-doughnut component, and the satellite cell component. The satellite model represents a single cell whose permeability is the same as the permeability of the doughnut. In solving the cylindrical sink model using finite difference time steps, a record is kept of volume and direction of water transferred between the central cell and the doughnut at the end of each time step. Before the next time step iteration, a fraction of this water transfer is applied uniformly around the outer boundary of the satellite cell model. The sign of this fraction is such that if flow is out of the central cell and into the doughnut, then the direction of water transfer is into the satellite cell, and vice-versa. The volume of the fraction is equal to the total volume transferred between the central cell and doughnut

Figure 17. Cylindrical sink model of nine square cells.

during the time increment, divided by the number of surrounding cells represented by the doughnut. Figure 17 shows the cylindrical sink model of nine square cells. The doughnut is divided into eight segments, each representing an "average" of the eight surrounding square cells in the group of nine. The arrows indicate groundwater flow between the central cell and one of the eight segments of the doughnut. The arrows on the satellite cell are to indicate a uniform distribution of inter-cell flow around its boundary. Next, drawdown in the satellite is calculated for that time step. When the satellite cell reaches maximum available drawdown state it can indicate appropriate decline in production rate for cylindrical sink. The strength of the cylindrical sink is always equal to the pumping rate of the satellite cell multiplied by the number of surrounding cells represented by the doughnut. Conservation of mass is maintained between the central cell and doughnut, and between the central cell and satellite cell. The doughnut estimates inter-cell flow loss from, or gain to, the central cell, while the satellite cell estimates radial convergence losses of head in the doughnut and controls pumping rate of the cylindrical sink.

The question arises whether the water flow between the central cell and doughnut can be applied uniformly around the satellite model circumference as has been done here, or whether it would be more correct to apply it over a portion of the satellite circumference of similar length to the contact length between the central cell and the appropriate fraction of the doughnut inner circumference (see Figure 17). The appropriate fraction is the reciprocal of the number of wells represented by the doughnut. Following a procedure given in Muskat (1946,

pp. 163-169), it may be shown that for steady, confined flow through a cylindrical model into a concentric well, the head at the well depends on total rate of water entry into the model at the outer boundary and on average head over outer boundary, but is independent of water velocity distribution around the outer boundary. While this fact cannot directly validate the unconfined transient flow model, it does give an indication that the procedure followed here is a reasonable approximation.

Model Formulation

The purpose of this section is to indicate how the finite difference equations of the single cell model solution in Chapter 3 are modified for use in the cylindrical sink model. The cylindrical sink model is composed of equations similar to (3.12) to (3.15). The differences are in the number and spacing of the annuli, in the discharge rate of the cylindrical sink, and in the transfer of water into or out of the outer boundary of the satellite cell model. Let the central cell part of the model have n_a annuli, spaced in proportion to e^r , according to Equation (3.7). Let the doughnut be composed of n_b annuli, linearly spaced, as explained later. Thus, n for the outer, n -th, annulus of the model, with impermeable outer boundary, is $n = n_a + n_b$. The cylindrical sink is the n_d -th annulus, where $n_d = \{n_a + \text{Integer}(n_b/2) + 1\}$. By Integer $(n_b/2)$, it is meant that decimal places are dropped after dividing, to leave an integer, next smaller than the real number.

Let the central cell have radius r_a . For the square grid well location geometry, the radius of the cylindrical sink is twice the radius

of the central cell, that is, $2r_a$. The radius of the outer impermeable boundary is $3r_a$. We let the node of the annulus which forms the cylindrical sink, have radius $2r_a$, and let the distance to either wall of this annulus be a constant, C . Let the distances, between each annulus wall and node and wall, etc., continuing in both directions away from the cylindrical sink, increase successively by the constant amount, C .

Figure 18 shows the annuli equally spaced, however, for simplicity in the diagram. There are n_b such intervals on either side of the cylindrical sink node (see Figure 18). Note that n_b must be an odd number while n_a can be even or odd. Thus, $r_a = \{C + 2C + 3C + \dots + n_b C\}$ or

$$C = r_a / \left\{ \sum_{m=1}^{n_b} m \right\}. \quad \text{The node and annulus radii are given by the following}$$

formulae. In terms of i subscripts, they are,

$$\text{for } r_i < r_{n_d}, \quad r_i = r_{i+\frac{1}{2}} - 2\{n_d - i\}C,$$

$$\text{for } r_i > r_{n_d}, \quad r_i = r_{i-\frac{1}{2}} + 2\{i - n_d\}C,$$

$$\text{where } i = n_a + \frac{1}{2}, n_a + 1, n_a + 1\frac{1}{2}, \dots, n - \frac{1}{2}, n, n + \frac{1}{2}; \quad (5.1)$$

or, in terms of k subscripts, where $k = 2i$, in order to transform the i 's into integers for computer referencing,

$$r_k < r_{2n_d}, \quad r_k = r_{k+1} - \{2n_d - k\}C,$$

$$r_k > r_{2n_d}, \quad r_k = r_{k-1} + \{k - 2n_d\}C,$$

$$\text{where } k = 2n_a+1, 2n_a+2, 2n_a+3, \dots, 2n-1, 2n, 2n+1. \quad (5.2)$$

Figure 18. Right-hand side of axial section through finite difference model of cylindrical sink model.

The nodes and the annuli of the satellite cell are spaced identically to those of the central cell.

The link between the central cell-doughnut component and the satellite cell component works as follows. We let U_i [L^3/T] be the flow rate, in the direction of positive r , across the i -th annulus' outer wall, at radius $r_{i+1/2}$. Then, treating aquifer recharge as positive, and flow in the direction of positive r as positive flow, the flow across the cell boundary into the doughnut, that is, from the n_a -th annulus into the n_a+1 -th annulus, is

$$U_{n_a} = \sum_{i=1}^{n_a} q_i - \pi \{ r_{i+1/2}^2 - r_{i-1/2}^2 \} S_y \{ h_j - h_{j-1} \} / \Delta t_j ,$$

where i takes on integer values only. For every j -th time interval, Δt_j , the sequence of major steps relevant to the link between the two model components goes as follows. We use the square cell group (Figure 15) to illustrate:

1. Set new time increment, $\Delta t_j = 1.2\{\Delta t_{j-1}\}$.
2. Set q_{n_a} of satellite cell equal to $U_{n_a}/8$ which was calculated in the central cell for previous time interval, Δt_{j-1} . This distributes a flow, equal in magnitude to one-eighth of the inter-cell flow from central cell into doughnut, around and entering the outer annulus of the satellite cell component (see Figures 17 and 18).
3. The satellite cell determines well discharge rate, in the light of radial convergence head losses, for the current time interval, Δt_j .

4. Set q_{n_d} , that is, for the annulus of the doughnut containing the cylindrical sink, equal to $8q_1$ from the satellite cell. This controls the pumping rate of the cylindrical sink for the current time interval, Δt_j .
5. The central cell-doughnut determines its new heads and a new value for U_{n_a} for the current time interval, Δt_j .
6. If the total pumping time, $t_{\max}$, has not elapsed, go back to step 1. Otherwise, stop.

Accuracy Check of Cylindrical Sink Model

In order to check the accuracy of the cylindrical sink model, a two-dimensional, cartesian coordinate, finite difference model was developed. It is expected that the cylindrical sink model will represent the equilateral-triangular grid geometry cell group (Figure 14) most closely, the hexagonal grid cell group (Figure 16) least closely, while it will be somewhere between for the square grid cell group (Figure 15). Comparisons were made only for the square grid cell group, which consists of nine square cells.

In the square grid model, the nodes were equally spaced. With equally spaced nodes, radial convergence losses at the wells are not as well represented as in the circular model with exponentially spaced nodes. In order to obtain, for the well in the central cell, an independent measure of the difference in representation of radial convergence head losses between the two models, the following was done. Drawdown was calculated for a single, impermeably bounded, circular cell, and again for the corresponding square cell. Identical time increments

and pumping rate functions were used in each case, so that the comparison would not be invalidated due to well failure, should it occur in the circular model where convergence head losses are greater at the central well. For an example of results, see Figure 19. Figure 19 shows that for the independent comparison of radial convergence losses, the circular model drawdowns are not quite as great as those for the square grid model. This can be explained, at least in part, by the volume of water mined out of the cone of depression close to the well, being greater in the case of the circular model than in the case of the uniform node spacing, square model. To compensate, the drawdown farther out in the circular model is less than in the square model.

Having this independent measure of the difference in radial convergence head loss between the circular and square models, then the nine square cells model, and corresponding cylindrical sink model, were next examined. Permeability for the central cell in each model was set equal to that in the single cell case described above. Various trials, using various permeabilities, involved different permeability contrasts between the central cells and the surrounding cells, or doughnut. In all cases, identical time increments, and discharge rate functions for the greatest discrepancy between the circular cell group model and square cell group model were used. The greatest discrepancy occurred when the permeability of the central cell is low and that of the surrounding cells is high. Of the trials made, the one resulting in the most discrepancy gave the results which are also plotted on Figure 19.

Figure 19. Comparison of drawdowns produced by the circular models and by the square models.

The curves for the cell group show the circular model drawdown is greater than that for the square model. A possible explanation for this reversal follows. Since the permeability of the central cell is low, the central well fails early (after 6 minutes) in the pumping period, while the surrounding wells, being in high permeability cells, do not fail at all. Consequently, there is an overwhelming withdrawal of water at the cylindrical sink, compared to the water withdrawal at the central well. The cylindrical sink, having so much surface area and so little convergence head loss, has a relatively shallow "trough" of depression on either side of it, while in the square model, the nodal squares that represent the surrounding wells have larger convergence losses than the cylindrical sink. Therefore, in the outer part of the central cell, as seen on Figure 19, the drawdown for the square cell model is now above that of the circular model in order to compensate for the deeper "cones" of depression necessary at the nodal squares representing wells in the square model. We can infer from this qualitative discussion that if exponential spacing of nodes along the two axial directions away from each nodal square well of the square model had been used, then (1) the two curves for the independent cells would more nearly coincide, that is, the square cell curve would come closer to the circular cell curve; and (2) the two curves for the square, and circular, cell group models would be still farther apart, because of still deeper cones of depression occurring around the now much smaller nodal square wells of the surrounding square cells while the cylindrical sink is unchanged.

A second accuracy check of the cylindrical sink model was made, as well. Under homogeneous aquifer conditions, and simultaneous, equal pumping rates from all wells, there should be no inter-cell flow between the central cell and the surrounding doughnut. With a homogeneous permeability of 4×10^{-4} [ft/sec], the maximum difference in drawdown between the central cell and the satellite cell just prior to well failure, after 24 percent of the pumping season had elapsed, was 0.6 [ft], in a total of 160 [ft] of drawdown. Maximum inter-cell flow in any time interval was 5 percent of the discharge rate at the central cell. These are certainly tolerable errors in an analysis of this kind. At lower permeability values, errors could be greater due to greater head variations in space, however, the model was not tested for other permeability values.

Discussion of Results

The advantage of the cylindrical sink model over a two-dimensional square model having exponentially spaced nodes and nodal rectangles, and being reduced to one-quarter size by symmetry, is that the former model results in a faster computer program. It is faster for two reasons. If the number of equations in the two-dimensional model were x , then the number of equations required for an equivalent, cylindrical sink model would be approximately $1.5\sqrt{x}$, where $\sqrt{x}$ equations represent the central cell-doughnut component and $.5\sqrt{x}$ equations represent the satellite cell. Therefore, the circular representation of the cell group model requires significantly fewer equations for solution than does the square representation. The other reason is that the cylindrical sink model equations, having only one independent space variable, r , require only

one iteration, per time interval, for solution, while, on the other hand, the square model equations, having two independent space variables, x and y , and being solved by the iterative alternating direction implicit method (Prickett and Lonnquist, 1971), may require several iterations, per time interval, for solution. The disadvantage of the cylindrical sink model, in comparison with the two-dimensional model, is that it is an inferior approximation of the geometry of the flow system that would occur in a group of nine square cells.

While the cylindrical sink model cannot represent the polygonal cell group models exactly, the inter-cell flow phenomena of both model representations must be of the same order of magnitude, for the conditions examined here. In the illustrative example results for heterogeneous permeability, inter-cell flow effects on total costs were negligible according to the cylindrical sink model. Even if inter-cell flow effects were 50 percent in error, a maximum error in the writer's estimation, the resulting effect on costs in the example results would still be negligible. Note that in all of this discussion regarding the accuracy of the cylindrical sink approximation, considerations were limited to simultaneous pumping. The accuracy of the cylindrical sink model was not checked with regard to non-simultaneous pumping. The reason for this is that the scope of this study does not include a rigorous analysis of the influence of non-simultaneous pumping.

Conclusions

The following conclusions may be drawn from the accuracy study of the cylindrical sink model and from the well field design method defined in earlier chapters.

(1) The circular approximation of the polygonal cell group model can be used to measure extreme inter-cell flow effects due to heterogeneous permeability, under the conditions of the illustrative example given here.

(2) Further testing of this model approximation may indicate that its application to a wider range of aquifer conditions is also justified.

(3) Other, more accurate, solutions of the polygonal cell group models could have been substituted for the cylindrical sink model employed here, involving no other changes in the overall well field design analysis.

CHAPTER 6

DISCUSSION AND CONCLUSIONS

A method of cost minimization for a particular kind of well field design problem was described. The problem involves construction of a uniform grid well field over an extensive area. The chief characteristic of the method is that it takes into account uncertainty in the lateral distribution of field permeability in the aquifer. In this chapter, practical applications of the method and recommendations for further work are discussed, and conclusions are listed.

Practical Applications

Conditions in Bangladesh

The well field design method applies to the kind of conditions that exist in Bangladesh. In Bangladesh, there is extensive flat-lying terrain composed of the delta created by the Ganges and Brahmaputra Rivers. Much rainfall occurs in the summer time, while the winters are dry by comparison. In some parts of the country, the rainfall is insufficient for growing crops during the dry, winter season (Karim, 1968). The unconfined aquifer which is formed by the deltaic sediments receives recharge from rainfall through the ground surface during the wet season. A network of groundwater wells could provide both a sanitary water supply year-round, and irrigation water for crops during the dry season.

In Bangladesh, where many new wells are needed over extensive areas and in a short time, it would be expedient to proceed directly with well field construction based on a uniform grid design. One important decision in establishing such a design is what density-capacity combination to use for the well grid.

Well Density-Capacity Combinations

A well field design that uses a uniform grid can be defined by a well density-capacity combination. By expressing water demand and well field costs on a "per unit ground-surface area" basis, the well field costs resulting from alternative well density-capacity combinations can be compared without regard to the total number of wells to be constructed in the well field area. This simplifies analysis to the consideration of costs for one well and its appropriate size of aquifer cell. The size of aquifer cells is determined by the following relationship: the product of well capacity multiplied by well density must equal the "maximum instantaneous demand rate."

Where different sub-areas of the total well field design area have known differences in their physical characteristics, the method may indicate different well density-capacity combinations. At boundaries between different designs, an understanding of the design method and use of judgment are necessary to avoid, for example, two wells being located much closer together than the spacing of either adjacent grid.

Heterogeneity Among Aquifer Cells

After the well field has been constructed, a field permeability value can be measured at each well by means of pump tests. This value is assumed to represent the permeability of the well's cell of aquifer. The permeability at each well will, in general, be different. This permeability is a major factor influencing the fraction of groundwater storage in the cell that can be extracted by pumping during a given time interval. It also affects the energy consumed in the pumping. The total well field cost per unit area is of interest rather than the cost at each individual well. Therefore, it is the frequencies of the various cell-permeability values that is important, rather than the actual spatial distribution of field permeability. It is convenient to define the frequency of each cell-permeability value by a pdf. The pdf is a probabilistic model of differences in permeability among aquifer cells. While the permeability outcome for any specific cell is unknown before constructing and pump-testing its well, the outcomes for the total well field are assumed before well field construction, in the permeability frequencies defined by the pdf.

This is a more realistic assumption than assuming a completely homogeneous aquifer. In the illustrative example (Chapters 2 and 4), the least cost well field design for a homogeneous aquifer (permeability = 4×10^{-4} [ft/sec]) had a well capacity of 3.5 [ft³/sec] and well density of 2.49×10^{-7} [well/ft²]. With a heterogeneous aquifer having the same average permeability, the capacity of the wells was 2.5 [ft³/sec] and the density was 3.48×10^{-7} [well/ft²]. The well field cost was 17 percent higher with the heterogeneous aquifer than with the homogeneous aquifer.

Inter-Cell Flow

The assumption of uniform size and shape of aquifer cells in the well field design area is an approximation. In real well fields, a cell's shape varies with the permeability distribution within the cell and within its adjacent cells. The size of any cell will depend on the quantity of groundwater pumped out of it, in relation to the quantity pumped out of its adjacent cells. The cell sizes will also change in time, depending on variations in pumping schedules of adjacent wells.

With regard to permeability variations, the same drawdown at a well can be produced by an infinite variety of permeability distributions. The field permeability, as measured by a pump test, is the important property. Its value may change in time as the cone of depression develops in the aquifer cell. Nevertheless, it is practical to assign a representative permeability value to a well to reflect the apparent permeability of the aquifer cell assigned to it. Possible effects of permeability differences among different cells were examined in Chapter 4.

With regard to non-simultaneous operation of the wells, it should be noted that drawdown fluctuations in the aquifer close to any well due to its being operated sporadically, are damped in passing outward through the aquifer toward the assumed boundary location of the cell. A graph of drawdown at a cell boundary would indicate a smoothed average of the sporadic pumping rates of the nearby wells. By operating the wells so that the total volume of water withdrawn from each well is equal over some predetermined "maximum non-simultaneous pumping period," the

inter-cell flow due this cause can be limited to any predetermined amount by limiting the non-simultaneous pumping period.

Vertical Permeability in Aquifer

Vertical movement of groundwater is unrestricted in the aquifer response model solutions provided in Chapter 3, the vertical permeability being in effect that of air or a vacuum. It is assumed that, with unconfined aquifers and long pumping time, the proportions of energy consumed in the flow system by vertical flow components may be neglected by comparison with the energy consumed by horizontal flow components. This assumption is discussed in Chapter 3 under the headings of Dupuit Assumptions and Delayed Drainage. An important point is that if the well screen extends above the water table so that a seepage face exists in the well, then the water entering the well through the seepage face falls freely through air to the water level in the well. The aquifer model in Chapter 3 involves a well screen opposite the entire saturated thickness of aquifer penetrated by the well.

Influence of Well Failures

With a uniform-grid-well-field design on a heterogeneous aquifer, wells in low permeability cells will have greater drawdown to pump against than wells in higher permeability cells. In some cells, the permeability may be so low that drawdown reaches the pump intake, and the well cannot pump at its design rate. This condition is defined as well failure. The well field design method includes the influence of well failure on costs by first holding the drawdown in a failed well at the

level of the pump intake and letting the well produce at whatever rate it can under that condition for the remainder of the specified pumping period; second, the water deficit below the specified demand is determined and a penalty cost applied to the deficit. Any degree of aversion to well failures can be built into the design method by appropriately weighting the penalty cost that is applied to the resulting water deficit.

Bayesian Decision Theory Application

The well field design method is well suited for a Bayesian decision-theoretic analysis (Bostock and Davis, 1975). Where uncertainty exists in the form of a pdf that represents the aquifer heterogeneity, the method may be used to calculate costs for a range of pdf's, each with a probability of being the true model. The designer may then choose the design that minimizes the expected costs in view of the assumed models and their probabilities. However, when the expected value criterion is used for making the decision, a small portion of the time, poor results will be obtained in the form of a high frequency of low permeabilities giving well failures. This probability can be reduced by weighting the cost of the water deficit resulting from well failures. Alternatively, well field designs which have more than a specified small probability of a water deficit that will exceed some specified small amount, can be discarded.

In addition, the Bayesian analysis enables calculation of the expected worth of additional data in the form of permeability measurements at test wells before making the design decision. However, it

should be kept in mind that the information in a data sample may be influenced by the assumption of homogeneity within aquifer cells but heterogeneity among cells. The amount of information in a data sample may depend on the sizes of the aquifer cells and on the area of aquifer represented by the pdf models. Further work is needed on this aspect of the analysis.

Management and Maintenance

Ensuring reliable operation of all wells in a field requires effective management of well operation and maintenance. Effective management may be the most difficult problem in making a well field design work.

For example, in a rural county of South Carolina, the "cluster well concept" is being tried on an experimental basis. Houses are located in a scattered manner along country roads. Each well serves from one to ten connections. The cluster well design is transformed into a system by central management of all wells. The management company must provide adequate operation and maintenance of the wells. Up to the time of this experiment, many small companies had failed, and funding agencies hesitated to finance them for this reason (Cobb, 1974). If difficulties like this are experienced in a technological society such as exists in North America, the problems of management in a country like Bangladesh may be intractable. Evidence of ability and willingness in the local population to take the responsibility for maintaining the effectiveness of their well field system would appear to be a prerequisite for construction of any technologically advanced well field system.

Recommendations for Further Work

Vertical Permeability in Aquifer

The aquifer response model presented in this study neglects resistance to vertical flow in the aquifer. Recently, aquifer modelling methods and theories for taking into account resistance to vertical flow in conjunction with horizontal flow have been developed (Cooley, 1971; Neuman, 1974). It is recommended that results using these methods be compared with results using the methods presented here. Of interest are the effects of various degrees of anisotropy of permeability in the horizontal plane, various ratios of cell depth to cell diameter, and the computer time consumed by the methods.

Optimal Depths for Well and Pump Intake

A Bayesian decision theory analysis for the optimal depths to drill the wells and set the pump intakes is recommended. The quantity of groundwater stored in the aquifer at the beginning of the pumping season depends on a stochastic process involving the frequency and intensity of rainfall during the wet seasons when the aquifer receives recharge. The decisions to be optimized in this case are, (1) to what depth to drill the wells, and (2) at what depth to set the pump intakes. The objective is to minimize the drilling costs and pump column costs in view of uncertainty of depth of water at the start of each pumping season.

Aquifer Heterogeneity

Further work is recommended to gain a better understanding of the meaning and possible applications of defining aquifer heterogeneity in terms of a pdf. The following questions arise. (1) How does cell size affect the pdf for frequencies of permeabilities among cells? (2) Instead of assuming that permeability is homogeneous throughout each aquifer cell, would a better assumption be that the permeabilities of the annuli closest to the well differ from the average permeability for the cell according to some pdf? (3) What kinds of pdf's apply to aquifers of different geologic types, such as river delta aquifers, consolidated rock aquifers with fracture permeability, and valley fill aquifers?

Maximum Non-Simultaneous Pumping Period

More work needs to be done to develop the method given in Chapter 4 for calculating the maximum non-simultaneous pumping period without increasing the probability of well failures.

Maintenance Costs

Costs due to the salaries of well supervisory personnel and the equipment they require are difficult to relate directly to well density-capacity combinations. There is a lack of data on the number of wells that one person or a team of people can service. Well reconditioning cost was not included in the analysis presented here because of the lack of information on these costs and their recurrence frequency. With more information on both of these maintenance costs, they could be included in the well field design method of this study.

Conclusions

(1) A method was developed for comparing uniform grid well field costs for alternative, well density-capacity combinations required to meet a given groundwater demand.

(2) An aquifer response model was developed to represent an impermeably bounded single cell of aquifer. A finite difference solution and an analytical solution were obtained. The model is cylindrical in shape, homogeneous, isotropic, and involves the assumption of no resistance to vertical flow of groundwater. It allows for decrease in transmissivity with dewatering, and for declining, average discharge rate when maximum drawdown in the well has been reached.

(3) The well field design method takes into account uncertainty in the spatial distribution of permeability in the aquifer. The frequencies of permeability values among cells in the aquifer area of interest are defined by a probability density function.

(4) Inter-cell flow effects due to heterogeneous permeability, for the aquifer conditions and operating decisions assumed in the illustrative example, were found to be negligible.

(5) For conditions of the illustrative example, the least cost well field design for the homogeneous aquifer with $K = 4 \times 10^{-4}$ [ft/sec] was $Q_C = 3.5$ [ft³/sec], with $N_W = 2.49 \times 10^{-7}$ [well/ft²]. The least cost design changed to $Q_C = 2.5$ and $N_W = 3.48 \times 10^{-7}$ when a heterogeneous aquifer with $K_m = 4 \times 10^{-4}$ replaced the homogeneous aquifer. The example results show a 17 percent increase in costs as a result of aquifer heterogeneity.

(6) The well field design method was used in the example to calculate penalty costs (foregone benefits) due to lack of information on the true value of the mean, K_m , to be used in an exponential pdf. For the range of K_m examined, there were no penalty costs. This technique was extended to calculate the expected worth of more information using a Bayesian decision-theoretic formulation, by Bostock and Davis (1975).

(7) The heterogeneous analysis method can be extended to calculate a maximum safe time period over which non-simultaneous pumping can continue, without excessive effect on costs.

(8) Where previous knowledge of the spatial distribution of aquifer properties indicates different well field designs in different areas of the aquifer, multiple design analysis, with respect to the different areas, can be performed using the method presented here.

(9) The single cell aquifer response model was extended to represent a central cell and its immediately surrounding cells, in order to estimate bounds on inter-cell flow effects due to aquifer heterogeneity.

(10) The well field design method presented in this study is independent of the mathematical theory for groundwater flow used in the cell model.

(11) In Appendix, equations are developed for estimating errors associated with approximating the boundary shapes of hexagonal, square and equilateral cells by a circle of equal area. The errors were found to be negligible for practical well discharge capacities and aquifer transmissivities. Part of the error analysis was published previously (Bostock, 1971).

APPENDIX

CIRCULAR APPROXIMATION OF POLYGONAL CELL BOUNDARIES

In Chapter 3, a response model is given for an aquifer cell. The model is circular in the horizontal cross-section, but it represents polygonal cells having the three shapes resulting from the three possible uniform grid geometries. These cell shapes are hexagonal, square and equilateral triangular. The approximating circle has the same area as the polygon that it represents. The purpose of this Appendix is to develop equations for estimating the error in predicted drawdown at the well due to this cell boundary shape approximation.

First, we review the conditions which produce these cell boundary shapes. An infinite well field is one in which well locations form a repeating grid geometry that extends to infinity in all horizontal directions. We assume that all wells in the infinite grid discharge at the same rate. The most efficient grid geometries are those that are most regular or uniform; such that clustering of wells is minimized. Let us consider an infinite grid well field with uniformly spaced wells, in which all wells pump at the same rate and begin pumping at the same instant in time from static aquifer water level conditions. We assume that all aquifer properties are laterally constant. Then each well is enclosed by a boundary of no-flow in the aquifer. All of the boundaries have the same shape and size. For these conditions, the problem of calculating drawdown in the wells can be reduced to considering one

typical well in the infinite well field. Fiering (1964) uses this simplification for analyzing drawdown in an infinite square grid well field. Childs (1969, p. 413) also uses it.

Figure 1 depicts each grid geometry and corresponding no-flow boundary shape of the cells. For each of these grid patterns, let the dimension parameter defining spacing between wells be equal to the distance between any well and its nearest neighbors. Let the spacing parameters be b , l and p , for the equilateral triangular, square and hexagonal grid geometries, respectively. These distances are shown in Figures 14, 15 and 16. Then the area drained by the typical well in each of the three grid patterns, in terms of spacing parameter, is as follows:

<u>No-flow boundary shape</u>	<u>Grid geometry</u>	<u>Area drained by typical well</u>
Hexagonal	Equilateral triangular	$\{\sqrt{3}/2\}b^2$
Square	Square	l^2
Equilateral triangular	Hexagonal	$\{3\sqrt{3}/4\}p^2$

Let the density of wells per unit aquifer surface area be the same for each grid geometry. That is, let the area enclosed by the boundary of no flow for each geometry be the same. Let the circle having the same area have radius r_e . Then

$$\pi r_e^2 = \{\sqrt{3}/2\}b^2 = l^2 = \{3\sqrt{3}/4\}p^2 ,$$

where $b^2 = 2\pi r_e^2/\sqrt{3}$,

$l^2 = \pi r_e^2$, and

$p^2 = 4\pi r_e^2/\{3\sqrt{3}\}$.

Figure 20 is a circle, hexagon, square and equilateral triangle, each having the same area superimposed for comparison. The hexagon deviates least from the circle while the equilateral triangle deviates most.

There is no infinite, regular well field geometry that will produce a circular no-flow boundary. For impermeably bounded models of equal horizontal area, thickness, permeability and storage coefficient, the circular no-flow boundary model is the most efficient of all possible shapes. Therefore, it will be used as a basis for comparing the differences in drawdown resulting from each of hexagonal, square and equilateral triangular no-flow boundary shapes.

Witherspoon and others (1967, p. 105) provide a formula for the circular boundary case. This formula was derived by Muskat (1946, p. 657). It is for an aquifer model that is identical to the well-known Theis (1935) model with the exception that the Muskat formula model is bounded laterally by a no-flow boundary at finite radius r_e , from the center of the production well. In the Theis model, r_e is infinite. Otherwise, both aquifer models have homogeneous, isotropic permeability, K , constant storage coefficient, S , constant vertical thickness, H , horizontal, impermeable upper and lower boundaries, and the well, which is screened over the entire aquifer thickness, produces at constant

Figure 20. Circle, hexagon, square and equilateral triangle having equal areas, and superimposed for comparison.

rate, $-Q_w$, from time zero, when static piezometric head, h , condition prevailed throughout the aquifer. Another condition for these models is that the piezometric surface may never fall below the top of the aquifer, that is, no dewatering of the aquifer is allowed. Note that the flow in the artesian aquifer model is horizontal, and of constant, vertical thickness.

The infinite grid well field is such that each well draws its water from nearby in the aquifer. In practice, this condition arises only (1) with unconfined aquifers which receive areally uniform recharge by infiltration, or (2) with aquifers from which groundwater is being mined. In both of these cases, the groundwater flow system must have vertical components of flow because the major source of water is at the water table. In the artesian aquifer model, there are no vertical flow components. Also, in the unconfined aquifer, vertical thickness of flow decreases as the well is approached due to aquifer dewatering. Rigorous modelling of the unconfined aquifer conditions would require a three-dimensional, finite difference or finite element type of analysis, involving a moving upper boundary. Nevertheless, the use of a simpler, artesian aquifer model here is supported as follows. (1) The largest amount of aquifer dewatering in the unconfined aquifer occurs close to the well due to converging radial flow. This radial flow near the well must be nearly identical for the four, no-flow boundary shapes under consideration here. Therefore, the effect of dewatering near the well should be nearly the same in each case. Subtracting circular boundary drawdown from drawdowns due to each of the infinite grid boundary shapes should eliminate its effect. (2) The average horizontal distance of

flow for both unconfined and artesian models must be almost identical.

(3) The effect of vertical components is unknown; however, the writer estimates it to be of the same sign and similar magnitude, or smaller than the effect of horizontal flow components, because for practical well spacings the average horizontal distance of flow is greater than the average vertical distance of flow.

For the artesian aquifer model, the difference between drawdown produced with the no-flow boundary shape of any one of the three infinite well field grids, and drawdown produced by the circular boundary, may be calculated as follows. First, since the maximum difference is wanted, allow maximum drawdown before dewatering can occur, to be unlimited. Then, as pumping time, t , tends to infinity, the shape of the cone of depression in the piezometric surface within the no-flow boundary tends to a constant shape, that is, all parts of it reach a constant rate of decline in time, equal to $-Q_w/AS$, where A is the horizontal area enclosed by each no-flow boundary. Immediately after time zero when pumping starts, drawdown in the well will be practically independent of external boundary shapes. At the other extreme, as time tends to infinity, the difference between drawdowns at any instant produced by first, the circular no-flow boundary shape, and second, any one of the external no-flow boundary shapes, will tend to a maximum constant value. The objective is to determine this constant for each of the three infinite well field grids previously defined.

The following equations (Witherspoon and others, 1967, p. 105) allow calculation of drawdown for the circularly bounded artesian

aquifer. Note that x_m has been substituted here in place of $b_n r_e$ appearing in Witherspoon and others (1967).

$$P_{DC} = \left\{ \ln(r_D) + \frac{1+4t_D}{2r_D^2} - \frac{3}{4} - 2 \sum_{m=1}^{\infty} \frac{J_0\left(\frac{x_m}{r_D}\right) e^{-\left\{\frac{x_m}{r_D}\right\}^2 t_D}}{x_m^2 J_0^2(x_m)} \right\}$$

where P_{DC} = dimensionless pressure for circular no-flow boundary model,

$$= \frac{2\pi K H s_c}{-Q_w};$$

$$t_D = \text{dimensionless time} = \frac{K H t}{r^2 S};$$

$$r_D = \text{dimensionless radius} = \frac{r_e}{r}, J_1(x_m) = 0;$$

r_e = radial distance from well centerline to circular no-flow boundary.

Drawdown for the circular no-flow boundary is $s_c = \frac{-Q_w}{2\pi K H} P_{DC}$.

Drawdown for the polygonal boundary shapes can be determined using image well theory (Jacob, 1950, p. 376; Ferris and others, 1962, p. 144). Drawdown components from the central well and all image wells can be calculated using the infinite artesian aquifer model solution (Theis, 1935) as given by Witherspoon and others (1967, p. 6).

$$P_{DI} = \frac{1}{2} \left\{ -\gamma - \ln\left(\frac{1}{4t_D}\right) - \sum_{m=1}^{\infty} \frac{\left\{\frac{-1}{4t_D}\right\}^m}{m.m!} \right\}$$

where P_{DI} = dimensionless pressure for the laterally infinite artesian aquifer model,

$$P_{DI} = \frac{2\pi K H s_I}{-Q_w};$$

$$t_D = \text{dimensionless time} = \frac{K H t}{r^2 S};$$

$$\gamma = \text{constant} = .5772\dots$$

Thus, drawdown at the well at center of a cell having any of the three polygonal shapes is

$$\sum_{n=1}^{\infty} s_{In} = \frac{-Q_w}{2\pi K H} \sum_{n=1}^{\infty} P_{DIn}$$

where n indicates that P_{DIn} is to be calculated using the distance to the n -th well, r_n , in the appropriate array of image wells (see Figure 1).

That is, $t_{DN} = \frac{K H t}{r_n^2 S}$. When $n = 1$, $r_n = r_w$, the radius of the central

well's screen.

Thus, the maximum departure of any one of the three infinite grid no-flow boundary model drawdowns from the circular no-flow boundary model is

$$\lim_{t \rightarrow \infty} \left\{ \sum_{n=1}^{\infty} s_{In} - s_c \right\} = \frac{-Q_w}{2\pi K H} \left\{ \lim_{t \rightarrow \infty} \left\{ \sum_{n=1}^{\infty} P_{DIn} - P_{DC} \right\} \right\}.$$

Note that P_{DC} and P_{DI1} are both functions of well screen radius, r_w , at model center, and that r_w does not occur anywhere else in the expression. r_w has no effect on the interference drawdown produced by the model boundaries.

By the following procedure, r_w can be eliminated. For $n = 1$, subtract P_{DC} from P_{DI1} . Take the limit as r_w goes to zero. Note that

$$(1) \lim_{r_w \rightarrow 0} J_0 \left(\frac{x_n r_w}{r_e} \right) = 1; \quad (2) \lim_{r_w \rightarrow 0} \frac{1}{\left\{ \frac{4KHt}{r_w^2 S} \right\}} = 0; \quad (3) \text{ in the expression for}$$

P_{DC} , t_d is always divided by r_D so that $\frac{t_D}{r_D} = \frac{KHt}{r_e^2 S}$ which is independent of

r_w . Therefore,

$$\lim_{r_w \rightarrow 0} \{P_{DII} - P_{DC}\} = \frac{1}{2} \left\{ \gamma - 1.5 + \ln \left(\frac{1}{4t_{De}} \right) + 4t_{De} - \sum_{m=1}^{\infty} \frac{e^{-x_m^2 t_{De}}}{x_m^2 J_0^2(x_m)} \right\}.$$

where $t_{De} = \frac{KHt}{r_e^2 S}.$

Let this quantity be P_{De} . It represents the component of dimensionless pressure due to interference effects from the circular no-flow boundary.

Next, we consider how to evaluate the remaining part, $\sum_{n=2}^{\infty} P_{DIn}$.

This is done by evaluating P_{DIn} for each image well in the appropriate grid (see Figure 1). As the radial distance to the n -th image well, r_n , increases, P_{DIn} decreases. Usual practice when dealing with infinite image well systems is to add the individual effects of image wells out to the point where the effect associated with the addition of the next more distant wells can be considered to have negligible influence on the cumulative effect (Ferris and others, 1962, p. 159). Drawdown components due to all more distant wells to infinite distance are omitted. Bostock (1971) gave an estimation of the error due to truncating distant image wells. Basic to the analysis is the assumption that the interference due to wells beyond some distance which is large relative to

the grid spacing between wells, can be treated as though it were due to an areally uniform groundwater discharge. Results of the analysis indicate that the usual practice of truncating the infinite image well system, as described above, is quite accurate.

Values of the expression $\left\{ \sum_{n=2}^{\infty} P_{DIn} + P_{De} \right\}$, for specified values of pumping duration, t , were obtained from a computer program, using double precision, on a CDC 6400 computer. It was found that for increasing values of t , this expression tended toward a constant, maximum value, depending on which infinite grid geometry was used. The estimated maximum relative error for the three constants is 3×10^{-3} . The maximum differences in drawdown between each of the polygonal cells and the equivalent circular approximation are as follows. The maximum departure of the hexagonal no-flow boundary model drawdown from the circular no-flow boundary model drawdown is $\frac{|-Q_w|}{2\pi KH} (1.25 \times 10^{-4})$, and that for the square no-flow boundary model drawdown is $\frac{|-Q_w|}{2\pi KH} (1.88 \times 10^{-3})$, and that for the equilateral triangular no-flow boundary model drawdown is $\frac{|-Q_w|}{2\pi KH} (7.32 \times 10^{-2})$. These results are a measure of the groundwater extraction efficiency of each infinite well field grid geometry. They indicate that the equilateral triangular grid, which produces hexagonal no-flow boundaries in the aquifer about each well, is the most efficient of the three grid geometries investigated.

The maximum departure of an assumed circular boundary drawdown calculation from any of the three grid boundary drawdowns, will be greatest for large Q/KH ratio values. For example, letting $Q = -\pi$ cubic

feet per second and $KH = .005$ cubic feet per second, per foot, gives 0.0125 feet, 0.188 feet, and 7.0 feet of departure for the equilateral triangular, square and hexagonal well grids, respectively. Since this Q/KH ratio is extremely large for any real well field, it may be concluded that the circular boundary approximates the hexagonal and square boundaries sufficiently well, but the approximation may be poor for the equilateral triangular boundary, when Q/KH is large.

NOMENCLATURE

- [] square brackets enclose dimension symbols.
- () round brackets enclose independent variables of a function and immediately follow the function symbol.
- { } "pinched" brackets designate hierarchy of arithmetic operations.
- / slash denotes division, which is always performed after all multiplication, except where pinched brackets intervene.
- b well spacing parameter for equilateral triangular grid and hexagonal no-flow boundary shape.
- c constant of proportionality between pumping energy consumed and pumping cost, [$\$/L^4$].
- D total seasonal demand, [L].
- D_i maximum instantaneous demand rate, [L/T].
- E pump efficiency, approximated by a constant fraction.
- g acceleration due to gravity, a constant, [L/T^2].
- h Dupuit head, a constant in the vertical direction, [L].
- $h_{i,j}$ head within the i-th annulus of the finite difference model during the time interval, Δt_j , [L].
- h_w water level in well, [L].
- h piezometric head, [L].
- H uniform thickness of horizontal, artesian aquifer, [L].
- i subscript for referencing properties of the i-th annulus in finite difference aquifer cell model.

j	subscript indicating a specific time instant, t_j , at the end of the j -th time interval, Δt_j .
k	subscript for referencing radii in finite difference aquifer cell model.
K	aquifer permeability, $[L/T]$.
K_i	permeability between node i and node $i+1$ of the aquifer response model, $[L/T]$.
K_m	mean permeability, $[L/T]$.
l	well spacing parameter for square grid, with square no-flow boundary shape.
L	length dimension.
m_0	initial saturated thickness of aquifer, $[L]$.
m	average value of h in both space out to r_e , and in time, up to time t , $[L]$.
M	mass dimension.
n	number of annuli in finite difference aquifer model.
n_a	number of annuli in central cell part of cylindrical sink finite difference model.
n_b	number of annuli in doughnut part of cylindrical sink finite difference model.
n_d	the n_d -th annulus of the cylindrical sink model is the cylindrical sink itself.
N_w	well density per unit ground surface area, $[well/L^2]$.
p	absolute pressure, $[M/LT^2]$. Also, well spacing parameter for hexagonal grid and equilateral triangular no-flow boundary shape.
p_0	atmospheric pressure, a constant, $[M/LT^2]$.

- q_i flow into i -th annulus of finite difference aquifer cell model, from ground surface, $[L^3/T]$.
- Q_c well design discharge rate, or capacity (the minus sign is dropped, for convenience, although a negative design recharge rate is intended), $[L^3/T \text{ well}]$.
- Q_r total flow rate of fluid crossing a vertical cylindrical surface at radius r , in the aquifer, positive outwards, $[L^3/T \text{ well}]$.
- Q_w well recharge rate. When Q_w is positive, it represents well recharge rate, when negative, well discharge rate. $Q_w(t)$ is a function of time, $[L^3/T \text{ well}]$.
- Q_{wj} average well recharge rate during the time interval, Δt_j , $[L^3/T \text{ well}]$.
- r radial distance from axis of cylindrical coordinate system, $[L]$.
- r_a radius of central cell and of satellite cell in cylindrical sink model, $[L]$.
- r_e radius of outer cylindrical boundary of cylindrical aquifer response model, $[L]$.
- r_i radii of annuli nodes, when i is a whole number. When i is a mixed number, it refers to annuli boundaries, $[L]$.
- r_k radii of annuli nodes and boundaries referenced by integer subscripts.
- r_w well radius, $[L]$.
- s_0 pumping lift to pump outlet elevation at ground surface, from initial static water level in well, $[L]$.
- s_a head loss in aquifer below initial static water level, $[L]$.
- s_{aj} average value of s_a during Δt_j , $[L]$.

$s_{a \max}$	maximum value of s_a , [L].
$s_{b \max}$	maximum available drawdown, a property of the aquifer and its piezometric head state, [L].
s_f	pump efficiency head loss due to friction in pump bowls, column and pump head, including velocity head at pump outlet, [L].
$s_{\max}$	maximum drawdown, difference in elevation between initial static water level in well and elevation of top of pump intake screen, [L].
s_p	pump outlet pressure head, [L].
s_w	head loss across well screen and along well casing to pump screen, [L].
S	aquifer storage coefficient.
S_y	aquifer specific yield, a constant in time and space.
S_{yi}	specific yield of the i -th annulus of the finite difference aquifer response model.
t	time coordinate; duration of pumping since time zero when static water level conditions prevailed in the aquifer, [T].
$t_{\max}$	maximum length of pumping season, [T].
$t_{\min}$	minimum possible time in which D can be met by pumping at rate D_i , [T].
t_s	maximum, safe period for non-simultaneous pumping, [T].
Δt_j	time interval between t_{j-1} and t_j , [T].
T	time dimension.
$T_{i,j}$	transmissivity between node i and node $i+1$, during time interval Δt_j , $[L^2/T]$.

U_i	flow rate, in the direction r , across the i -th annulus' outer wall at radius $r_{i+1/2}$, [L^3/T].
V	value of water at pump outlet per unit volume, [L^3].
x	x -coordinate of rectangular coordinate system, [L].
y	y -coordinate of rectangular coordinate system, [L].
z	z -coordinate of rectangular and cylindrical coordinate system, [L].
z_s	aquifer free surface boundary, [L].
ρ	density of water, a constant, [M/L^3].
θ	radian angle of cylindrical coordinate system, [L/L].

LITERATURE CITED

- Ahrens, T. P. 1970. Basic considerations of well design. Water Well Journal; April, May, June, August; 45-50, 49-51, 47-51, 35-37.
- Bostock, C. A. 1971. Estimating truncation error in image well theory. Water Resources Res., 7(6), 1658-1660.
- Bostock, C. A., and D. R. Davis. 1975. Application of Bayesian decision theory in well field design. Paper given at joint annual meeting of the Arizona Section, American Water Resources Association, and the Hydrology Section, Arizona Academy of Sciences, held at Tempe, Arizona, April. Proceedings to appear.
- Charny, I. A. 1951. A rigorous derivation of Dupuit's formula for unconfined seepage with seepage face. Proceedings of the Academy of Sciences, U.S.S.R., 79(6).
- Childs, E. C. 1969. An Introduction to the Physical Basis of Soil Water Phenomena. New York: John Wiley and Sons, Ltd. 463 pp.
- Cobb, E. L. 1974. Two tests for the cluster well concept. Water Well Journal; February; 16-18, 23.
- Cook Well Strainer Co. 1965. Areas per lineal foot of Cook type W. W. strainers. Form STR2-1, revised, September.
- _____. 1966. Price list applying to catalogs (1252, 1252a, 1252b), dated April 1.
- Coolley, R. L. 1971. A finite difference method for unsteady flow in variably saturated porous media: Application to a single pumping well. Water Resources Res., 7(6), 1607-1625.
- _____. 1972. Numerical simulation of flow in an aquifer overlain by a water table aquitard. Water Resources Res., 8(4), 1046-1050.
- Cooper, H. H., Jr., and C. E. Jacob. 1946. A generalized graphical method for evaluating formation constants and summarizing well-field history. Trans. Amer. Geophys. Union, 27(4), 526-534.
- Deb, A. K., and A. K. Sarkar. 1971. Optimization in design of hydraulic network. Proc. Amer. Soc. Civil Eng., Jour. San. Eng. Div., 97(SA2), 141-159.

- Deininger, R. A. 1970. Systems analysis of water supply systems. Jour. of Amer. Water Resources Assoc., 6(4), 573-580.
- Encyclopaedia Britannica. 1967. Vol. 10. Chicago: Encyclopaedia Britannica.
- Ferris, J. G., D. B. Knowles, R. H. Brown and R. W. Stallman. 1962. Theory of aquifer tests; ground water hydraulics. U. S. Geol. Surv. Water Supply Paper, 1536-E, U. S. Government Printing Office, Washington, D. C., 69-173.
- Fiering, M. B. 1964. A digital computer solution for well field drawdown. Bull. Int'l. Assoc. Sci. Hydrol., IX^e Annee, 4, 16-23.
- Freeze, R. A. 1969. Theoretical analysis of regional groundwater flow. Scientific Series No. 3, Inland Waters Branch, Department of Energy, Mines and Resources (now Environment), p. 147.
- Hantush, M. S. 1956. Analysis of data from pumping tests in leaky aquifers. Trans. Amer. Geophys. Union, 37, 702-714.
- _____. 1961. Economical spacing of interfering wells, in "Ground Water in Arid Zones." Int'l Assoc. Sci. Hydrol., Publ. 57, 350-364.
- _____. 1962a. Flow of ground water in sands of nonuniform thickness. Part I: Flow in a wedged-shaped aquifer. Jour. Geophys. Res., 67(2), 703-709. Part II: Approximate theory. Jour. Geophys. Res., 67(2), 711-720. Part III: Flow to wells. Jour. Geophys. Res., 67(4), 1527-1534.
- _____. 1962b. Hydraulics of gravity wells in sloping sands. Proc. Amer. Soc. Civil Eng., Jour. Hydraulics Div., HY4, 1-15.
- _____. 1964. Hydraulics of wells. Advances in Hydroscience, Vol. 1. New York: Academic Press, 281-442.
- Jacob, C. E. 1950. Flow of groundwater. Engineering Hydraulics, (H. Rouse, ed.). New York: John Wiley and Sons, Ltd. 321-386.
- Johnson E. E., Inc. 1966. Ground Water and Wells, a Reference Book for the Water Well Industry. St. Paul: U. O. P. Johnson Division. 440 pp.
- Kally, E. 1969. Pipeline planning by dynamic computer programming. Jour. Amer. Water Works Assoc., 61(3), 114-118.
- _____. 1971. Automatic planning of the least-cost water distribution network. Water and Water Engineering, 75(902), 148-152.

- Karim, M. A. 1968. Optimization of water resources for irrigation in Dinajpur and Rangpur. M.S. thesis, The University of Arizona, Tucson, 147 pp.
- Liang, T. 1971. Design conduit system by dynamic programming. Proc. Amer. Soc. Civil Eng., Jour. Hydraulics Div., 97(HY3), 383-393.
- Maddock, T., III. 1972. Algebraic technological function from a simulation model. Water Resources Res., 8(1), 129-134.
- _____. 1974. Nonlinear technological functions for aquifers whose transmissivities vary with drawdown. Water Resources Res., 10(4), 877-881.
- Muskat, M. 1946. The Flow of Homogeneous Fluids through Porous Media. 2nd printing. Ann Arbor: J. W. Edwards, Inc. 763 pp.
- Nelson, A. G., and C. D. Busch. 1967. Cost of pumping irrigation water in central Arizona. Arizona Agricultural Experimental Station Tech. Bull. 182. College of Agriculture, University of Arizona, Tucson.
- Neuman, S. P. 1972. Theory of flow in unconfined aquifers considering delayed response of the water table. Water Resources Res., 8(4), 1031-1045.
- _____. 1973. Supplementary comments on "Theory of flow in unconfined aquifers considering delayed response of the water table." Water Resources Res., 9(4), 1102-1103.
- _____. 1974. Effect of partial penetration on flow in unconfined aquifers considering delayed gravity response. Water Resources Res., 10(2), 303-312.
- Neuman, S. P., and P. A. Witherspoon. 1971. Analysis of nonsteady flow with a free surface using the finite element method. Water Resources Res., 7(3), 611-623.
- Nind, T. E. W. 1964. Groundwater lecture notes. Unpublished, University of Saskatchewan, Saskatoon, Canada.
- Prickett, T. A., and C. G. Lonnquist. 1971. Selected digital computer techniques for groundwater resource evaluation. Bull. 55, Illinois State Water Survey, Urbana. 62 pp.
- Raman, V. 1970. Developments in Water system network design. Proc. Amer. Soc. Civil Eng., Jour. San. Eng. Div., 96 (SA5), 1249-1263.
- Rushton, K. R. 1974. Extensive pumping from unconfined aquifers. Water Resources Bull., 10(1), 32-41.

- Standard Mathematical Tables. 1970. Student edition, 18th edition.
Cleveland: The Chemical Rubber Co. 724 pp.
- Supkow, D. J. 1972. Transmissivity distribution in the Tucson basin aquifer. Proceedings of the Prescott meeting of the Hydrology Section, Arizona Academy of Science, and the Arizona Section, American Water Resources Association, May.
- Theis, C. V. 1935. The relation between the lowering of the piezometric surface and the rate and duration of discharge of a well using groundwater storage. Trans. Amer. Geophys. Union, 16th Annual Meeting, part 2, 519-524.
- _____. 1957. The spacing of pumped wells. Ground Water Notes, No. 31 (open file for distribution in the Ground Water Branch only), U. S. G. S. Water Resour. Div., Ground Water Branch, 4 pp.
- Tipton and Kalmbach, Inc., Engineers (Denver, Colorado). 1960. Feasibility report on salinity control and reclamation project number two (Chaj. Dvab.). West Pakistan Water and Power Development Authority.
- Todd, D. K. 1959. Ground Water Hydrology. New York: John Wiley and Sons, Inc. 336 pp.
- Walton, W. C. 1970. Groundwater Resource Evaluation. New York: McGraw-Hill. 664 pp.
- Witherspoon, P. A., I. Javandel, S. P. Neuman and R. A. Freeze. 1967. Interpretation of Aquifer Gas Storage Conditions from Water Pumping Tests. New York: American Gas Association, Inc. 272 pp.