INFORMATION TO USERS

This material was produced from a microfilm copy of the original document. While the most advanced technological means to photograph and reproduce this document have been used, the quality is heavily dependent upon the quality of the original submitted.

The following explanation of techniques is provided to help you understand markings or patterns which may appear on this reproduction.

1. The sign or "target" for pages apparently lacking from the document photographed is "Missing Page(s)". If it was possible to obtain the missing page(s) or section, they are spliced into the film along with adjacent pages. This may have necessitated cutting thru an image and duplicating adjacent pages to insure you complete continuity.
2. When an image on the film is obliterated with a large round black mark, it is an indication that the photographer suspected that the copy may have moved during exposure and thus cause a blurred image. You will find a good image of the page in the adjacent frame.
3. When a map, drawing or chart, etc., was part of the material being photographed the photographer followed a definite method in "sectioning" the material. It is customary to begin photoing at the upper left hand corner of a large sheet and to continue photoing from left to right in equal sections with a small overlap. If necessary, sectioning is continued again — beginning below the first row and continuing on until complete.
4. The majority of users indicate that the textual content is of greatest value, however, a somewhat higher quality reproduction could be made from "photographs" if essential to the understanding of the dissertation. Silver prints of "photographs" may be ordered at additional charge by writing the Order Department, giving the catalog number, title, author and specific pages you wish reproduced.
5. PLEASE NOTE: Some pages may have indistinct print. Filmed as received.

Xerox University Microfilms

300 North Zeeb Road
Ann Arbor, Michigan 48106

76-22,486

WU, Sherman Shou-Chou, 1928-
MARS SYNTHETIC TOPOGRAPHIC MAPPING.

The University of Arizona, Ph.D., 1976
Engineering, civil

Xerox University Microfilms, Ann Arbor, Michigan 48106

© 1976

SHERMAN SHOU-CHOU WU

ALL RIGHTS RESERVED

MARS SYNTHETIC TOPOGRAPHIC MAPPING

by

Sherman Shou-Chou Wu

A Dissertation Submitted to the Faculty of the
DEPARTMENT OF CIVIL ENGINEERING AND ENGINEERING MECHANICS

In Partial Fulfillment of the Requirements
For the Degree of

DOCTOR OF PHILOSOPHY
WITH A MAJOR IN CIVIL ENGINEERING

In the Graduate College
THE UNIVERSITY OF ARIZONA

1 9 7 6

Copyright 1976 Sherman Shou-Chou Wu

THE UNIVERSITY OF ARIZONA

GRADUATE COLLEGE

I hereby recommend that this dissertation prepared under my
direction by Sherman Shou-Chou Wu
entitled Mars Synthetic Topographic Mapping
_____ be accepted as fulfilling the dissertation requirement of the
degree of Doctor of Philosophy

Philip B Newlin 4/19/76
Dissertation Director Date

After inspection of the final copy of the dissertation, the
following members of the Final Examination Committee concur in
its approval and recommend its acceptance:*

<u>Lawrence M. Coe</u>	<u>4/19/76</u>
<u>A. J. Malville</u>	<u>4/19/76</u>
<u>Philip B. Newlin</u>	<u>4/19/76</u>
_____	_____
_____	_____

*This approval and acceptance is contingent on the candidate's adequate performance and defense of this dissertation at the final oral examination. The inclusion of this sheet bound into the library copy of the dissertation is evidence of satisfactory performance at the final examination.

STATEMENT BY AUTHOR

This dissertation has been submitted in partial fulfillment of requirements for an advanced degree at The University of Arizona and is deposited in the University Library to be made available to borrowers under rules of the Library.

Brief quotations from this dissertation are allowable without special permission, provided that accurate acknowledgment of source is made. Requests for permission for extended quotation from or reproduction of this manuscript in whole or in part may be granted by the copyright holder.

SIGNED: Sherman D. C. White

TO MY PARENTS

PREFACE

The study of Mars topographic synthesis is an extended scientific research of the Mariner Mars missions, and will provide information for the preparation of the Viking Mars missions which will consist of landing two scientific packages on the surface of Mars at the time of the bicentennial celebration of the United States. It is being conducted at the Center of Astrogeology, U.S. Geological Survey, and funded by the National Aeronautics and Space Administration (NASA). Since this experiment synthesizes data from various sources, it relates to many other research institutes. They include the Jet Propulsion Laboratory of the California Institute of Technology, Department of Earth and Planetary Science of the Massachusetts Institute of Technology, Laboratory for Atmospheric and Space Physics of the University of Colorado, NASA Goddard Space Flight Center, the Rand Corporation, as well as the Goldstone, Haystack, Arecibo and Kitt Peak observatories.

The result of this experiment is the first comprehensive contour map of the surface of Mars. The description of this experiment is divided into five parts. Part I describes the figure of Mars and defines its topographic datum in terms of its gravity field. Part II discusses the methods and procedures of deriving topographic contours for the entire planet using the data from various scientific experiments and includes a brief description of each of the various data sources. Part III describes techniques of contouring local features at relatively large scales by stereo photogrammetric methods

including the establishment of a control net for those areas which are covered by a number of stereo models. Part IV includes discussions and conclusions. Part V includes appendices and references, which contain the development of formulas and lists some of the important data. Since this topographic map is derived from the synthesis of a very large amount of data, which cannot all be attached, the citation of all references should be helpful and useful for those who intend to utilize that data for further studies.

A remark should be made at this point, that because of the inadequacy of the information for covering the entire planetary surface of Mars, the contour maps compiled from this experiment are very preliminary. Also, the map accuracy is very difficult to define since some of the data sources do not have enough information to perform an analysis. It can be foreseen right away that these maps will frequently be revised whenever more information becomes available.

To list all of the many persons who have supported, assisted, and contributed in some way to this experiment, would be monumental task. However, the author wishes to particularly express his appreciation to Harold Masursky, the team leader of the television experiment of Mariner Mars 1971, for his initiation of the study of Mars topographic mapping, and to other investigators of various experiment teams of the Mariner 9 mission, for the various data sources supplied by them. They are: J. Lorell, J. F. Jordan, E. J. Christensen, A. Kliore, and R. M. Goldstein of the Jet Propulsion Laboratory of the California Institute of Technology; C. Barth, and C. Hord of the University of

Colorado; G. H. Pettengill and R. Reasenberg of the Massachusetts Institute of Technology; J. Pearl of the NASA Goddard Space Flight Center; Raymond Batson and his associates involved in planetary cartography at the U.S. Geological Survey; and M. E. Davies of the Rand Corporation. The author is indebted to the entire Photogrammetry Unit of the Center of Astrogeology, U.S. Geological Survey, for their great assistance and continuing technical and moral support. They are: F. J. Schafer, A. G. Dahl, Raymond Jordan, G. M. Nakata, J.J. Stapleton, B. C. Philpott, J. J. Cole, and M. A. Stough. To be specific, under his supervision, they performed almost all of the compilations of non-image data and measurements of stereo models on photogrammetric instruments. He would also like to express his appreciation to G. W. Colton and H. J. Moore of the U.S. Geological Survey for their kind help in completely reviewing this paper; to James Van Divier, R. E. Sabala and R. D. Carroll, also of the U.S. Geological Survey, for their preparation of maps and illustrations.

Special thanks go to Professors D. C. Merchant of Ohio State University and P. B. Newlin, Q. M. Mees and A. J. Malvick of the University of Arizona, and M. H. Carr, E. C. Morris, J. F. McCauley, G. A. Swann and J. D. Alderman of the U.S. Geological Survey, for all the necessary arrangements made by them for the author's Ph.D. program. Without their advice, this paper could not have been written.

Last, but not least, the author wants to express his appreciation to all of those who have reviewed the contour maps and expressed their opinions.

This paper was performed under JPL contract W0-8122, NASA contracts L-55232 (Viking Project Office), and W-13687 and W-13709 (Planetology Project Office).

TABLE OF CONTENTS

	Page
LIST OF ILLUSTRATIONS	xi
LIST OF TABLES.	xv
ABSTRACT.	xvi
PART I. FIGURE, SIZE, AND GRAVITY FIELD OF MARS AND ITS TOPOGRAPHIC DATUM	
	1
CHAPTER	
1. INTRODUCTION	2
1.1 Statement of Objectives	2
1.2 Mars.	4
1.3 Summary of the Mariner Mars Missions.	9
1.3.1 Mariner-Mars 1964.	10
1.3.2 Mariner-Mars 1969.	11
1.3.3 Mariner-Mars 1971.	13
1.4 Mapping Strategy.	15
2. COORDINATE SYSTEM AND MAP PROJECTIONS.	18
2.1 Martian Coordinate System	18
2.2 Map Scale and Format.	21
2.3 Map Projections	23
2.3.1 Mercator Conformal Projection.	25
2.3.2 Lambert Conformal Conic Projection	26
2.3.3 Polar Stereographic Conformal Projection	29
3. THE GRAVITY FIELD, FIGURE, AND TOPOGRAPHIC DATUM OF MARS .	33
3.1 The Gravity Field of Mars	33
3.2 The Figure of Mars.	37
3.3 The Topographic Datum of Mars	43

TABLE OF CONTENTS--Continued

	Page
PART II. CONTOURING THE ENTIRE PLANET OF MARS USING NON-IMAGING TOPOGRAPHIC DATA	46
4. NON-IMAGING TOPOGRAPHIC DATA SOURCES OF MARINER 9.	47
4.1 S-Band Radio Occultation.	48
4.2 Ultraviolet Spectrometer (UVS).	49
4.3 Infrared Interferometer Spectrometer (IRIS) and Infrared Radiometer (IRR).	49
5. EARTH-BASED RADAR DATA	54
6. DATA REDUCTION AND ELEVATION ADJUSTMENT.	59
6.1 Data Reduction.	59
6.2 Elevation Adjustment.	60
6.2.1 Elevation Adjustment of Radar Data	61
6.2.2 Elevation Adjustment of Infrared Interferometer Spectrometer Data.	63
6.2.3 Elevation Adjustment of Ultraviolet Spectrometer Data	63
7. TOPOGRAPHIC CONTOUR MAPS OF MARS	65
7.1 Contouring Methods and Procedures	65
7.2 Nomenclature.	66
7.3 Topographic Contour Maps of Mars (1:25,000,000 and 1:5,000,000)	67
PART III. CONTOURING BY STEREO PHOTOGRAMMETRIC METHODS USING TELEVISION PICTURES OF MARINER 9.	99
8. MARINER 9 MARS IMAGERY	100
8.1 Television Cameras.	100
8.2 Photography	101
8.3 Image Processing.	103

TABLE OF CONTENTS--Continued

	Page
9. NON-CONVENTIONAL PHOTOGRAMMETRIC METHOD.	104
10. BLOCK ADJUSTMENT	112
10.1 Theoretical Approach (Formula Derivation).	112
10.2 Practical Application (Coordinate Measurement and Data Processing).	123
10.2.1 Conditions of the Selected Photographs . . .	123
10.2.2 Photo Coordinate Measurement	123
10.2.3 Coordinate Refinement.	124
Film Shrinkage Correction	124
Lens Distortion Correction.	125
Curvature Correction.	125
Results of Corrections.	126
10.2.4 Block Adjustment Programming	126
PART IV. DISCUSSIONS AND CONCLUSIONS.	130
11. DISCUSSIONS, CONCLUSIONS, AND RECOMMENDATIONS.	131
11.1 Problems	131
11.2 Discussions.	132
11.2.1 The Use of Earth-Based Radar Data.	132
11.2.2 Martian Flattening	137
11.3 Conclusions.	137
11.4 Recommendations.	140
11.4.1 Revision of the Mars Contour Maps.	140
11.4.2 Compilation of Large Scale Mars Maps	140
11.4.3 Publication of Topographic Data.	141
11.4.4 Modification of the Mercator Projection. . .	141
11.4.5 Primary Control Net.	141
11.4.6 Mars Figure for Radar Observations	142
APPENDIX A. DATUM AND CONTROL OF MARS TOPOGRAPHY.	143
APPENDIX B. ASSOCIATED LEGENDRE FUNCTION $P_{nm}(\sin \phi)$	165
SELECTED BIBLIOGRAPHY.	166

LIST OF ILLUSTRATIONS

Figure	Page
2-1. Location of the Martian prime meridian of longitude which passes through the crater Airy-0.	20
2-2. Map sheet layout for mapping Mars at the scale of 1:5,000,000	22
2-3. Quadrangle layout and map projections for the 1:5,000,000 Mars map series	24
2-4. Grid of Mercator conformal projection with 5° increments in both longitude and latitude for 1:5,000,000 (45° x 30°) quadrangle maps MC-8 to MC-23	26
2-5. Grid of Lambert conformal conic projection (two standard parallels) with 5° increments in both longitude and latitude for 1:5,000,000 (60° x 35°) quadrangle maps MC-2 to MC-7 and MC-24 to MC-29	30
2-6. Grid of the polar stereographic projection with 5° increments in both longitude and latitude for 1:5,000,000 quadrangle maps MC-1 and MC-30.	32
3-1. Contour map of gravitational potential of Mars, fourth degree and order spherical harmonics, with J ₂ set equal to zero	38
3-2. Contour map of the areopotential of Mars, in terms of fourth degree and order spherical harmonics and including J ₂ and centrifugal force.	39
3-3. Contour map of the topographic datum of Mars.	45
4-1. Locations of all occultation points distributed over the entire planet of Mars	50
4-2. Locations of elevation points converted from ultraviolet spectrometer measurements from Mariner 9.	51
4-3. Locations of elevation points provided by the infrared interferometer spectrometer experiment of Mariner 9	53

LIST OF ILLUSTRATIONS--Continued

Figure	Page
5-1. Locations of ground-based radar measurements of Mars including 1967, 1969 and 1971 oppositions at Haystack Observatory, Massachusetts.	57
5-2. Locations of ground-based radar measurements of Mars including 1969, 1971 and 1973 oppositions at Goldstone Observatory, California.	58
7-1. Topographic contour map of Mars.	68
7-2. Topographic contour map of the Diacria quadrangle of Mars.	69
7-3. Topographic contour map of the Arcadia quadrangle of Mars.	70
7-4. Topographic contour map of the Mare Acidalium quadrangle of Mars.	71
7-5. Topographic contour map of the Ismenius Lacus quadrangle of Mars.	72
7-6. Topographic contour map of the Casius quadrangle of Mars	73
7-7. Topographic contour map of the Cebrenia quadrangle of Mars	74
7-8. Topographic contour map of the Amazonis quadrangle of Mars	75
7-9. Topographic contour map of the Tharsis quadrangle of Mars.	76
7-10. Topographic contour map of the Lunae Palus quadrangle of Mars	77
7-11. Topographic contour map of the Oxia Palus quadrangle of Mars	78
7-12. Topographic contour map of the Arabia quadrangle of Mars	79
7-13. Topographic contour map of the Syrtis Major quadrangle of Mars	80
7-14. Topographic contour map of the Amenthes quadrangle of Mars	81
7-15. Topographic contour map of the Elysium quadrangle of Mars.	82
7-16. Topographic contour map of the Memnonia quadrangle of Mars	83

LIST OF ILLUSTRATIONS--Continued

Figure	Page
7-17. Topographic contour map of the Phoenicis Lacus quadrangle of Mars.	84
7-18. Topographic contour map of the Coprates quadrangle of Mars	85
7-19. Topographic contour map of the Margaritifer Sinus quadrangle of Mars	86
7-20. Topographic contour map of the Sinus Sabaeus quadrangle of Mars.	87
7-21. Topographic contour map of the Iapygia quadrangle of Mars.	88
7-22. Topographic contour map of the Mare Tyrrhenum quadrangle of Mars.	89
7-23. Topographic contour map of the Aeolis quadrangle of Mars .	90
7-24. Topographic contour map of the Phaethontis quadrangle of Mars	91
7-25. Topographic contour map of the Thaumasia quadrangle of Mars	92
7-26. Topographic contour map of the Argyre quadrangle of Mars .	93
7-27. Topographic contour map of the Noachis quadrangle of Mars.	94
7-28. Topographic contour map of the Hellas quadrangle of Mars .	95
7-29. Topographic contour map of the Eridania quadrangle of Mars	96
7-30. Topographic contour map of the Mare Australe quadrangle of Mars.	97
7-31. Topographic contour map of the Mare Boreum quadrangle of Mars	98
8-1. Reseau grid for camera A vidicon on board Mariner 9. . . .	102
8-2. Reseau grid for camera B vidicon on board Mariner 9. . . .	102

LIST OF ILLUSTRATIONS--Continued

Figure		Page
9-1.	Geometric configuration for setting up models with non-conventional model geometry on an analytical stereo-plotter.	105
9-2.	Photo map of the Mars Canyonlands	109
9-3.	Photo map of Olympus Mons, the largest volcano on the Martian surface	111
10-1.	Relationships between the camera station (perspective center), the image plane (photo coordinates), and the ground object (survey point).	113
11-1.	Comparison between the parameters of the triaxial ellipsoid and the 6.1 mb gravity datum.	133
11-2.	Displacement of the center of mass from the center of figure.	135
11-3.	Relationship between the radii from a point P on the triaxial ellipsoidal datum to the center of figure and the center of mass.	136
11-4.	Topographic profile along the Martian equator	138

LIST OF TABLES

Table	Page
2.1. Scale variations in the Mercator conformal projection of the 1:25,000,000 map.	27
3.1. The fourth degree and fourth order gravity coefficients of Mars--from Mariner 9 radio-tracking data	37
5.1. Topographic information from ground-based radar observation of Mars	55
10.1. Results of the photo coordinate refinement.	127
A1.1. Topographic datum of Mars	144
A1.2. Radio occultation data from Mariner Mars 9 mission.	152

ABSTRACT

Topographic contour maps of Mars are compiled by the synthesis of data acquired from various scientific experiments of the Mariner 9 mission in 1971, which includes topographic information derived from different sources, such as S-band radio-occultation, the UVS-ultraviolet spectrometer, the IRR-infrared radiometer, the IRIS-infrared interferometer spectrometer and television imagery, as well as radar information collected by Earth-based observatories at Goldstone, Haystack and Arecibo. The entire planet is mapped at scales of 1:25,000,000 and 1:5,000,000 using the non-imagery topographic data.

For the computation of map projections, a two-axial spheroid figure is adopted. The semi-major and semi-minor axes are 3,393.4 km and 3,375.7 km respectively, with a polar flattening of 0.0052 or $\frac{1}{192}$. The planet eccentricity is 0.101849. For the 1:25,000,000 scale map, the Mercator projection is used between the 65° parallels, and the polar stereographic projection is used from the polar region both north and south of the 55° parallels. For the 1:5,000,000 maps, the Mercator projection is used for the equatorial region between the 30° parallels; the Lambert conformal conic projection is used between parallels 30° to 65° , and the polar stereographic projection is used for the polar regions both north and south of the 65° parallels.

For the computation of elevations, a topographic datum is defined by a gravity field described in terms of spherical harmonics of fourth order and fourth degree combined with a 6.1 millibar occultation

pressure surface. This areoid can be approximated by a triaxial ellipsoid with semi-major axes of $A=3,394.6$ km and $B=3,393.3$ km and a semi-minor axis of $C=3,376.3$ km. The semi-major axis, A, intersects the Martian surface at longitude 105°W . The dynamic flattening of Mars as determined from the J_2 term of the gravity field is 0.00525. The mean radius of the 6.1 mb areoid is 3,382.9 km. Other parameters determining the datum include the planet rotational velocity $\omega=0.70882176 \times 10^{-4}$ radian/sec and the gravitational constant $\mu=0.4282844 \times 10^5 \text{ km}^3/\text{sec}^2$.

The procedure for establishing topographic contour lines is to convert all the non-imagery topographic data, obtained from the different sources, from radii to heights with respect to the adopted topographic datum. All the heights are then adjusted into a common system to minimize discrepancies, and then plotted on the various map projections using an XY plotter. Contour lines are then interpolated using shaded relief maps as reference. The contour interval of the maps is one kilometer.

For some prominent features or features of special geologic interest where pictures with adequate stereo overlap from Mariner 9 are available, local contour maps at relatively larger scales were also compiled on a stereo plotter by photogrammetric methods. If high resolution B-frames are used, a map scale as large as 1:100,000 with a contour interval of 400 meters can be obtained. In most cases, however, stereo models from Mariner 9 photography have very unusual model geometries and therefore, special unconventional procedures were developed using the mission support data for establishing model

orientation. In the case where the coverage is composed of a number of models, a block adjustment, basically based on resections and intersections, using a least squares solution method is applied for the establishment of a control net for intermodel bridging.

Because of insufficient information on the accuracies of some of the data sources, a formal analysis of contour line accuracy is not possible. However, a 1-2 km probable error may be estimated. Due to the lack of data in some areas, these Mars contour maps are lacking in detail and subsequent revisions will be necessary whenever more information becomes available.

PART I

FIGURE, SIZE, AND GRAVITY FIELD OF MARS
AND ITS TOPOGRAPHIC DATUM

CHAPTER 1

INTRODUCTION

The scientific achievements of the Mariner Mars 9 mission have accomplished a giant step toward the understanding of the planet Mars and our solar system. Unlike Venus, our closest neighboring planet, which has extremely high temperatures and high atmospheric pressures with permanent clouds, the planet Mars has a more suitable environment for a possible eventual man-landing exploration. Although, as Moore and Cross (Moore and Cross, 1973, p. 9) pointed out, due to the unsuitable environment, the existence of intelligent life on Mars can be ruled out, but the problem of whether or not some terrestrial-like organisms exist, is yet to be found out. Also, in the sense that the solar system is man's environment, it may bring us a better understanding of our own planet when we understand more of planetary origins and evolutions through the study of both the similarities and differences between other planets and the Earth.

Mars, in many respects, is somewhat similar to the Earth in that it has a thin transparent atmosphere, moving clouds, intermittent seasonal weather systems with occasional dust storms, and the changing polar caps which are attractive to man's interest for further exploration.

1.1 Statement of Objectives

To seek for evidence of the existence of some forms of life, past or present, in terms of the composition and structure of the

Martian surface and atmosphere, and other scientific interests, the United States has developed, in the Viking Mars project, two scientific packages which it will attempt to land on Mars in the very near future.

In support of a successful Mars landing, topographic contour maps of Mars were required for mission support and mission operation. This requirement initiated an experiment which is an attempt to derive topographic contour maps of Mars by synthesizing all the available topographic information obtained from various experiments on Mariner 9 as well as all the data from Earth-based radar observations of Mars. This experiment is not only essential to both mission planning and mission operations, but is also important to geological studies and other scientific studies as well.

In addition to the support of space exploration, the importance of the topographic mapping of Mars to other scientific studies can be seen in the Wells report (Wells, 1972):

A comprehensive knowledge of the topographic relief at all scales on Mars is fundamental in the continued observational and theoretical exploration of the planet. Such information on large scales bears not only on the shape of the surface itself, but also on the relationship with stress/strain effects in the outer crustal layers, the state of the interior of the planet, and influences on dynamical motions in the atmosphere. Small-scaled relief provides data on environmental process such as regional structuring, localized weather effects, and mass transport of various atmospheric constituents near ground level. All of these phenomena can affect the choices of landing sites for future spacecraft missions. Many facets of scientific interest would thus be served by a more precise morphological definition of the Martian surface.

This paper is an attempt to briefly describe all of the aspects of the topographic mapping of Mars with the exception of shaded

relief and mosaic mapping techniques which are published or will be discussed elsewhere.

To provide a better understanding of the Martian topography, the characteristics of Mars are first briefly described. Also, a brief discussion of the Mariner Mars missions will certainly help in understanding the derivation of the topographic maps, since they were mainly compiled from non-imaging sensor data from the Mariner Mars missions.

1.2 Mars

Mars, one of our closest neighboring planets, is the fourth planet from the Sun revolving in an orbit between Earth and Jupiter. The distance between Mars and the Earth ranges from 56 million to 101 million kilometers. Due to its unusual reddish color, as of blood and fire, Mars was worshipped by the Greeks as their god of war and its two moons were named Phobos and Deimos meaning "fear" and "terror". Therefore, the symbol of Mars (♂) represents a shield and spear (Glasstone, 1968).

Mars has a mass of only one tenth that of the Earth's and one seventh of the Earth's volume. But with its comparable temperature and seasonal changes, it was, in the early days, said to be one of the most Earth-like objects in the solar system.

Like Earth, Mars is not a spherical body but is flattened at the poles. It revolves in an elliptical orbit which has a 24° inclination to its axis (Moore and Cross, 1973, p. 12), which is close to the inclination of the Earth's orbit. Therefore, the various seasons and the lengths of the days and nights are similar to those of the Earth.

However, due to a longer orbit and a slower average speed, Mars has 687 days with 24 hours and 39.6 minutes per day in a solar year. Therefore, the duration of the Martian seasons, in terms of Earth days, is roughly twice that of the Earth's seasons. Because of the relatively large eccentricity of the Martian orbit, the seasonal periods are different. The spring, summer, autumn and winter of the northern hemisphere are 199, 182, 146 and 160 Earth days respectively, which are the reverse of those periods in the southern hemisphere. The southern hemisphere, during its spring and summer, when Mars is near perihelion, receives much more heat than the northern hemisphere does during its spring and summer. Therefore, the size of the polar cap of the southern polar region decreases much faster than that of the north and may eventually disappear during the summer due to a hotter summer even though it may be shorter than the summer season of the northern polar region, where the polar cap becomes small but never disappears completely. Another fact is, that due to a longer autumn and winter period (381 Earth days), the size of the southern polar cap reaches as far north as latitude 45°S and is bigger than the north polar cap which does not spread any farther south than 60°N latitude due to the short autumn and winter seasons (306 days). From these facts, it can be seen that it is significant for Mars mappers to know during which season photography of the polar regions was taken.

Because of their seasonal changes, the polar caps are the most prominent features on the Martian surface along with the bright areas and dark areas. Starting at the end of summer in either hemisphere of

Mars, a bright white polar cap constantly increases in size when a vast, whitish, diffuse haze form appears over the polar region. Just before the local spring, the cloud decreases or sometimes eventually disappears and the sharp outline of the cap itself is exposed. In the past the polar caps were believed to consist of either solidified water similar to hoarfrost as suggested by William Hersch or solid carbon dioxide snow (dry ice) as many other scientists have lately suggested. The Mariner 9 experiments have proposed that the primary caps which come and go with the seasons are mostly carbon dioxide but that the residual cap left each year is possibly water ice (Hartmann and Raper, 1974).

The bright areas of Mars which include both orange and yellowish-brown areas cover about 70% of the Martian surface, mainly in the northern hemisphere. This is the reason why the planet looked reddish and is therefore called the red planet. The bright areas are said to be a function of phase angle. It is believed that these bright areas appear so because of fine particles of dust which are deposited over large, flat and smooth lowland areas by high winds. The dark areas cover about 25% of Mars, mostly in the southern hemisphere, which are heavily cratered highland terrain. It is believed that along high flat regions and gentle slopes, depositions of larger particles, coarser material or even rocks, are favored so that highlands appear to be darker in color. During the first orbital revolutions of Mariner 9, a planet wide dust storm was in progress, allowing only four dark spots and the clear bright south polar cap to be visible. These four dark spots later proved to be the highest volcanic mountains on Mars. Also,

it will be shown in later chapters that the average elevation of the northern hemisphere of Mars is about four kilometers lower than the average elevation of the southern hemisphere which appears to be darker in color. Therefore, the variations of the bright and dark markings may be explained as having something to do with the transport and deposition of fine materials carried by the high winds. Due to the low pressure of the Martian atmosphere, very high wind velocities are necessary to create enough force to transport the surface particles (Jet Propulsion Laboratory [JPL], 1973b, p. 33).

The temperatures on Mars are not greatly different from those on Earth. Due to the greater distance between Mars and the Sun, the surface temperatures on Mars are expected to be colder than those on Earth and can be as low as well below -100°C according to the estimate made by E. W. Maunder. The difference of temperature between day and night can be 100°C at the equator but less at high latitudes. During the summer time, temperatures in the daytime are above the freezing point of water at all latitudes up to about 60°N and 70°S . During the night there is no part of the planet where the temperature is above -20°C (Glasstone, 1968).

The highest and lowest temperatures observed at the Martian equator by Mariner 7 were 290°K at noon and 200°K during the night. But a low of 150°K was recorded at the south polar cap (Cunningham and Schurmeier, 1969). Results from the infrared radiometer of Mariner 9 showed a measurement of 250°K brightness temperature at the latitude of 65°S (Chase et al., 1972). But no area on Mars had a brightness temperature in excess of 300°K (Kieffer et al., 1973).

In general, the surface of the dark areas of Mars is about 10°C warmer than the adjacent bright areas in the daytime due to the fact that one absorbs the heat and the other reflects it.

The atmospheric pressure of Mars is very low and is less than one percent of the Earth's pressure. It is not dense enough for fluid water to remain stable (JPL, 1973b). Measurements of Martian surface pressure from the infrared spectrometer and the ultraviolet spectrometer of Mariners 6 and 7 vary from 4.05 to 8.16 mb and 3.97 to 8.44 mb respectively (Hord, 1972). Results from the infrared spectrometer measurements of the Mariners showed a range from 8 mb, to 1.5 mb, at the top of the South Spot (Arsia Mons), with an average of 4.8 mb surface pressure over the sampled area. An average surface pressure of 3.5 mb was obtained over the Tharsis region (Conrath et al., 1973). The Martian atmosphere is primarily composed of CO_2 ranging from 60% to perhaps 100% (Kliore et al., 1969).

Because of the fact that Mariner 4 photography was concentrated in the cratered terrain areas, it was suggested that the Martian surface was much like that of the Moon. However, the Mariner 6 and 7 photography showed, in addition to the cratered terrain, two types of uncratered terrain on the Martian surface (Murray et al., 1971). They are classified as chaotic and featureless terrains. Chaotic type terrains are younger than cratered type terrain (Sharp et al., 1971b). The Mariner 9 mission has shown that Mars is distinctly different from the Earth and the Moon.

Except for the Coprates Canyon complex, which has been renamed Valley Marineris and expanded to a length of 4,800 km with a depth of 6 km and a width of 200 km at the widest spot no other features have been discovered which would appear as dark canal-like lines which have been reported for so many years (Cutts et al., 1971). One of the big surprises of the Mariner 9 mission was the discovery of huge volcanic features, one as high as 27 km which indicates that Mars is presently geologically active (Bradbury et al., 1972, p. 91).

In comparison with the Earth, it was discovered from the Mariner 9 mission that Mars has a rough gravity field and a shape which is essentially a triaxial ellipsoid (Lorell et al., 1972).

The two moons of Mars are both found to be dark, old, heavily cratered and irregular in shape because their bodies are too small to impose a spherical shape (Masursky et al., 1972, Cutts, 1974). The mass of Phobos and Deimos are 17.4×10^{18} g and 3.1×10^{18} g respectively. They are somewhat triaxial in shape with a mean radius of 10.9 km and 5.7 km respectively (Pollack et al., 1973). Both are in circular orbits, keeping the same side toward Mars at all times. The orbital period of Phobos is 7.7 hours and the period for Deimos is 30.3 hours.

1.3 Summary of the Mariner Mars Missions

Mariner 4 was the first spacecraft to take man's first close-up pictures of the Martian surface. But Mariner 9 was the first man-made object to orbit another planet and acquire photographic coverage of the entire surface. Mariner 4 photographically covered about 1% of the

Martian surface at approximately three kilometer resolution. Mariner 6 and 7 then extended the Martian photographic coverage up to 10% and also improved man's viewing resolution to 0.3 kilometers (Leighton and Murray, 1971). But it was Mariner 9, the most productive mission in the planetary exploration program, that gave us new revolutionary knowledge of Mars. During a period of 349 days in Martian orbit, Mariner 9 transmitted photographs and other various scientific information back to Earth which amounted to about 27 times as much information as acquired by all three of the previous Mariner flyby missions combined (Hartmann and Raper, 1974). A brief description of each of these Mariner Mars missions is summarized in the following sections.

1.3.1 Mariner-Mars 1964

The year 1964 was the first attempt by man to launch a vehicle to the planet Mars. This was the Mariner 4 spacecraft. It was launched on November 28, 1964, and, after a flight of 228 days and a journey of 235 million miles, it took the first close up pictures of Mars at 0^h 18^m 33^s GMT on July 15, 1965, and by-passed Mars within a range of 9,850 kilometers. Mariner 4 carried a television camera, and transmitted back 21 full frame pictures of Mars. With the on-board radio occultation equipment, experiments were performed to study the Martian atmospheric pressure, temperature and densities. Significant scientific results from this mission include: 1) it was found that Mars has a thin atmosphere and that the Martian surface pressure is less than 1% of that on Earth (Cunningham and Schurmeier, 1969); 2) the equatorial radius of Mars was found to be approximately 12 to 20 miles

greater than the previous best estimate. The new value was indicated to be approximately 3,400 kilometers; and 3) the mass of Mars was estimated to be 1:3,098,500 of the Sun (de Vaucouleurs, 1965). The returned pictures showed a heavily cratered moon-like terrain.

1.3.2 Mariner-Mars 1969

In 1969 two identical spacecraft, Mariners 6 and 7, were launched to fly by Mars. Both spacecraft carried identical scientific instruments which included two television cameras, one infrared spectrometer, one ultraviolet spectrometer, one infrared radiometer, and experiments for acquiring S-band occultation data and celestial mechanics information. The primary objectives of the mission were to investigate the Martian surface and its atmosphere near the dark area of Meridiani Sinus. Therefore, Mariner 6 was assigned to study the equatorial region of Mars in the west-east direction concentrating on a point near 20°S that would provide a good coverage of the many light and dark features, while Mariner 7 was assigned a pass that would cover the south polar cap and its edge concentrating on the region between -30° and -50° of latitude (National Space Science Data Center, 1971).

Mariner 6 was launched at $01^{\text{h}} 29^{\text{m}} 02^{\text{s}}$ GMT on February 24, 1969, and arrived at Mars on July 29, 1969. Then a sequence of 50 photographs of the Martian surface from far-encounter and 25 photographs from near-encounter were taken before it passed Mars at $05^{\text{h}} 19^{\text{m}} 07^{\text{s}}$ GMT on July 31, 1969, after approaching within 3,431 kilometers of the Martian surface.

Mariner 7 was launched at 22^h 22^m 01^s GMT on March 27, 1969, and began its first far-encounter sequence of approach photography at 09^h 32^m 33^s GMT on August 5, 1969. After having taken a total of 126 photographs of the Martian surface, it passed Mars approaching within 3,430 kilometers of its surface (Cunningham and Schurmeier, 1969).

The two television cameras carried on both Mariners 6 and 7 included one wide-angle (not as defined photogrammetrically) which has an 11°x14° field of view with a focal length of 52 millimeters and one narrow angle which has a 1.1°x1.4° field of view with a focal length of 508 millimeters. The image format for both cameras is 9.6 mm x 12.3 mm having image elements of 704 lines x 935 pixels (Leighton et al., 1969).

Significant scientific results from Mariner Mars 1969 included:

- 1) in addition to the cratered terrain, as previously found by Mariner 4, two other types of uncratered terrains were discovered on Mars--chaotic and featureless (Sharp et al., 1971b);
- 2) light material was found in local lowland areas. No linear network of canal-like features were observed on the Martian surface (Cutts et al., 1971);
- 3) the south polar cap was found to be a region of cratered terrain likely occupied by CO₂ ice with irregular angular depressions (Sharp et al., 1971a);
- 4) temperatures measured from the occultation experiment agreed with results obtained from both the infrared spectrometer and infrared radiometer as described in section 1.1 (Herr and Pimentel, 1969; Neugebauer et al., 1969); and the surface pressure was recorded to be between 4 and 7 millibars at four occultation points (Hartmann and Raper, 1974);
- 5) the locations of the occultation points are: Mariner 6

entry point (4°N and 356°E) and exit point (79°N and 84°E), and Mariner 7 entry point (58°S and 30°E) and exit point (38°N and 212°E). The radius of Mars at the Mariner 6 entry point near the equator is about 3,394 kilometers and 3,374 kilometers at the exit point near the polar region (Kliore et al., 1969); and 6) it was found from the ultraviolet spectrometer experiment that the most abundant material in the Martian atmosphere is CO_2 (Barth et al., 1969, Herr and Pimentel, 1969).

1.3.3 Mariner-Mars 1971

For the Mariner-Mars 1971 project two identical spacecraft, Mariners 8 and 9 were launched. Each spacecraft carried identical instrument packages to perform six experiments in Mars orbit. The basic objectives of this mission were to acquire photography for mapping the red planet and to observe its dynamic characteristics over a period of a minimum of 90 days. The six scientific experiments included two television cameras (one wide angle and one narrow angle), one ultraviolet spectrometer (UVS), one infrared radiometer (IRR), one infrared interferometer spectrometer (IRIS), the S-band radio occultation and the celestial mechanics (Masursky et al., 1970).

The original plan was to put Mariner 8 in a Martian orbit having an inclination angle of 80° at a periapsis altitude of 1,250 kilometers for a photographic mapping and reconnaissance mission. The Mariner 9 mission was designed to take high resolution coverage photography of the middle latitudes. For this purpose, the orbital inclination angle was to be 50° with a periapsis altitude of 850 kilometers. However, due to the loss of Mariner 8 because of a launch

failure, the Mariner 9 mission was redesigned to be a compromise for obtaining the major goals of both missions. Therefore, the inclination angle of Mariner 9 was changed to 65° with an altitude of 1,250 kilometers.

Mariner 9 was then launched at $22^{\text{h}} 23^{\text{m}} 04^{\text{s}}$ GMT on May 30, 1971, and, after a 167 day and 394 million kilometers flight, it was inserted into Martian orbit at $00^{\text{h}} 15^{\text{m}} 29^{\text{s}}$ GMT on November 14, 1971, with an orbital period of $11^{\text{h}} 59^{\text{m}} 28^{\text{s}}$ (Steinbacher et al., 1972). Due to a planetwide dust storm, the photographic acquisition task could not be started until January 2, 1972. The photography then had to be acquired within three mapping cycles, starting from revolution 100 and ending in revolution 262. No photographs were taken between revolutions 263 to 415 and only 329 pictures were taken during the period between revolution 416 and revolution 696 (Koskela, 1973).

Other scientific experiments were generally performed in three periods including one standard mission and two extended missions. The mission was ended on October 27, 1972, when all of the attitude control gas was used up. This occurred after 349 days in orbit which was four times as long as it was originally designed to last. Also, the scientific data obtained from this mission exceeded all of the planned goals (McCauley, Hipsher, and Steinbacher, 1974).

During the period from April 2 to June 4, 1972, with the exception of the S-band occultation and celestial mechanics experiments, no other experiments could be performed due to solar occultation. The fact is, during that period, Mariner 9 passed into the shadow of Mars

during each revolution, so that power could not be generated from the solar panels on the spacecraft. Another phenomenon, called superior conjunction, occurred from September 7 to October 12, 1972. During that period, Mars went behind the sun relative to the Earth so Mariner 9 could no longer be communicated with from Earth because of the Solar Corona (Steinbacher and Haynes, 1973; McCauley et al., 1974).

Mariner 9 was the most successful mission in the planetary explorations program. It has transmitted back to Earth, more than 7,300 photographs of Mars and some pictures of its two moons and has completed 100% coverage of the Martian surface where only 70% was originally planned on. From the six scientific experiments, Mariner 9 has transmitted a total of 54 billion bits of scientific information (Hartmann and Raper, 1974). This data provides man with extensive information for studying Mars. As an example, this Mars topographic mapping experiment has utilized information from almost every experiment of Mariner 9. A detailed description of data analysis will be given in the following chapters. The tracking stations include the 64 meter antenna at Goldstone, California; at Woomera, Australia; and Cebreros, Spain.

1.4 Mapping Strategy

The charting of the Martian surface started as early as 1840 by the German astronomers W. Beer and J. H. Mädler, and followed by N. Lockyer, 1864; R. A. Procter, 1867; G. Flammarion, 1876; and N. Green, 1877. But the first modern maps of Mars were made by Giovanni Schiaparelli (1835-1910) from his observations in 1870 and

1879 (de Vaucouleurs, 1965). Just before and during the series of the Mariner Mars missions, two recently published detailed Mars maps were compiled by Gerard de Vaucouleurs from many of his photographic observations of 1939 and 1941 as well as those observed from Lowell Observatory in 1950. But the one started by Andrew T. Young at Harvard Observatory in 1958 and continued and completed at the University of Texas, 1964, is perhaps the most comprehensive Mars map.

By the synthesis of the abundant data from the Mariner 9 sensors, as well as from Earth-based radar, the topographic map of Mars derived from this experiment, as described in this paper, is unique in the history of mapping and the first comprehensive map that represents the general topography of the Martian surface. The strategy used in contouring the Martian surface, as shown in the map produced by the U.S. Geological Survey during this investigation, can be described separately in terms of mapping purpose, data sources, scales, map projections, datum, controls, data reduction and contour techniques.

The purpose of this experiment is to utilize topographic information of the Martian surface transmitted by Mariner 9 and the information acquired by Earth-based radars at Goldstone, Haystack and Arecibo Observatories to compile a comprehensive topographic contour map of Mars. This map will be used for supporting the mission planning and mission operation of the 1976 Viking Mars missions and for the support of geological studies as well as other scientific interpretations of Mars. Data used for the compilation include television pictures of both wide and narrow-angle cameras of Mariner 9 and non-imaging sensor

data which include 259 S-band radio occultation measurements, 4,630 observations from the infrared interferometer spectrometer, 7,500 observations from the ultraviolet spectrometer, gravity data from celestial mechanics experiment, and 2,762 radar points from the Haystack Observatory observed during the 1967, 1969 and 1971 oppositions and 13,100 radar points observed by Goldstone Observatory during the 1969, 1971 and 1973 oppositions. Radar observations from the Arecibo Observatory were used only for reference to check the completed contour map.

The entire planet is mapped at scales of 1:25,000,000 and 1:5,000,000 using three different map projections depending on the locations and area mapped. The projections are Mercator conformal, Lambert conformal and polar stereographic projections.

The dynamic topographic datum is defined by a 6.1 mb pressure surface and a gravity field represented by fourth degree and fourth order spherical harmonics. To support the Mars landing, an aerographic coordinate system is used.

The data reduction includes the reduction of heights from various sources to the common topographic datum and the adjustment of all reduced heights by using S-band occultation measurements as control points because of their accuracy and distribution over the planet. Adjusted heights are then plotted on the appropriate map projections using an XY plotter. Contour lines are then interpolated using photo mosaics as reference. For prominent Martian features of scientific interest, large scale contour maps are compiled stereoscopically in an analytical stereoplotter. For bridging multimodel coverage, controls can be produced by using a block adjustment program.

CHAPTER 2

COORDINATE SYSTEM AND MAP PROJECTIONS

The first step in the mapping of another planet is to define a coordinate system and to select appropriate map projections so that features on the planet can be properly located on the map. The selection of map projections is, of course, dependent upon the scale, the size and the locality to be compiled.

2.1 Martian Coordinate System

The Martian latitudes and longitudes were first defined by W. Beer and J. H. Mädler when they made a chart of Mars in 1840. Their longitudes increase to the east, the zero-point being at a dark feature, later to be named Sinus Meridiani, and their zero latitude lies on an equatorial line on which all points are equal distant from both poles. Schiaparelli retained the same zero-point in his map made in 1877, then in 1909, the definition of the Martian zero-longitude was changed to be defined by the ephemeris to allow for compensation of errors in the rotational period of the planet.

In 1972, the Mariner 9 Geodesy/Cartography Group of the television team, selected the Martian zero-meridian to pass through a particular small crater which is approximately at the center of a large crater. The large crater was then named Airy and the small crater Airy-0 in honor of the late director of the Greenwich Observatory, Sir George

Biddell Airy, who installed a transit instrument to be used to define the prime meridian on the Earth (1884). The longitudes of this new system increase to the west which is the opposite of the conventional astronomical coordinate system.

Airy-0, as circled in figure 2-1(b), is about a half kilometer in diameter and lies within a large distinctive crater which has a secondary crater breaking its south rim as indicated by a cross mark in figure 2-1(a). The Airy-0 is located at -5.19° , south of the Martian equator (de Vaucouleurs, Davies, and Sturms, 1973).

The hour angle along the equator from the Mars vernal equinox to the new Martian prime meridian then should be (Davies and Arthur, 1973):

$$V = 148.24^{\circ} + 350.892017^{\circ} (\text{JD}-2,433,282.5) \quad (2.1)$$

where 2,433,282.5 is the ET of Julian date 1950, January 1.0.

The Geodesy/Cartography Group has also adopted the areographic coordinate system to be used for all Mariner 9 map products. This decision was especially made considering future Martian explorations since the areographic latitude is the angle between the equatorial plane and the normal to the reference spheroid of the point in question. For the computation of map projections, the adopted reference spheroid has an equatorial radius of $A=3,393.4$ kilometers and a polar radius of $B=3,375.7$ kilometers. This yields a Martian flattening of 0.0052 or $\frac{1}{192}$ and an eccentricity of 0.101849.

Figure 2-1.--Location of the Martian prime meridian of longitude which passes through the crater Airy-0--as circled in b.

The relationship between the areocentric latitude ψ and areographic latitude ϕ is given by (Hosmer, 1946, p. 181):

$$\tan \psi = \frac{B^2}{A^2} \tan \phi \quad (2.2)$$

The maximum difference between ψ and ϕ is $0^\circ 17' 58.7''$ at latitude 45° . At the equator and poles the difference is zero.

2.2 Map Scale and Format

The number of quadrangle maps is dependent upon the map scale used, and the map scale is dependent upon the use of the map and particularly dependent upon the photo resolution obtained from the Mariner 9 mission. In order to fulfill the criterion of minimum size geological annotation compatible with the 1 kilometer resolution of the Mariner photography, it was decided to use 1:5,000,000 as the smallest scale for the quadrangle mapping of the planet Mars (Batson, 1973a). Using approximately 0.5 m x 0.5 m as the size for all quadrangles, between 20 and 30 maps would be required to accomplish the desired coverage. Therefore, as shown in figure 2-2, it was decided to use a total of 30 quadrangles to map the entire planet (Batson, 1973a).

Quadrangle names and nomenclature of Martian features on all maps seen in later chapters, were adopted by the Geodesy/Cartography Group and approved by the International Astronomical Union (IAU). For simplification of filing and locating maps, in addition to the quadrangle name, a systematic identification number was assigned to each chart (Batson, 1973a). For example, the name of the north polar quadrangle is Mare Boreum. It is also called MC-1 meaning Mars Chart

Figure 2-2.--Map sheet layout for mapping Mars at the scale of 1:5,000,000.

number 1. The line under the quadrangle name which is a combination of alphabetic and numeric numbers, indicates the scale and the location of the map. The line 5m 90/0 in MC-1 indicates that the map has a scale of 1:5 million and that the center of the map is located on the planet at a latitude of 90° and a longitude of 0° .

For use during the Viking mission planning and mission operation, a desk size Martian chart is required for showing the entire planet. Therefore, a Mars map at a scale of 1:25,000,000 has also been prepared. This small scale map is shown in the chart in figure 2-2.

2.3 Map Projections

For the 1:25,000,000 and the 1:5,000,000 scale series of Mars maps, three conformal map projections are used so that at any point, scale distortion in longitude is the same as that in latitude and small features retain their actual shape.

For the 1:25,000,000 scale map, the Mercator projection is used between the north 65° and south 65° parallels, and the polar stereographic projection is used for the polar region north and south of the 55° parallels which provides a 10° overlap with the Mercator projections. For the 1:5,000,000 maps, as shown in figure 2-3, the Mercator projection is used for the quadrangles MC-8 to MC-23, each of which contains 45° of longitude and 30° of latitude along the equatorial belt; the Lambert conformal projection is used for the quadrangles MC-2 to MC-7 and MC-24 to MC-29 which contain 60° of longitude for bands between 30° and 65° of both north and south latitudes; the polar stereographic projections are used for both of the polar regions above 65° .

Figure 2-3.--Quadrangle layout and map projections for the 1:5,000,000 Mars map series.

2.3.1 Mercator Conformal Projection

For the Mercator projection, the scale is 1:1 along the equator, the X and Y coordinate axes are straight lines and the origin of the Y coordinates is at the equator (Thomas, 1964, Richardus and Adler, 1972). The equations for the X and Y coordinates are:

$$X = A\lambda \quad (2.3)$$

$$Y = A \ln \left\{ \left[\tan \left(\frac{\pi}{4} + \frac{\phi}{2} \right) \right] \left[\frac{1 - e \sin \phi}{1 + e \cos \phi} \right]^{\frac{e}{2}} \right\} \quad (2.4)$$

where A, e, and ϕ are described in section 2.1 and λ is the longitude of the point.

The projected scales vary depending upon the latitude of the point projected. The scale k can be computed from equation (2.5),

$$k = \frac{\sqrt{1 - e \sin^2 \phi}}{\cos \phi} = \frac{A}{N \cos \phi} \quad (2.5)$$

where N is the radius of curvature in the prime vertical and

$$N = \frac{A}{\sqrt{1 - e^2 \sin^2 \phi}} \quad (2.6)$$

The computation of the projected X, Y coordinates has been programmed on a Varian 620/i computer which commands an XY plotter. The Varian computer has 32K words of memory. The plotter table is 8' x 10' and has a precision of 0.001 inch. Map grids and topographic information can be directly plotted on the plotter at the desired projections and scales. Figure 2-4 is an example of a Mercator grid scribed on the XY plotter which is used for each of the 16 45° x 30° quadrangle maps MC-8 to MC-23.

Figure 2-4.--Grid of Mercator conformal projection with 5° increments in both longitude and latitude for 1:5,000,000 ($45^{\circ} \times 30^{\circ}$) quadrangle maps MC-8 to MC-23.

The scale ratios and the true scales of the 1:25,000,000 scale map are computed by using equation (2.5) and are listed in table 2.1. From the table, it can be seen that the scale at the 65° latitude is greater than twice that at the equator. The map users should be cautious when using the map for interpretation or mission planning work.

2.3.2 Lambert Conformal Conic Projection

In the Lambert conformal conic projection, the projected parallels are arcs of concentric circles with radii which are their corresponding projected meridians. The common center is also intersected by the projected meridians (Thomas, 1964, Richardus and Adler, 1972).

Table 2.1.--Scale variations in the Mercator conformal projection of the 1:25,000,000 map.

Latitude	Scale ratio	True scale
0°	1.000000	1:25,000,000
5	0.996234	1:24,905,849
10	0.984962	1:24,624,048
15	0.966262	1:24,156,543
20	0.940263	1:23,506,585
25	0.907149	1:22,678,715
30	0.867151	1:21,678,764
35	0.820553	1:20,513,836
40	0.767691	1:19,192,287
45	0.708948	1:17,723,693
50	0.644753	1:16,118,824
55	0.575583	1:14,389,576
60	0.501957	1:12,548,914
65	0.424430	1:10,610,773

To minimize scale distortion, two standard parallels are used. The central meridian of each quadrangle serves as its y axis, and the intersection of the y axis and its lowest latitude serves as the origin. The equations of the x and y coordinates are:

$$x = r \sin \ell \lambda \quad (2.7)$$

$$y = r_o - r \cos \ell \lambda \quad (2.8)$$

where

$$r = K E^{-\ell q} \quad (2.9)$$

$$r_o = K E^{-\ell q_o} \quad (2.10)$$

and

$$K = \frac{N_1 \cos \phi_1}{\ell E^{-\ell q_1}} = \frac{N_2 \cos \phi_2}{\ell E^{-\ell q_2}} \quad (2.11)$$

$$\ell = \frac{\ell n (N_1 \cos \phi_1) - \ell n (N_2 \cos \phi_2)}{q_2 - q_1} \quad (2.12)$$

$$q = \ell n \left\{ \left[\tan \left(\frac{\pi}{4} + \frac{\phi}{2} \right) \right] \left[\frac{1 - e \sin \phi}{1 + e \sin \phi} \right]^{\frac{e}{2}} \right\} \quad (2.13)$$

In equations (2.7) to (2.13), λ and ϕ are areographic coordinates of the point to be projected; E is the Napierian base = 2.71828183; N is calculated by using equation (2.6); ϕ_1 and ϕ_2 are the two standard parallels and equal to 35.83° and 59.17° respectively. The latitudes of the upper and lower boundaries are 65° and 30° respectively. This allows the latitude difference between ϕ_2 and ϕ_1 , 23.34° to be two-thirds of the latitude difference between the two boundaries, so that

scale errors are more uniformly distributed; and r_0 has the same coordinate as y at the origin; ℓ , K and r_0 are constants which can be calculated by using the latitude of the origin ψ_0 .

The scale is true only along the two standard parallels. The scale k of any other point varies and can be computed from equation (2.14),

$$k = \frac{K \ell E^{\ell q}}{N \cos \phi} \quad (2.14)$$

As in the case of the Mercator projection, this projection also has been programmed on the XY plotter for this experiment. An example of the Lambert conformal projection grid which was scribed on the XY plotter, is shown in figure 2-5. This is the grid used for the $12^\circ \times 35^\circ$ quadrangle maps from MC-2 to MC-7 and MC-24 to MC-29.

It should be remarked here that the so called 1:5,000,000 map is not exactly 1:5,000,000. The scale of the quadrangles is set to match the scale at the lower boundary latitude (30°) of the Lambert projection which matches the scale at the upper boundary latitude (30°) of the Mercator quadrangles which is already magnified with a scale ratio of 0.867151 from table 2.1. In other words, the scale at latitude 30° at the upper boundary, is no longer 1:5,000,000 rather, it is 1:4,335,755.

2.3.3 Polar Stereographic Conformal Projection

The polar stereographic projection is a special case of the Lambert projection with one standard parallel being the point at the pole. Therefore, the meridians are straight lines radiating from a

Figure 2-5.--Grid of Lambert conformal conic projection (two standard parallels) with 5° increments in both longitude and latitude for 1:5,000,000 ($60^\circ \times 35^\circ$) quadrangle maps MC-2 to MC-7 and MC-24 to MC-29.

central point which is the pole and the parallels are concentric circles about this central point (Thomas, 1964). The equations for computing the x and y coordinates, referred to the pole, are:

$$x = r \cos \lambda \quad (2.15)$$

$$y = r \sin \lambda \quad (2.16)$$

where

$$r = k_0 \frac{2A^2}{B} \left(\frac{1 - e \sin \phi}{1 + e \sin \phi} \right)^{\frac{e}{2}} \tan \frac{z}{2} \quad (2.17)$$

where

$$\cot \frac{z}{2} = \tan \left(\frac{\pi}{4} + \frac{\phi}{2} \right) \left(\frac{1 - e \sin \phi}{1 + e \sin \phi} \right)^{\frac{e}{2}} \quad (2.18)$$

k_0 is the scale factor at the pole, which can be arbitrary and generally selected to reduce the maximum scale distortions of the projection.

Scale distortion can be computed by (2.19),

$$k = \frac{2A^2}{B N \cos \phi} \left(\frac{1 - e}{1 + e} \right)^{\frac{e}{2}} \tan \frac{z}{2} \quad (2.19)$$

This projection has also been programmed on the XY plotter for this experiment. The grid which is shown in figure 2-6 is the polar stereographic projection which is used for the two polar quadrangles MC-1 and MC-30. The scale of these two quadrangles was determined by making the scale of latitude 65° to be the same scale as latitude 65° in the Lambert projections.

Figure 2-6.--Grid of the polar stereographic projection with 5° increments in both longitude and latitude for 1:5,000,000 quadrangle maps MC-1 and MC-30.

CHAPTER 3

THE GRAVITY FIELD, FIGURE, AND TOPOGRAPHIC DATUM OF MARS

It has been suspected for many years that Mars was not a spherical body, but like the Earth, a planet flattened at the poles. Because of the fact that radio-tracking data showed that the motion of Mariner 9 was irregular in Martian orbit, this indicated that the gravity field of Mars is rough, and the figure of Mars is much more complex than had been expected (JPL, 1973b). For the purpose of future Martian exploration, orbital or landing missions, the Mariner 9 Geodesy/Cartography Group of the television team decided to use the areoid potential surface (geoid of Mars) derived from using the Martian gravity field as a reference for computing heights of topography on the Martian surface. The topographic datum derived from the gravity field and the Mars figure are described sequentially in this chapter.

3.1 The Gravity Field of Mars

The results of the analysis of the Mariner 9 radio-tracking data has shown that the gravity field of Mars is rougher than that of either the Earth or the Moon (Lorell, Anderson and Shapiro, 1970; Lorell et al., 1972). Because of this, a large number of coefficients are required in the spherical harmonic representation of the gravity field. Lorell has taken the spherical harmonic expansion model to the tenth degree and found the largest positive gravity anomaly to be in the Tharsis region where there is also a high topographic feature

which is geologically quite significant. This has proved that the Martian topography does correlate with the gravitation potential. But, on the other hand, it was discovered that the higher degree spherical harmonics are not stable and only the lower degree harmonics have demonstrated stability, especially those coefficients of the fourth degree (Jordan and Lorell, 1975). Also, as Jafar pointed out (Jafar, 1975), the coefficients in the spherical harmonics between the second and third degree show a strong correlation with the topography and starting with the fourth degree, the correlation becomes weak. The conclusion that high order models are not any better, was drawn by Cain (Cain et al., 1973) when attempting to fit the higher order models to the radio occultation data. Therefore, the fourth order and fourth degree spherical harmonics derived for the Martian gravity field are adopted for the gravity potential surface for computing heights on the Martian surface (Jafar, 1975). Incidentally, a fourth order and fourth degree spherical harmonic expansion was attempted to be used to represent the worldwide gravitation potential of the Earth when disagreement was found between both the northern and southern hemispheres (Uotila, 1962a, 1962b).

The spherical harmonic expansion used to represent the Martian gravity field potential is:

$$U = \frac{GM_d}{r} \left\{ 1 - \sum_{n=2}^{\infty} J_n \left(\frac{A}{r} \right)^n P_{n0} \sin \phi + \sum_{n=2}^{\infty} \sum_{m=1}^n P_{nm} \left(\frac{A}{r} \right)^n \sin \phi \right. \\ \left. [C_{nm} \cos m\lambda + S_{nm} \sin m\lambda] \right\} \quad (3.1)$$

where

- G is the constant of gravitation
- M is the mass of Mars, also a constant
- A is the equatorial radius
- r is the radial distance of the orbiter from Mars
- P_{nm} denotes the associated Legendre polynomials
- ϕ is the latitude and λ is the longitude of Mars

If we set $-J_n = C_{no}$ and since the Martian mass constant, $\mu = GM = 42828.439 \text{ km}^3/\text{sec}^2$, has been previously determined (Christensen, 1975), then the equation can be changed to be expressed in terms of radial deviations from a mean sphere as (Jordan and Lorell, 1975):

$$\Delta r = R_m \sum_{n=1}^N \sum_{m=0}^n P_{nm} (\sin \phi) \left[C_{nm} \cos m \lambda + S_{nm} \sin m \lambda \right] \quad (3.2)$$

where R_m can be an arbitrarily selected radius of the mean sphere. Then the areopotential for ΔR is:

$$\Delta R_m = \Delta r + \frac{1}{2} \omega^2 \frac{R_m^4}{\mu} \cos^2 \phi \quad (3.3)$$

where $\omega = 0.70882176 \times 10^{-4} \text{ rad/sec}$, the rotational velocity of Mars. The computed radius R_D , which is used to define the topographic datum can then be obtained by:

$$R_D = R_m + \Delta R_m \quad (3.4)$$

where $R_m = 3,382.946 \text{ km}$. As we will see later in this chapter, this value for R_m was obtained by fitting the 6.1 millibar occultation

pressure data from Mariner 9. The computation for Δr in equation (3.2) has been programmed as a subroutine for the adjustment of all the data from the various sources used in this experiment as will be discussed in later chapters. It is also programmed on the XY plotter at $N = 4$, the fourth degree. In equation (3.2), the terms for the associated Legendre polynomials were obtained from text books on geodesy, such as Hotine (1969); Heiskanen, Meinesz and Vening (1958); and Heiskanen and Moritz (1967), which are also listed in appendix 2 of table A2.1. Values of the gravity coefficients C_{nm} 's and S_{nm} 's were obtained from the results of the celestial mechanics experiment of Mariner 9 by Jordan and Lorell which are listed in table 3.1 (Jordan and Lorell, 1975).

A contour map of the gravitation potential of Mars has been prepared by using equation (3.2) and is shown in figure 3-1, in which the term J_2 is not included. Figure 3-2 is the contour map of the areopotential of Mars, which includes the J_2 term and the centrifugal force.

It should be noted that equation (3.2) is for the conventional coordinate system in which longitudes increase to the east. Since longitudes increase to the west in the Mariner 9 case, $360^\circ - \lambda$ is used in the computations.

Table 3.1.--The fourth degree and fourth order gravity coefficients of Mars--from Mariner 9 radio-tracking data.

(C21, S21 and all first degree terms are omitted in the table from the potential series to allow the origin to be at the center of mass and the Z axis to coincide with the axis of rotation.)

Coefficient C_{nm}	Value ($\times 10^{-4}$)	$\pm$ ($\times 10^{-4}$)	Coefficients S_{nm}	Value ($\times 10^{-4}$)	$\pm$ ($\times 10^{-4}$)
J2 = -C20	19.65	0.06			
J3 = -C30	0.36	0.20			
J4 = -C40	-0.29	0.40			
C22	-0.548	0.010	S22	0.31	0.02
C31	0.048	0.040	S31	0.26	0.05
C32	-0.055	0.020	S32	0.026	0.020
C33	0.048	0.003	S33	0.035	0.003
C41	0.025	0.060	S41	0.019	0.070
C42	-0.0063	0.010	S42	-0.024	0.020
C43	0.0037	0.003	S43	0.00015	0.002
C44	-0.00023	0.0007	S44	-0.00250	0.001

3.2 The Figure of Mars

Mars has been suspected of being a flattened planet. For many years, astronomers have tried to observe the flattening of Mars and almost all optical measurements resulted in a large flattening value for Mars of about 0.011 (Dollfus, 1972). However, a value of approximately 0.0052 was obtained by those who observed the two satellites of Mars in their close Martian orbits. The difference between the

Figure 3-1.--Contour map of gravitational potential of Mars, fourth degree and order spherical harmonics, with J_2 set equal to zero.--The contour interval is 0.1 km on a Mercator projection for latitudes 65° to -65° and a polar stereographic projection for latitudes higher than 65° .

Figure 3-2.--Contour map of the areopotential of Mars, in terms of fourth degree and order spherical harmonics and including J_2 and centrifugal force.--The contour interval is 1 km.

optical and dynamic measurements is that the former can only measure the external geometric figure while the latter has considered the dynamic figure within the gravity field of Mars which is a measure of the total mass distribution. H. C. Urey pointed out in 1950 (Hartmann and Raper, 1974) that there may be a ring of high mountainous terrain in the equatorial zone. As discussed in chapter 11, the topographic map produced from this experiment shows that there is relatively high terrain along the equatorial band.

Because the orbital periods of Mariner 9 in Martian orbit were not constant but oscillating, this indicates that Mars is not only meridianally but also equatorially non-circular in shape. The radio occultation data from Mariner 9 has also indicated that the average terrain elevation in the northern hemisphere is about three to four kilometers lower than that in the southern hemisphere. This means that the northern hemisphere is closer to the center of mass of Mars. This shows that Mars is also asymmetric in the north-south direction (Kliore et al., 1973; Kliore et al., 1972a). All of these facts indicate that an oblate spheroid figure is not adequate to represent the planet.

By using all of the radio occultation measurements of Mariner 9 with the 6.1 millibar pressure surface, Cain (Cain et al., 1973, 1972) has tried to fit a triaxial ellipsoid using the equation:

$$\frac{x^2}{A^2} + \frac{y^2}{B^2} + \frac{z^2}{C^2} = 1 \quad (3.5)$$

and has also tried using spherical harmonics which gave the following results,

$$\begin{aligned}
 A &= 3394.67 \text{ km} \\
 B &= 3393.21 \text{ km} \\
 C &= 3376.78 \text{ km} \\
 \theta &= 108.50^\circ \text{ west longitude} \\
 f &= 0.00506 \\
 \text{rms fit} &= 1.63 \text{ km}
 \end{aligned}$$

Standish (Standish, 1973) has also used the Mariner radio occultation data to fit a tri-axial ellipsoid which was especially for use in the data reduction of the Mars radar observations. This resulted in the following values:

$$\begin{aligned}
 A &= 3399.3 \pm 0.7 \text{ km} \\
 B &= 3394.0 \pm 0.7 \text{ km} \\
 C &= 3376.4 \pm 0.5 \text{ km} \\
 f &= 0.00596 \\
 \theta &= 100.9 \pm 6.6^\circ
 \end{aligned}$$

As previously discussed, the topographic datum of Mars derived for this experiment is to use the gravity field of Mars and the 6.1 millibar pressure surface. The areoid is then not only defined mathematically by equations (3.1) of (3.2) but also can be represented by contour lines as shown in figure 3-3 of the next section. However, in terms of geometry, it can also be approximated by a triaxial ellipsoid. The figure and size of the triaxial ellipsoid can be obtained from gravity as (Christensen, 1975):

$$\theta = \frac{1}{2} \tan^{-1} \left(\frac{S_{22}}{C_{22}} \right) = 105^\circ \quad (3.6)$$

$$A = R \{1 + \frac{1}{2} J_2 + 3 [C22 \cos (2\theta) + S22 \sin (2\theta)]\} \\ + \frac{1}{2} \frac{\omega^2 R^4}{\mu} = 3,394.6 \text{ km} \quad (3.7)$$

$$B = R \{1 + \frac{1}{2} J_2 + 3 [C22 \cos 2(\theta + 90) + S22 \sin 2(\theta + 90)]\} \\ + \frac{1}{2} \frac{\omega^2 R^4}{\mu} = 3,393.3 \text{ km} \quad (3.8)$$

$$C = R (1 - J_2) = 3,376.3 \text{ km} \quad (3.9)$$

$$f = \frac{3}{2} J_2 + \frac{1}{2} \Phi = 0.00525 \quad (3.10)$$

where

$$\Phi = \frac{\omega^2 A^2 B}{\mu} \quad (\text{Heiskanen and Moritz, 1967, p. 111}) \quad (3.11)$$

In equations (3.6) to (3.9), R is the radius of the mean sphere at a 6.1 millibar pressure surface, which equals 3,382.946 kilometers. This will be discussed in the next section of this chapter.

These results confirm the Mars dynamic flattening of 0.0052 which was arrived at in the early days by observing the two satellites of Mars. It is also of interest to note that the results from Cain's fit of the spherical harmonics of fourth degree and order using occultation data are very close to that derived dynamically with the gravity field of Mars. This indicates that the triaxial ellipsoid fitted by Cain is very close to the areoid and is useful for approximating it. But the one that was fitted by Standish is different enough that we have difficulty in trying to correlate with the radar data from the Goldstone Observatory.

3.3 The Topographic Datum of Mars

The Martian surface pressure discussed in chapter 1, ranges from somewhere between 2.8 to 10.3 millibars as recorded from various experiments of the Mariner Mars missions. Since pressure measurements prove to correlate well with altitudes of ground features on the Martian surface, it is logical to select a certain surface pressure to be the datum for elevation reference. As discussed in sections 3.1 and 3.2, R_m in equations (3.2), (3.3), (3.4) and R in (3.7), (3.8) and (3.9) is selected to be the radius of a mean sphere which has a 6.1 millibar pressure. This value was selected because of the fact that 6.105 millibars is the triple-point pressure of water. C. A. Barth suggested (Hord, 1972) that a meaningful normalization on Mars is to choose the zero altitude at the triple-point pressure.

The triple-point pressure is the minimum pressure at which liquid water can exist in equilibrium with its gaseous vapor. At lower pressures (higher elevations), it boils or freezes depending on the temperature. At higher pressures (lower elevations), it can exist as a liquid in equilibrium, but it evaporates if the atmosphere is dry enough. At exactly 6.105 millibars and 273.01°K , the three states of water (gas, liquid and solid) can all exist in equilibrium.

When an instrument package is sent to the surface of Mars, consideration may be given to landing at lower elevations which are below the topographic datum so that evidence of the existence of water may be searched for.

The radius of this selected 6.1 millibar pressure surface is 3,382.946 kilometers. Therefore, the topographic datum is defined by equations (3.4) and (3.5). Radii of the datum have been computed for an increment of 5° in both longitude and latitude. A contour map to express this Mars topographic datum is shown in figure 3-3 with a one kilometer contour interval. Numerical values of radii of the datum have also been listed in Appendix A, Table A1-1. Here they are listed in 10° increments in both longitude and latitude.

In the reduction of the data from various sources used in this experiment, the radius of the datum at the point in consideration is computed by calling a subroutine in the computer. Only latitude and longitude of the point are required to find the datum at that point.

Figure 3-3.--Contour map of the topographic datum of Mars.--This areoid is derived from the Martian gravity field in terms of fourth degree and order spherical harmonics at a 6.1 mb datum. The contour interval is 1 km.

PART II

CONTOURING THE ENTIRE PLANET OF MARS USING NON-IMAGING TOPOGRAPHIC DATA

CHAPTER 4

NON-IMAGING TOPOGRAPHIC DATA SOURCES OF MARINER 9

The primary goals of Mariner-Mars 9 were to map the entire planet of Mars and to observe its dynamic characteristics. The instruments for the six experiments carried on board the spacecraft which included two television cameras, an infrared interferometer spectrometer, an infrared radiometer, an ultraviolet spectrometer, an S-band radio and a celestial mechanics experiment, provided broad topographic and thermal coverage, and measurements of parameters of the surface as well as the atmosphere of Mars. In fact, most of the results from each of these experiments are used in the topographic mapping of Mars. It is beyond the scope of this paper to discuss the theory, the instrumentation, and the data analysis of each of these experiments. On the other hand, a brief description of that part of each experiment which has significance to the topographic data will certainly assist in better understanding the nature of the maps produced through this investigation. This chapter will give descriptions of the S-band radio occultation, ultraviolet spectrometer, infrared interferometer spectrometer, and the infrared radiometer experiments. The television imaging system will be discussed separately in a later chapter.

4.1 S-band Radio Occultation

The S-band radio occultation experiment does not require any specific instrumentation other than the on-board S-band radio, the signals of which are also used by the on-board spectrometers, to study the temperature and pressure of the atmosphere and ionosphere of Mars. At the instant of the spacecraft orbital occultations at both entry and exit, the radii of Mars at those points can be determined by recording the time immediately before and immediately after an occultation. The occultation data and the spectrometer measurements data were received at the deep space stations at Goldstone, California, Woomera, Australia, and Cebreros, Spain (Kliore et al., 1972b).

The radio occultation technique has been used in all of the Mariner-Mars missions. The Mariner 9 spacecraft was occulted twice by Mars every 24 hours. One occultation measurement was made at entry (noted by N) and one at exit (noted by X). About 160 occultation points were recorded in the first 40 day period of the standard mission and the second set was measured during extended mission 1 which is significant because the coverage then included high latitudes, up to $+86^{\circ}$ and -80° , which improves the determination of the figure and the size of Mars. The last set of measurements were made during extended mission 2. There are, altogether, 259 usable points scattered over the entire Martian surface. Each of which also provided accurate pressure and temperature measurements. (The pressures recorded range from 2.8 to 10.3 millibars over the Martian surface.)

The accuracy of the radius measurements depends primarily on the precision of the recording time of the occultation. The uncertainty of the first set of 73 points was about 0.330 kilometers and the maximum uncertainty of the second set of measurements was 1.1 kilometers which altogether ranged from 0.25 km to 2.1 km (Kliore et al., 1973; Christensen, 1975).

As shown in figure 4-1, because of the wide distribution and accuracy, the Mariner 9 occultation measurements play an important role in this investigation and have been used as controls. This will be discussed again in chapter 6.

4.2 Ultraviolet Spectrometer (UVS)

The major objectives of the ultraviolet spectrometer experiment were to measure structure, composition and pressure of the Martian atmosphere and the Martian surface (Barth, Stewart et al., 1972). The ultraviolet intensity is a measure of the number of atmospheric scatterers. The local pressure can be determined, from these intensity measurements, and the variations of local pressure can be used to measure the Martian topography (Barth and Hord, 1971). As shown in figure 4-2, there are almost 7,500 measurements of elevation provided by the UVS experiment along the paths of Mariner 9. The resolution is about 30 kilometers.

4.3 Infrared Interferometer Spectrometer (IRIS) and Infrared Radiometer (IRR)

The infrared interferometer spectrometer was used to infer the Martian atmosphere and surface parameters which include the temperature

Figure 4-1.--Locations of all occultation points distributed over the entire planet of Mars.

Figure 4-2.--Locations of elevation points converted from ultraviolet spectrometer measurements from Mariner 9.

for a vertical temperature structure. It provides topographic information through the absorption of certain bands of CO_2 . The local variations are claimed to be reliable to 0.5 kilometers, but the absolute accuracy is about ± 1 kilometer (Herr et al., 1970; Hanel et al., 1972b; Hanel et al., 1970). While the infrared radiometer is used to infer the thermal properties of the Martian surface (Chase et al., 1972), the data can also be used to compile a temperature map which can be correlated with topographic variations (Cunningham and Schurmeier, 1969). As shown in figure 4-3, there are about 4,600 elevation points provided from the infrared experiment of Mariner 9. As in the case of the UVS data, these points were also observed along the paths of Mariner 9.

Figure 4-3.--Locations of elevation points provided by the infrared interferometer spectrometer experiment of Mariner 9.

CHAPTER 5

EARTH-BASED RADAR DATA

Radar observations of Mars have been going on since 1963 (Goldstein and Gillmore, 1963). Altitudes on the Martian surface are calculated from signal time delay. In other words, variations in travel time to and from Mars are associated with the topographic relief on the Martian surface. The resolution of the observations can be as small as 8 kilometers and the precision of the height measurements ranges from 75 meters to 200 meters. However, this precision is simply a direct translation from the precision of the time measurements of the observations. This may be applied to affect the local topography. The actual accuracy of heights involves both the error from the ephemeris and the figure of the planet assumed.

More than 15,000 data points on Mars topography observed from Goldstone, California, and Haystack, Massachusetts, along with sensor data from Mariner 9, were used in this investigation for compiling the topographic maps of Mars. All the information of Earth-based radar data is listed in table 5.1. Data reduction and elevation adjustment of these radar points will be discussed in the following chapter. For local relief, the radar data seems to be very reliable. But for globe wide topography, improvements need to be made, especially in such items as the improvement of the ephemeris and the figure of Mars used as a datum.

Table 5.1.--Topographic information from ground-based radar observation of Mars

Observatory (year)	Coverage	Number of points	Resolution E - W N - S	Precision	Mean sphere radius	Remarks
Haystack 1967	22°	118	6.1°		3,396 km	Pettengill et al., 1969
1969	3° to 12°	587	2.7°	100 m	3,393 km	Rogers et al., 1970
1971	-10.0° to -22.5°	2,044	0.8° (45km) 1.3° (80km)	75 m	3,394 km	Pettengill et al., 1971, 1973
Goldstone 1969	3° to 12°	238	200km 90km	200 m	3,390 km	Goldstein et al., 1970
1971	-14.3° to -18.6°	9,798	0.16° (8km) 1.3° (80km)	150 m	3,387 km	Downs et al., 1971, 1973
1973	-14.9° to -22.4°	3,096	0.16° (8km)	150 m	triaxial ellipsoid	Downs et al., 1975
Arecibo 1973			0.3° 1.0°			Pettengill et al., 1974 (reference only)

As shown in figure 5-1, more than 2,700 points were used from the oppositions of 1967, 1969 and 1971 at Haystack Observatory, Massachusetts. The coverage of the data points from the oppositions of 1969, 1971 and 1973 at Goldstone, California is shown in figure 5-2. There are more than 13,000 radar points which were used for this Mars project. Data observed at Arecibo was used only for reference because the map had already been compiled at the time the data was received.

Figure 5-1.--Locations of ground-based radar measurements of Mars including 1967, 1969 and 1971 oppositions at Haystack Observatory, Massachusetts.

Figure 5-2.--Locations of ground-based radar measurements of Mars including 1969, 1971 and 1973 oppositions at Goldstone Observatory, California.

CHAPTER 6

DATA REDUCTION AND ELEVATION ADJUSTMENT

The data reduction is the computation of the elevations of all of the data points with respect to the adopted topographic datum. The elevation adjustment is the adjustment of all of the reduced elevation points to be in agreement with those points which are selected as the control points. Since the radio-occultation points are distributed fairly evenly over the entire planet, and their accuracy as described in chapter 4, is consistent even though they range from 0.25 to 2.1 kilometers, it was decided that the data from the radio-occultation experiment would be used as control points.

6.1 Data Reduction

The procedure for determining the true elevation of any point depends upon the form of the topographic information of that point. In the first case, where the data point is the observed radial distance, the elevation of the point is obtained by comparing the observed and computed radii, which is obtained by using equations (3.2), (3.3) and (3.4). In the second case, where the elevations of the data points have already been reduced to the 6.1 millibar reference surface, then only the elevation adjustment is required. In the third case, the elevations of the data points have been previously determined by the experimenters using an arbitrary Mars figure, which could be a spherical shape with an arbitrary radius. The elevations are then

converted back to their radius value. The problem is then, that of the first case and that procedure is used for determining the true elevations of the points.

The data reduction of the radio occultation points, falls under the first case condition where the observed radius of all the points were provided. Following the procedure for the first case condition, the datum at each point is computed and then its absolute height above the datum is determined. The results of the data reduction for the occultation measurements are listed in Table A1.2 of Appendix A.

The data point elevations from the ultraviolet spectrometer experiment and the infrared interferometer spectrometer experiments were already reduced to a 6.1 millibar reference surface, and therefore, no data reduction was necessary. The points only needed to be adjusted.

For the Earth-based radar data points, as described before, observations were made from two different observatories over a period of three years of oppositions. For the oppositions of each year, different Mars figures were used and the information about these figures either was not available or was unclear at the time of this investigation. It was decided to adjust the raw elevation data directly. Further discussion of this problem and recommendations for revision will be discussed in chapter 11.

6.2 Elevation Adjustment

Since Mariner 9 had an inclination angle of 65° , all of the data from both the ultraviolet spectrometer experiment and the

infrared interferometer spectrometer experiment were along ground paths that are somewhat oriented in the north-south direction. The paths of the Earth-based radar data are exactly in the east-west direction in two belts in both the northern and southern hemispheres. Therefore, the procedure to adjust all elevations to a common system is to adjust all the Earth-based radar points first with the Goldstone and Haystack data adjusted separately by matching them to the occultation points since many of the occultation points are located within the zone of the radar data points. Then all of the data of the ultraviolet spectrometer experiment and the infrared interferometer spectrometer experiment were adjusted by matching them to the adjusted radar points as well as the occultation points at their mutual intersections. This was done like laying down all the railroad ties (data on paths) onto the two railroad tracks (radar data belts).

6.2.1 Elevation Adjustment of Radar Data

The radar data was adjusted for each year's oppositions separately. A polynomial carrying X , the longitudinal direction, to the fourth degree, was used. This is the same expression as for the topographic datum which is also expressed by a fourth degree Legendre polynomial. By comparing the control points selected with the corresponding observed radar points, coefficients of the polynomial were determined by a least square solution. Then all of the radar points obtained in the same year of oppositions were adjusted using the polynomial. The polynomial has 10 unknown coefficients as follows:

$$\Delta E = E_c - E_o = A + Bx + Cx^2 + Dxy + Ey^2 + Fx^3 + Gx^2 Y + Hxy^2 + Ix^4 + Jx^3 Y \quad (6.1)$$

where E_c is the elevation of the control point, E_o is the observed elevation of the corresponding radar point, x and y are, respectively, the longitude and latitude of the point. The adjusted elevation of each point can then be calculated by:

$$E_A = E_o + \Delta E \quad (6.2)$$

From the results of the radar elevation adjustment it was found that the Goldstone 1973 radar elevations are, on the average, 7.1 kilometers lower than the control system. This might be due to the fact that the triaxial ellipsoid by Standish used as the base for the 1973 radar data has a longer semi-major axis (3399.3 km) compared with the semi-major axis of the datum adopted (3394.6 km) in section 3.2. On the other hand, the Goldstone 1971 radar elevations were found to be, on the average, 1.4 kilometers higher than the control system. This might be due to the fact that a mean radius of 3387 kilometers was assumed for a spherical Mars for that year's oppositions. The standard errors of the residuals are 1.1 and 0.6 kilometers for the adjustment of Goldstone 1973 and 1971 respectively.

The Haystack 1971 data was found to be, on the average, 5.3 kilometers too low, whereas the 1969 data is, on the average, 1.3 kilometers lower than the control system. The Haystack 1967 radar data

was found to best match the control system and has only 0.1 kilometer standard error after adjustment.

6.2.2 Elevation Adjustment of Infrared Interferometer Spectrometer Data

The 4,630 points from the infrared spectrometer experiment were adjusted altogether using a polynomial of 15 unknowns. As in the case of the radar adjustment, x , the longitudinal direction, was carried to the fourth degree and y , the latitudinal direction as also carried to the fourth degree. The polynomial is

$$\begin{aligned} \Delta E = E_c - E_o = & Ax + By + Cx^2 + Dxy + Ey^2 + Fx^3 + Gx^2y + Hxy^2 \\ & + Iy^3 + Jx^4 + Kx^3y + Lx^2y^2 + Mxy^3 + Ny^4 + T \end{aligned} \quad (6.3)$$

A total of 268 points from both the occultation experiment and the adjusted radar points were used for the controls. Since this data was already reduced to a 6.1 millibar datum, it showed to be, on the average, only 0.2 kilometers higher than the control system.

6.2.3 Elevation Adjustment of Ultraviolet Spectrometer Data

For the adjustment of the 7,500 data points provided by the ultraviolet spectrometer experiment, the same technique, using the polynomial in (6.3) was attempted using 264 control points from the occultation and the radar data adjustments. Results of the adjustment showed an inconsistency. Then an attempt was made to adjust all of the data together by expanding the polynomial using the Legendre expansion to the fourth degree and fourth order with 25 unknown coefficients used to

define the Martian gravity field. The adjustment did not seem to improve. Then the final solution was to adjust each of the 39 paths separately with a second degree polynomial as:

$$\Delta E = A + Bx + Cy + Dx^2 + Exy + Fy^2 \quad (6.4)$$

In some paths the secondary adjusted infrared data points had to be used for control.

The reason that the UVS data cannot be adjusted globally may be explained by the fact that the ultraviolet spectrometer was sensitive to temperature and therefore to seasonal changes, and other unknown factors.

CHAPTER 7

TOPOGRAPHIC CONTOUR MAPS OF MARS

In this chapter the methods and procedures used for contouring Mars, and also the contour maps of Mars produced will be briefly described.

7.1 Contouring Methods and Procedures

After completion of the computation for the data reduction and elevation adjustment on a PDP 11/45 computer, the adjusted data is put on magnetic tapes. Using the XY plotter, the adjusted elevations are then plotted on the designated 1:5,000,000 projection grids. The data from each source was plotted on separate grids.

All of the grids of the same quadrangle with the plotted data from the different sources, were overlaid on each other and contour lines were then drawn by interpolation using all of the elevations available. The data grids with the contours were then overlaid on the same shaded relief quadrangles (Inge and Bridges, 1975) or photo mosaic maps, at the same scale as the data grids. The contour lines, in some places, needed to be slightly adjusted. At the same time, when gross errors of any data point were detected, the point was discarded.

During the process of compilation, some geologists who are studying the geology of the Martian surface, were asked for advice on contouring some of the Martian features where the data was either insufficient or questionable.

Where large scale contour maps of some prominent features or features of special geologic interest were available by stereo compilation, which will be discussed in later chapters, they were reduced onto the 1:5,000,000 maps.

After the completion of the contour compilations, copies of the contour maps were sent to about 30 geologists, cartographers, and engineers for their review and comments. Some slight modifications have been made as a result of their comments.

The final form for publication of these maps, are shaded relief bases, or photo mosaic bases with the contour lines superimposed. These shaded relief base maps were compiled by the Cartography Unit of the U.S. Geological Survey, Branch of Astrogeologic Studies.

7.2 Nomenclature

The nomenclature shown on the maps which are illustrated in the next section, was derived from classical names. After Mariner 9, the IAU working group on Martian nomenclature proposed names of prominent craters and other Martian features. Most of the crater names are in honor of deceased astronomers and other scientists.

To help in reading the maps, or in understanding the Martian feature referred to, the meaning of other feature classical names are as follows (Cutts, 1974):

- (1) Catena - Crater Chain
- (2) Chasma - Canyon
- (3) Dorsum, Dorsa - Ridge, Ridges
- (4) Fossa, Fossae - Ditch, Ditches

- (5) Labyrinthus - Valley Complex
- (6) Mensa, Mensae - Mesa, Mesas
- (7) Mons, Montes - Mountain, Mountains
- (8) Patera - Irregular crater
- (9) Planitia - Plain
- (10) Planum - Plateau
- (11) Tholus - Hill
- (12) Vallis, Valles - Valley, Valleys
- (13) Vastitas - Extensive plain

7.3 Topographic Contour Maps of Mars (1:25,000,000 and 1:5,000,000)

Contour lines on the topographic maps of Mars at the scales of 1:25,000,000 and 1:5,000,000 were derived from non-imaging sensor data, as described in this Chapter. The maps shown in figures 7-2 to 7-31 are 4.7 times reduced from their original size. Therefore the maps as illustrated are no longer at 1:5,000,000 scale. However, a bar scale is located at the bottom of each map.

The map as shown in figure 7-1 is the 1:25,000,000 Mars map which is 5.5 times reduced.

The map bases are shaded relief maps established by airbrush techniques. If the shaded relief map for any of these quadrangles is not available, the map base is replaced by a photo mosaic map.

Figure 7-1.--Topographic contour map of Mars.

Figure 7-2.--Topographic contour map of the Diacria quadrangle of Mars
(contour interval = 1 km)

Figure 7-3.--Topographic contour map of the Arcadia quadrangle of Mars.
(contour interval = 1 km)

Figure 7-4.--Topographic contour map of the Mare Acidalium quadrangle of Mars.
(contour interval = 1 km)

Figure 7-5.--Topographic contour map of the Ismenius Lacus quadrangle of Mars.
(contour interval = 1 km)

Figure 7-6.--Topographic contour map of the Casius quadrangle of Mars.
(contour interval = 1 km)

Figure 7-7.--Topographic contour map of the Cebrenia quadrangle of Mars.
(contour interval = 1 km)

Figure 7-8.--Topographic contour map of the Amazonis quadrangle of Mars. (contour interval = 1 km)

Figure 7-9.--Topographic contour map of the Tharsis quadrangle of Mars. (contour interval = 1 km)

Figure 7-10.--Topographic contour map of the Lunae Palus quadrangle of Mars. (contour interval = 1 km)

Figure 7-11.--Topographic contour map of the Oxia Palus quadrangle of Mars. (contour interval = 1 km)

Figure 7-12.--Topographic contour map of the Arabia quadrangle of Mars. (contour interval = 1 km)

Figure 7-13.--Topographic contour map of the Syrtis Major quadrangle of Mars. (contour interval = 1 km)

Figure 7-14.--Topographic contour map of the Amenthes quadrangle of Mars. (contour interval = 1 km)

Figure 7-15.--Topographic contour map of the Elysium quadrangle of Mars. (contour interval = 1 km)

Figure 7-16.--Topographic contour map of the Memnonia quadrangle of Mars. (contour interval = 1km)

Figure 7-17.--Topographic contour map of the Phoenicis Lacus quadrangle of Mars. (contour interval = 1 km)

Figure 7-18.--Topographic contour map of the Coprates quadrangle of Mars. (contour interval = 1 km)

Figure 7-19.--Topographic contour map of the Margaritifer Sinus quadrangle of Mars. (contour interval = 1 km)

Figure 7-20.--Topographic contour map of the Sinus Sabaeus quadrangle of Mars. (contour interval = 1 km)

Figure 7-21.--Topographic contour map of the Iapygia quadrangle of Mars. (contour interval = 1 km)

Figure 7-22.--Topographic contour map of the Mare Tyrrhenum quadrangle of Mars. (contour interval = 1 km)

Figure 7-23.--Topographic contour map of the Aeolis quadrangle of Mars. (contour interval = 1 km)

Figure 7-24.--Topographic contour map of the Phaethontis quadrangle of Mars.
(contour interval = 1 km)

Figure 7-25.--Topographic contour map of the Thaumasia quadrangle of Mars.
(contour interval = 1 km)

Figure 7-26.--Topographic contour map of the Argyre quadrangle of Mars.
(contour interval = 1 km)

Figure 7-27.--Topographic contour map of the Noachis quadrangle of Mars.
(contour interval = 1 km)

Figure 7-28.--Topographic contour map of the Hellas quadrangle of Mars.
(contour interval = 1 km)

Figure 7-29.--Topographic contour map of the Eridania quadrangle of Mars.
(contour interval = 1 km)

Figure 7-30.--Topographic contour map of the Mare Australe quadrangle of Mars. (contour interval = 1 km)

Figure 7-31.--Topographic contour map of the Mare Boreum quadrangle of Mars. (contour interval = 1 km)

PART III

CONTOURING BY STEREO PHOTOGRAMMETRIC METHODS
USING TELEVISION PICTURES OF MARINER 9

CHAPTER 8

MARINER 9 MARS IMAGERY

The primary goal of Mariner 9 was to photographically map the planet Mars, therefore, the television imaging system was the major instrumentation of the six on-board experiments. For supporting the analysis of the 7,329 pictures sent back to Earth, a large work force was required to do real-time and non real-time image processing.

8.1 Television Cameras

The imaging system consists of two television cameras which were similar to those used on Mariners 6 and 7. Both cameras have the same image format of 9.6 mm x 12.5 mm, consisting of 700 lines x 832 pixels of image elements. Each pixel size is approximately 13.3 micrometers. The wide angle camera, referred to as the A camera, has a calibrated focal length of 52.267 mm and a field of view of $11^{\circ} \times 14^{\circ}$. The other camera, called the narrow angle or B camera, has a calibrated focal length of 500.636 mm with a field of view of $1.1^{\circ} \times 1.4^{\circ}$. At a nominal altitude of 1,500 km the A camera has a 1 km to 3 km ground resolution and the B camera has a 0.1 km to 0.3 km ground resolution. Camera A had 8 changeable filters and camera B had only one fixed filter. Although the vidicon cameras introduce a number of different kinds of distortions in the imagery, they are, at present, the most feasible way of acquiring space imagery on which photogrammetric measurements can be

made (Wong, 1968). The 111 reseau marks of the A camera and 63 reseau marks in the B camera, provide a means of geometrically correcting for most of the distortions. Figures 8-1 and 8-2 show the reseau grids for camera A and B respectively. The reseau grids were calibrated and this information can be found in JPL 610-202 (Snyder, 1971).

8.2 Photography

Thirty-one pictures were taken during each 12 hour orbit of Mars. Most of the pictures were received by the 210 feet antenna at Goldstone, California and recorded on magnetic tape. The photo coverage varies from 380 x 500 km to 1,150 x 1,500 km depending upon the altitude. The photographs are identified by a DAS number (Data Automation System), derived from a spacecraft clock. It is the start time of the scanning of each picture and is an eight digit number. Obtaining stereoscopic coverage of the Martian surface was not a specific objective of the Mariner 9 mission. However, during the planet wide dust storm, many pictures which were taken of a few unobscured features from different directions in space, turned out to be a bonus for the mission. The mission planners eventually realized the potential of stereo photogrammetry. More convergent stereo coverage was acquired of features of special geologic interest. Non-conventional photogrammetric methods had to be developed to process these unusual stereo model geometries.

Figure 8-1.--Reseau grid for camera A vidicon on board Mariner 9.

Figure 8-2.--Reseau grid for camera B vidicon on board Mariner 9.

8.3 Image Processing

The television pictures from Mariner 9 were reconstructed at the Jet Propulsion Laboratory Image Processing Laboratory. There were two kinds of processing, one is real-time processing, the other is non real-time processing (Cutts, 1974). The real-time processing produced pictures from the magnetic tape records of the television image elements radioed back to earth. This computer processing involved shading corrections and contrast enhancement to bring out fine detail. The non real-time image processing produces pictures for special mapping requirements and other scientific studies. The pictures produced from this processing, in addition to contrast and detail enhancement, can also be geometrically corrected. This processing can also provide picture rectification to specific map projections (Levinthal et al., 1973, Seidman et al., 1973).

The Reduced Data Records (RDR) version, which has geometric and photometric distortions removed, are used for stereo photogrammetric work.

CHAPTER 9

NON-CONVENTIONAL PHOTOGRAMMETRIC METHOD

Some stereo coverage was acquired from the Mariner 9 mission. In most of the stereo models formed from this coverage, the camera stations were located in different orbits. Because of this, the stereo pictures have significant flight height differences, large tilt angles and different sun illumination. These conditions cause the surface feature to appear slightly different in the two stereo photographs. To set up stereo models with these very unusual model geometries, special non-conventional photogrammetric procedures which use the mission support data were developed (Wu et al., 1973). If C_1 and C_2 , as shown in figure 9-1, are the two camera stations of the convergent photography, and N_1 and N_2 are their nadir points respectively, it will be easier to obtain a model if the principal line $N_1 P_1$, which contains the principal point and the nadir point of the left photograph, is set along the x axis of the plotter and setting the model zero coordinates at the principal point. It is advantageous to prepare initial orientation parameters in which both BY and ω of photo 1 are zero. The y tilt, ϕ , of photo 1 is simply equal to VAR_1 , which is VAR-5 in the SEDR data of photo 1 (the angle between the local vertical and the direction to the spacecraft). Other parameters of photo 1 can be determined as in the following:

Figure 9-1.--Geometric configuration for setting up models with non-conventional model geometry on an analytical stereo-plotter.

$$BX_1 = (SRR-Q) (\sin VAR_1) \quad (9.1)$$

$$BZ_1 = (SRR-Q) (\cos VAR_1) + h \quad (9.2)$$

where SRR-Q in the SEDR data is the slant range from the camera station to the principal point intersecting on the Martian surface.

The determination of the initial parameters of photo 2 are almost the same as in the case of photo 1, if the principal line of photo 2 is coincident with the principal line of photo 1. But this is usually not the case as it is shown in the lower part of figure 9-1. The procedure used in determining the initial parameters of photo 2 in this case is to use the given longitudes and latitudes of the principal point and the nadir point of each photograph. From these, it is possible to find the azimuth of N_1P_1 , P_1P_2 , and P_2N_2 . Then $\Delta\alpha_p$ and $\Delta\alpha$, which are the differences between N_1P_1 and P_1P_2 , and N_1P_1 and P_2N_2 respectively, can be determined. Then:

$$BX_2 = [(SRR-Q) (\sin VAR_2)] \cos \Delta\alpha + d \cos \Delta\alpha_p \quad (9.3)$$

$$BY_2 = [(SRR-Q) (\sin VAR_2)] \sin \Delta\alpha + d \sin \Delta\alpha_p \quad (9.4)$$

$$BZ_2 = (SRR-Q) (\cos VAR_2) \quad (9.5)$$

$$\phi_2 = \arctan \frac{BX_2}{BY_2} \quad (9.6)$$

$$\omega_2 = \arctan \frac{BY_2}{BZ_2} \quad (9.7)$$

where SRR-Q in the SEDR data is the slant range from camera station 2 to the ground location of the principal point of photo 2, and VAR_2 is the local zenith at the principal point of photo 2, as is explained for photo 1, and d is the distance between the two principal points which can be determined from the given coordinates.

Parameters for each photograph should be reduced to the model scale which can simply be taken as the photo scale at the principal point of photo 1 and determined approximately as:

$$S_p = \frac{f_1 (1 - \tan \frac{t_1}{2} \sin t_1)}{H_1 - h_1} \quad (9.8)$$

where,

$$H_1 = \text{RMAG}_1 - R \quad (9.9)$$

RMAG in the SEDR data is the slant range from the spacecraft to the center of Mars; t_1 is the tilt angle which is QST in the SEDR data; R is the radius of Mars at the nadir point of photo 1. This is determined as (Bomford, 1962, p. 403):

$$R = A (1 - F \sin^2 \phi) \quad (9.10)$$

where, A is the semi-major axis of Mars,

$$A = 3,393.4 \text{ km}$$

$$F = 0.0052, \text{ the flattening of Mars}$$

$$\phi \text{ is the latitude at the nadir point}$$

$$h_1 \text{ is the elevation at the principal point of photo 1,}$$

which can be ignored when compared with H_1 .

Once all initial parameters are prepared, normal operation procedure follows on an analytical plotter for the relative orientation.

It should be mentioned that since there are no ground control points for an absolute orientation, the model is scaled by the given coordinates of the two principal points or other reseau marks. Leveling of the model is usually done arbitrarily by using the initial parameters of photo 1 as a guide.

The technique was applied to a model of camera B photographs which was set up on an analytical plotter. The photograph identification numbers are DAS-07326763 (left) and 10132929 (right). They have, according to the SEDR data, a slant range of 5,123 and 5,321 km for the left and right photographs respectively. The left photograph has a tilt angle of 2.08° and the tilt angle of the right photograph is 18.40° . The base-to-height ratio of this model is 0.37. The model scale is approximately 1:920,000. Figure 9-2, is the contour map compiled from this model and superimposed on one of the photographs as a base. The map scale is 1:100,000 and the contour interval is 400 meters with 200 meter supplemental contours. This area is a small portion of the Martian canyon lands. It has a 4.5 kilometer depth at this location.

The non-conventional photogrammetric method was also applied to another stereomodel of camera A photographs which was set up on an AS-11A analytical plotter. The photograph identification numbers are DAS-05492378 (left) and 06823918 (right). They have a slant range, to the center of Mars of 5,582 and 6,356 km and a tilt angle of 7.06° and 12.91° for the left and right photographs respectively. This is a

Figure 9-2.--Photo map of the Mars Canyonlands--compiled on AP/C plotter using B-frames DAS-0732 and -10132929, contour interval 400 m.

model of convergent photography and has a base-to-height ratio of 0.89. The model scale is 1:10,800,000 with a contour interval of 2 km. The contour map is shown in figure 9-3. This is Olympus Mons (original name Nix Olympica), the largest and highest volcanic feature ever seen. It is about 27 km high above the datum and about 500 km wide at its base. The location on the Martian surface is at longitude 134.2°W and latitude 19.0°N .

For multiple model coverage, a common control system is needed. A block adjustment technique used to provide a common control system will be discussed in the next chapter.

Figure 9-3.--Photo map of Olympus Mons, the largest volcano on the Martian surface.
(compiled on AS-11A plotter).

CHAPTER 10

BLOCK ADJUSTMENT

In order to solve the control problem of multi-model coverage, and also the problem of establishing a control net for the Viking Mars mission, a block adjustment has been derived based on analytical photogrammetry theory and a computer program has also been developed.

10.1 Theoretical Approach (Formula Derivation)

The concept of the problem of block adjustment is to solve all of the space resection, orientation and intersection problems simultaneously (Brown, Davis, and Johnson, no d.). In other words, it adjusts all camera orientation parameters and the ground survey coordinates simultaneously, based on the least squares solution. It can also determine the camera interior orientation such as the location of the principal point and the camera focal length, if it is necessary. Therefore, this method can be used to determine the exterior orientation of the camera station and the ground survey points. This is accomplished by assigning weight constraints. For example, the weight of the ground survey points is 1, if the ground coordinates are given for control, and the weight will be 0, if the ground survey coordinates are also unknown parameters.

The relationship between the camera station, the image point and the ground survey point can be expressed as shown in figure 10-1, the

Figure 10-1.--Relationships between the camera station (perspective center), the image plane (photo coordinates), and the ground object (survey point).

mathematical basis of this method can be expressed by the fact that the changes (differentials) of the photo coordinates x , y , are functions of the changes of the interior and exterior orientations of the camera as well as the changes of the ground survey points as expressed in (10.1) and (10.2):

$$\begin{aligned}
 dx = & \frac{\partial x}{\partial \kappa} d\kappa + \frac{\partial x}{\partial \phi} d\phi + \frac{\partial x}{\partial \omega} d\omega + \frac{\partial x}{\partial X_o} dX_o + \frac{\partial x}{\partial Y_o} dY_o + \frac{\partial x}{\partial Z_o} dZ_o \\
 & + \frac{\partial x}{\partial x_o} dx_o + \frac{\partial x}{\partial y_o} dy_o + \frac{\partial x}{\partial f} df + \frac{\partial x}{\partial X} dX + \frac{\partial x}{\partial Y} dY + \frac{\partial x}{\partial Z} dZ
 \end{aligned}
 \tag{10.1a}$$

$$\begin{aligned}
dy = & \frac{\partial y}{\partial \kappa} d\kappa + \frac{\partial y}{\partial \phi} d\phi + \frac{\partial y}{\partial \omega} d\omega + \frac{\partial y}{\partial X_0} dX_0 + \frac{\partial y}{\partial Y_0} dY_0 + \frac{\partial y}{\partial Z_0} dZ_0 \\
& + \frac{\partial y}{\partial x_0} dx_0 + \frac{\partial y}{\partial y_0} dy_0 + \frac{\partial y}{\partial f} df + \frac{\partial y}{\partial X} dX + \frac{\partial y}{\partial Y} dY + \frac{\partial y}{\partial Z} dZ \quad (10.1b)
\end{aligned}$$

If x^0 , y^0 are the observed photo coordinates; and if x^{00} , y^{00} are the computed values of the photo coordinates using the approximations of the related parameters; and if v is the residual of the observation, then,

$$\begin{bmatrix} v_x \\ v_y \end{bmatrix} + \begin{bmatrix} x^0 - x^{00} \\ y^0 - y^{00} \end{bmatrix} = \begin{bmatrix} \frac{\partial x}{\partial \kappa} & \frac{\partial x}{\partial \phi} & \frac{\partial x}{\partial \omega} \\ \frac{\partial y}{\partial \kappa} & \frac{\partial y}{\partial \phi} & \frac{\partial y}{\partial \omega} \end{bmatrix} \begin{bmatrix} d\kappa \\ d\phi \\ d\omega \end{bmatrix} \quad \begin{array}{l} \text{-- ER, (Exterior orientation)} \\ \text{---rotation} \end{array}$$

$$+ \begin{bmatrix} \frac{\partial x}{\partial X_0} & \frac{\partial x}{\partial Y_0} & \frac{\partial x}{\partial Z_0} \\ \frac{\partial y}{\partial X_0} & \frac{\partial y}{\partial Y_0} & \frac{\partial y}{\partial Z_0} \end{bmatrix} \begin{bmatrix} dX_0 \\ dY_0 \\ dZ_0 \end{bmatrix} \quad \begin{array}{l} \text{-- ET, (Exterior orientation)} \\ \text{---translation} \end{array}$$

$$+ \begin{bmatrix} \frac{\partial x}{\partial x_0} & \frac{\partial x}{\partial y_0} & \frac{\partial x}{\partial f} \\ \frac{\partial y}{\partial x_0} & \frac{\partial y}{\partial y_0} & \frac{\partial y}{\partial f} \end{bmatrix} \begin{bmatrix} dx_0 \\ dy_0 \\ df \end{bmatrix} \quad \text{-- I, (Interior orientation)}$$

$$+ \begin{bmatrix} \frac{\partial x}{\partial X} & \frac{\partial x}{\partial Y} & \frac{\partial x}{\partial Z} \\ \frac{\partial y}{\partial X} & \frac{\partial y}{\partial Y} & \frac{\partial y}{\partial Z} \end{bmatrix} \begin{bmatrix} dX \\ dY \\ dZ \end{bmatrix} \quad \text{-- S, (Survey point)}$$

(10.2)

or if ϵ is the difference between the observed and computed values, let B represent the change in photo coordinates due to the change in exterior, interior, or the survey points, and let Δ be the alternative, then,

$$V + \epsilon = B^{ER} \Delta^{ER} + B^{ET} \Delta^{ET} + B^I \Delta^I + B^S \Delta^S \quad (10.3)$$

Since the camera is always calibrated before it is to be used, then equation (10.3) becomes:

$$V + \epsilon = B^E \Delta^E + B^S \Delta^S \quad (10.4)$$

This is the form of the observation equations on photo coordinates. Each point comprises two equations. From equation (10.4), for each camera, there are six parameters as "ER" and "ET" in equation (10.2), and for each survey point, there are three elements as "S" in equation (10.2). Therefore, the form of the condition equations are:

$$V_i^E - \Delta_i^E + \epsilon_i^E = \overline{0} \quad (10.5)$$

$$V_j^S - \Delta_j^S + \epsilon_j^S = \overline{0} \quad (10.6)$$

where

$i = 1 \dots m$, the number of camera stations, and

$j = 1 \dots n$, the number of ground survey points.

Therefore, the general form of the total condition equations for the resection, orientation, and intersection problems is:

$$\begin{bmatrix} V \\ V^E \\ V^S \end{bmatrix} - \begin{bmatrix} B^E & B^S \\ I & \overline{0} \\ \overline{0} & I \end{bmatrix} \begin{bmatrix} \Delta^E \\ \Delta^S \end{bmatrix} + \begin{bmatrix} \epsilon \\ \epsilon^E \\ \epsilon^S \end{bmatrix} = \overline{0} \quad (10.7)$$

The notation of the condition equations can be simplified to:

$$V - B\Delta + \epsilon = 0 \quad (10.8)$$

The total number of the observation equations is $2mn$.

From equation (10.8), $V = B\Delta - \epsilon$. To get the normal equations in the form, $N\Delta + U = 0$, the least squares method is applied to make $V'WV$ a minimum, where W is the weight. If we apply Taylor's series such that,

$$F = V'WV - 2k' (V - B\Delta + \epsilon)$$

then,

$$\frac{F}{V} = 0 \rightarrow B^T W B \Delta + B^T W \epsilon = 0 \quad (10.9)$$

Equation (10.9) is the form of the normal equations, where $N = B^T W B$, and $U = B^T W \epsilon$.

The total number of the normal equations is $6m + 3n$ which is also the number of unknowns in the simultaneous solution of the resection and intersection problems.

From equation (10.9), the partition matrix of the normal equations can be formed as:

$$\left[\begin{array}{c|c} B^{ET}_{WB} E + W^E & B^{ET}_{WB} S \\ \hline B^{ST}_{WB} E & B^{ST}_{WB} S + W^S \end{array} \right] \begin{bmatrix} \Delta^E \\ \Delta^S \end{bmatrix} + \begin{bmatrix} B^{ET}_{W\epsilon} - W^E_{\epsilon} E \\ B^{ST}_{W\epsilon} - W^S_{\epsilon} S \end{bmatrix} \quad (10.10)$$

(6m + 3n) × (6m + 3n)

Equation (10.10) is the form of the normal equations, which is ready for programming for a simultaneous solution of the block adjustment. The size of this matrix depends upon the number of photographs (m) and the number of ground survey points (n) as:

$$\begin{array}{c} \uparrow 6m \\ \downarrow \\ \uparrow 3n \\ \downarrow \end{array} \left[\begin{array}{cc|ccc} [6 \times 6] & \bar{0} & [6 \times 3] & \cdots & [6 \times 3] \\ & \bar{0} & [6 \times 3] & \cdots & [6 \times 3] \\ \hline [3 \times 6] & \cdots & [3 \times 6] & [3 \times 3] & \bar{0} \\ [3 \times 6] & \cdots & [3 \times 6] & \bar{0} & [3 \times 3] \end{array} \right] \quad \begin{array}{c} \xleftarrow{6m} \quad \xrightarrow{3n} \end{array} \quad (10.11)$$

where in equation (10.10),

$$B^{ET}_{WB} E + W^E = \begin{bmatrix} B_1^{ET} W_1 B_1^E & \bar{0} \\ & \ddots \\ \bar{0} & B_m^{ET} W_m B_m^E \end{bmatrix} + \begin{bmatrix} W_1^E & \bar{0} \text{ or } 0 \\ & \ddots \\ \bar{0} \text{ or } 0 & W_m^E \end{bmatrix} \quad (10.12a)$$

$$B^{ST}_{WB} S = \begin{bmatrix} B_1^{ST} W_1 B_1^S & \bar{0} \\ & \ddots \\ \bar{0} & B_n^{ST} W_n B_n^S \end{bmatrix} \begin{bmatrix} W_1^S & \bar{0} \text{ or } 0 \\ & \ddots \\ \bar{0} \text{ or } 0 & W_n^S \end{bmatrix} \quad (10.12b)$$

$$B^{ET}_{WB} S = \begin{bmatrix} B_1^{ET} W_1 B_1^S \cdots B_1^{ET} W_n B_n^S \\ \vdots \\ B_m^{ET} W_m B_1^S \cdots B_m^{ET} W_n B_n^S \end{bmatrix} \quad (10.12c)$$

$$B_{(3n)(6m)}^{ST_{WB}E} = \begin{bmatrix} B_1^{ST_{W_1B_1}E} & \dots & B_n^{ST_{W_nB_n}E} \\ \vdots & & \vdots \\ B_n^{ST_{W_nB_1}E} & \dots & B_n^{ST_{W_nB_n}E} \end{bmatrix} \quad (10.12d)$$

$$B_{(6m)(1)}^{ET_{WE-W}E} = \begin{bmatrix} B_1^{ET_{W_1\epsilon_1}E} - W_1^{E\epsilon_1}E \\ \vdots \\ B_m^{ET_{W_m\epsilon_m}E} - W_m^{E\epsilon_m}E \end{bmatrix} \quad (10.12e)$$

$$B_{(3n)(1)}^{ST_{WE-W}S} = \begin{bmatrix} B_1^{ST_{W_1\epsilon_1}S} - W_1^{S\epsilon_1}S \\ \vdots \\ B_n^{ST_{W_n\epsilon_n}S} - W_n^{S\epsilon_n}S \end{bmatrix} \quad (10.12f)$$

and wherever the symbol $\bar{0}$ or $\emptyset$ occurs it means that it is either a diagonal matrix or a full matrix, depending on whether they are independent or correlated. In most cases, the matrices of weighting are diagonal matrices because of the uncorrelation. The information for weighting can be obtained from:

$$\epsilon_{\Delta} = \mu_o^2 N^{-1} \quad (10.13)$$

$$\mu_o^2 = \frac{V'WV}{2mn - (6m + 3n)} \quad (10.14)$$

$$W = \sigma_o^2 \Sigma_{xy}^{-1} \quad (10.15)$$

Since B matrices, previously defined at the beginning of this section, are the changes in the photo coordinates due to the changes in the exterior orientation and the changes in the ground survey coordinates, we can apply the partial differentiation to the photo coordinates x, y.

The basic formulas for the photo coordinates x , y are:

$$x = x_o + \frac{f}{Z} X \quad (10.16a)$$

$$y = y_o + \frac{f}{Z} Y \quad (10.16b)$$

where x_o , y_o are the coordinates of the principal point in the photograph, usually zero and $\frac{f}{Z}$ serves as the scaling from the ground X , Y coordinates. But since the camera stations are not truly vertical, then x , y should also involve the three angular rotations as well as the translation of the exposure station itself. Therefore, equations (10.16) become:

$$x = x_o + f \left[\frac{A(X-X_o) + B(Y-Y_o) + C(Z-Z_o)}{G(X-X_o) + H(Y-Y_o) + (Z-Z_o)} \right] \quad (10.17a)$$

$$y = y_o + f \left[\frac{D(X-X_o) + E(Y-Y_o) + F(Z-Z_o)}{G(X-X_o) + H(Y-Y_o) + (Z-Z_o)} \right] \quad (10.17b)$$

where

$$\begin{bmatrix} A & B & C \\ D & E & F \\ G & H & I \end{bmatrix} = \begin{bmatrix} m_{11} & m_{12} & m_{13} \\ m_{21} & m_{22} & m_{23} \\ m_{31} & m_{32} & m_{33} \end{bmatrix} = [M] = [\kappa] [\phi] [\omega] \quad (10.17c)$$

of which,

$$\kappa = \begin{bmatrix} \cos \kappa & \sin \kappa & 0 \\ -\sin \kappa & \cos \kappa & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$\phi = \begin{bmatrix} \cos \phi & 0 & \sin \phi \\ 0 & 1 & 0 \\ -\sin \phi & 0 & \cos \phi \end{bmatrix}$$

$$\omega = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos \omega & \sin \omega \\ 0 & -\sin \omega & \cos \omega \end{bmatrix} \quad (10.18)$$

After substituting the multiplication of the three sequential rotations with the primary ω about x-axis, the secondary ϕ about the y' -axis, and the tertiary κ about the z'' -axis, x, y coordinates are expressed as:

$$\begin{bmatrix} x \\ y \end{bmatrix} = \frac{f}{D} \begin{bmatrix} N_x \\ N_y \end{bmatrix} + \begin{bmatrix} x_o \\ y_o \end{bmatrix} \quad (10.19a)$$

where,

$$D = (X-X_o)\sin \phi - (Y-Y_o)\sin \omega \cos \phi + (Z-Z_o)\cos \omega \cos \phi \quad (10.19b)$$

$$N_x = (X-X_o)\cos \phi \cos \kappa + (Y-Y_o)(\cos \omega \sin \kappa + \sin \omega \sin \phi \cos \kappa) \\ + (Z-Z_o)(\sin \omega \sin \kappa - \cos \omega \sin \phi \cos \kappa) \quad (10.19c)$$

$$N_y = -(X-X_o)\cos \phi \sin \kappa + (Y-Y_o)(\cos \omega \cos \kappa - \sin \omega \sin \phi \sin \kappa) \\ + (Z-Z_o)(\sin \omega \cos \kappa + \cos \omega \sin \phi \sin \kappa) \quad (10.19d)$$

Then applying partial differentiation to x and y with respect to the unknown parameters which are the elements of the exterior orientation and the ground survey coordinates as:

$$\begin{aligned} \frac{\partial x}{\partial \kappa} = \frac{f}{D^2} \{ & D[-(X-X_0)\cos \phi \sin \kappa + (Y-Y_0)(\cos \omega \cos \kappa - \sin \omega \sin \phi \sin \kappa) \\ & + (Z-Z_0)(\sin \omega \cos \kappa + \cos \omega \sin \phi \sin \kappa)] \} \end{aligned} \quad (10.20)$$

$$\begin{aligned} \frac{\partial x}{\partial \phi} = \frac{f}{D^2} \{ & D[-(X-X_0)\sin \phi \cos \kappa + (Y-Y_0)\sin \omega \cos \phi \cos \kappa \\ & - (Z-Z_0)\cos \omega \cos \phi \cos \kappa] - N_X [(X-X_0)\cos \phi \\ & + (Y-Y_0)\sin \omega \sin \phi - (Z-Z_0)\cos \omega \sin \phi] \} \end{aligned}$$

$$\begin{aligned} \frac{\partial x}{\partial \omega} = \frac{f}{D^2} \{ & D[-(Y-Y_0)(\sin \omega \sin \kappa - \cos \omega \sin \phi \cos \kappa) \\ & + (Z-Z_0)(\cos \omega \sin \kappa + \sin \omega \sin \phi \cos \kappa)] \\ & + N_X [(Y-Y_0)\cos \omega \cos \phi + (Z-Z_0)\sin \omega \cos \phi] \} \end{aligned}$$

$$\frac{\partial x}{\partial X_0} = \frac{f}{D^2} \{-D(\cos \phi \cos \kappa) + N_X \sin \phi\}$$

$$\frac{\partial x}{\partial Y_0} = \frac{f}{D^2} \{-D(\cos \omega \sin \kappa + \sin \omega \sin \phi \cos \kappa) - N_X \sin \omega \cos \phi\}$$

$$\frac{\partial x}{\partial Z_0} = \frac{f}{D^2} \{-D(\sin \omega \sin \kappa - \cos \omega \sin \phi \cos \kappa) + N_X \cos \omega \cos \phi\}$$

$$\begin{aligned} \frac{\partial y}{\partial \kappa} = - \frac{f}{D^2} \{ & D[(X-X_0)\cos \phi \cos \kappa + (Y-Y_0)(\cos \omega \sin \kappa + \sin \omega \sin \phi \cos \kappa) \\ & + (Z-Z_0)(\sin \omega \sin \kappa - \cos \omega \sin \phi \cos \kappa)] \} \end{aligned}$$

$$\begin{aligned}\frac{\partial y}{\partial \phi} = \frac{f}{D^2} \{ & D[(X-X_0)\sin \phi \sin \kappa - (Y-Y_0)\sin \omega \cos \phi \sin \kappa \\ & + (Z-Z_0)\cos \omega \cos \phi \sin \kappa] - N_Y [(X-X_0)\cos \phi \\ & + (Y-Y_0)\sin \omega \sin \phi - (Z-Z_0)\cos \omega \sin \phi] \}\end{aligned}$$

$$\begin{aligned}\frac{\partial y}{\partial \omega} = \frac{f}{D^2} \{ & D[-(Y-Y_0)(\sin \omega \cos \kappa + \cos \omega \sin \phi \sin \kappa) \\ & + (Z-Z_0)(\cos \omega \cos \kappa - \sin \omega \sin \phi \sin \kappa)] \\ & + N_Y [(Y-Y_0)\cos \omega \cos \phi + (Z-Z_0)\sin \omega \cos \phi] \}\end{aligned}$$

$$\frac{\partial y}{\partial X_0} = \frac{f}{D^2} [D \cdot \cos \phi \sin \kappa + N_Y \sin \phi]$$

$$\frac{\partial y}{\partial Y_0} = \frac{f}{D^2} [-D(\cos \omega \cos \kappa - \sin \omega \sin \phi \sin \kappa) - N_Y \sin \omega \cos \phi]$$

$$\frac{\partial y}{\partial Z_0} = \frac{f}{D^2} [-D(\sin \omega \cos \kappa + \cos \omega \sin \phi \sin \kappa) + N_Y \cos \omega \cos \phi]$$

$$\frac{\partial x}{\partial X} = - \frac{\partial x}{\partial X_0} \quad \frac{\partial x}{\partial Y} = - \frac{\partial x}{\partial Y_0} \quad \frac{\partial x}{\partial Z} = - \frac{\partial x}{\partial Z_0}$$

$$\frac{\partial y}{\partial X} = - \frac{\partial y}{\partial X_0} \quad \frac{\partial y}{\partial Y} = - \frac{\partial y}{\partial Y_0} \quad \frac{\partial y}{\partial Z} = - \frac{\partial y}{\partial Z_0}$$

The values of the above partial differentiations will constitute the matrices B^E and B^S . The computation is accomplished by successive approximations.

10.2 Practical Application (Coordinate Measurement and Data Processing)

Since the purpose of this task is to develop the method and procedures to be used during the Viking Mars missions for deriving a control net, a block of six Mariner 9 camera A photographs were selected for the program testing. These six photographs cover a prominent feature on the Martian surface called Olympus Mons, as shown in figure 9-3, which is the largest volcano yet discovered in the solar system. However, fictitious data was used for debugging the program.

This section describes the data procurement including photographic coordinate measurements and refinement, and the programming for the block adjustment.

10.2.1 Conditions of the Selected Photographs

The six photographs selected from Mariner 9 camera-A frames include DAS-05492378, 06823918, 06823708, 06823428, 09701344 and 06895668. These photographs were taken at altitudes ranging from 2,200 kilometers to 2,970 kilometers. Therefore, their scales are small, ranging from 1:42,000,000 to 1:56,800,000 and the ground resolution is about 1.5 kilometers. Tilt angles range from 2.5° to 21.4° . Each photo covers 400 km x 500 km or more. These conditions may make the convergence of the simultaneous solution difficult.

10.2.2 Photo Coordinate Measurement

A total of 40 pass points were selected in the area of coverage. Each of the 40 points appears on at least two or more of the selected

six photographs. The RDR version data tapes were used to generate the imagery which was put on glass plates. The final imagery is about 3.76 times magnified since the 50 micrometer increment on the optronics photowrite system was used.

Measurements were made on a digitized Mann Comparator which has a precision of from one to two micrometers. As shown in figure 8-1, the center 85 reseau marks were measured. The two extreme outside columns of reseau marks were not used. All of the pass points appearing on each photograph were also measured.

10.2.3 Coordinate Refinement

Corrections applied to the photo coordinate measurements include film shrinkage correction, lens distortion correction and Mars curvature correction.

Film Shrinkage Correction. In the film shrinkage correction, two polynomials having 12 unknowns and carried to the second degree were used where the x-, y- coordinates are corrected simultaneously. The polynomials are:

$$\Delta x = A + Bx + Cx^2 + Dy + Ey^2 + Fxy \quad (10.21a)$$

$$\Delta y = G + Hx + Ix^2 + Jy + Ky^2 + Lxy \quad (10.21b)$$

where Δx and Δy are the differences between the measured and calibrated x, y coordinates of the reseau marks.

Lens Distortion Correction. The requirement for the camera lenses that were used for the Mariner Mars 1971 mission was that the lens distortion should be less than $f(2/10,000)$ which is less than 11 micrometers (Snyder, 1971) for the A camera. The cameras were pre-flight calibrated and the actual distortions were equal to or less than 10 micrometers within a radial distance of 6.3 mm. But the distortions can go as high as 33 micrometers at the corner points of the photograph. Lens distortions were applied by using equations:

$$\Delta x = (x - x_p)(p_1 r^2 + p_2 r^4) - (y - y_p)(q_1 r + q_2 r^3) \quad (10.22a)$$

$$\Delta y = (y - y_p)(p_1 r^2 + p_2 r^4) + (x - x_p)(q_1 r + q_2 r^3) \quad (10.22b)$$

where Δx and Δy are the corrections for the lens distortion applied to the x and y coordinates respectively, x_p and y_p are the principal point eccentricity which are 0.213 mm and 0.317 mm respectively, p_1 and p_2 are coefficients of the radial symmetrical optical distortion, and $p_1 = 0.915181\text{-E}5$, $p_2 = -0.126362\text{-E}5$; q_1 and q_2 are coefficients of the tangential symmetrical optical distortion and $q_1 = 0.626100\text{-E}5$, $q_2 = 0.169432\text{-E}8$.

Curvature Correction. For extremely high altitude photography, correction for the Martian surface curvature is necessary. The curvature correction is applied to the image points by using the formula:

$$d_c = \frac{H}{2Rf^2} r^3 \quad (10.23)$$

where

H is the flight height above the Martian surface in kilometers

R is the mean radius of Mars, also in kilometers

f is the camera focal length in millimeters

r is the radial distance of the image point from the principal point

d_c is the curvature correction along the radial direction in millimeters. This correction should be computed in terms of its x and y components.

Among these six selected photographs, d_c can be as large as 0.060 mm at the original scale and equivalent to 3.5 kilometers on the ground if the curvature correction were not applied.

Results of Corrections. After applying all of the corrections as described in this section, the photo coordinates of each photograph are refined and ready for use in the block adjustment. The corrections as listed in table 10.1, on the following page, are average values from each photograph. It is of interest to note that the magnitudes of the lens distortion corrections are only 2 to 3 micrometers at the original photo scale.

10.2.4 Block Adjustment Programming

Since the concept of the block adjustment is to solve the resection and intersection problems simultaneously by an iterative method, initial estimates of exterior orientation parameters and X , Y , Z coordinates of survey points must be made. Those parameters which are exactly known, will be used as controls, and a weight of "1" will be assigned to them, so their values will be preserved.

Table 10.1--Results of the photo coordinate refinement.

Photo DAS number	Magnification	Film shrinkage distortion x(mm) y(mm)	Lens distortion correction x(mm) y(mm)	Principal distance (mm)
05492378	3.7580	0.028 0.027	0.008 0.004	196.419
06823918	3.7589	0.054 0.059	0.007 0.006	196.465
06823708	3.7583	0.019 0.017	0.013 0.009	196.433
06823428	3.7581	0.024 0.040	0.009 0.010	196.424
09701344	3.7591	0.039 0.051	0.015 0.007	196.477
06895668	3.7553	0.029 0.025	0.003 0.005	196.277

Note: (1) All magnitudes are at the magnified photo scale
 (2) Distortions in each category are average values from each photograph.

This means that their value will never be changed. For those parameters which are unknowns, in this case the pass points, very weak weights are assigned and they are changed after each iteration until the changes become small, falling within the pre-set criterion. The program will then stop and the solution is arrived at.

As previously described, equation (10.10) is the form of the normal equations in which all elements are defined in equations (10.12a) through (10.12f), of which, the B^E and B^S matrices are made up of values of the partial differentiations of the photo x and y coordinates with respect to the camera exterior orientation parameters and the survey point coordinates as defined in equations (10.20). The most important part of this problem is to assign the proper weights to the elements involved.

During each iteration the values of Δ^E and Δ^S , the changes of exterior orientation parameters and survey coordinates, are computed by solving the normal equations (10.10). These changes should be decreasing and eventually become insignificant after a few iterations.

Because of the matrix size, as indicated in (10.11), the program for the block adjustment always needs a big computer. For instance, in this selected block which consists of 6 photographs and 40 pass points, the size of the normal equation matrix is $(6m + 3n) \times (6m + 3n) = 156 \times 156$.

The program was debugged by using fictitious data for a block of three pictures with 20 survey points. The photographs were assumed to have a photo scale of 1:6,000. After five iterations, it converged with linear errors of less than 10 meters and angular parameter errors of less than 0.05° . But with the Mariner photography, due to the complete lack of ground control and the low degree of accuracy of the camera parameters, there is no real sound basis for assigning weights

except by using the method of trial and error. Therefore, it has been difficult to obtain reasonable results. Further investigations are being carried on in search of some non-conventional techniques which might be used in dealing with this non-conventional photogrammetric problem.

PART IV

DISCUSSIONS AND CONCLUSIONS

CHAPTER 11

DISCUSSIONS, CONCLUSIONS, AND RECOMMENDATIONS

Using the sensor data of the Mariner 9 mission and the Earth-based radar data, this experiment of the topographic contouring of Mars has resulted in the completion of the first comprehensive contour map of Mars. This is the first map of the topography of the entire Martian surface compiled at a resolution significantly higher than that achieved from Earth-based measurements. Also, the mapping technique is unique and the first to be used in the mapping of a planetary body. However, due to the broad involvement of many scientific fields, many difficult problems occurred during the compilation and after the completion of the map. This chapter discusses the problems, the conclusions and recommendations for future Mars mapping activities.

11.1 Problems

Because of the broad involvement, the most noticeable problem was the difficulty in collecting data from other scientists and experimenters of the Mariner 9 mission. This experiment was delayed about two years because of the time involved in getting data from some of the data sources. Frequent revisions of the results of the data analysis of some of the experiments has greatly increased the task of this experiment, causing the original planned budget to be exceeded.

Technical problems, of course, cannot be avoided. Because of the nature of the unconventional photography, that is: television

vidicon camera imagery, extremely high flight heights, extremely large surface coverage presenting a problem with large magnitude of curvature corrections, high tilt angles, the complete lack of ground controls, and in addition, there are uncertainties in the range distances and the angular parameters from the mission support data which are as much as 10 kilometers and 0.2° respectively (Blasius, 1973); it has been found to be very difficult to establish ground control points on the Martian surface by the traditional methods of analytical photogrammetry for stereoscopic compilation. For the support of the Mars landing of the Viking Mars mission, stereo compilation has become necessary and so the solution of the control problem has also become necessary.

11.2 Discussions

The following discussions are intended to be brought to the attention of related or interested scientists.

11.2.1 The Use of Earth-Based Radar Data

Earth-based radar observations of the Martian surface have been found to be one of the more significant sources of information of the Martian topography. But the problem it faced in this experiment is the assumption of the figure of Mars which was based on the analysis of the results of the radar oppositions during the early days. Most of the past radar opposition experimenters assumed a spherical figure for Mars, except in the case of the 1973 oppositions observed at the Goldstone Observatory where a triaxial ellipsoid of Mars was used. The triaxial ellipsoid (Standish) as discussed in chapter 3, is

Datum of triaxial ellipsoid

$$A = 3,399.3 \text{ km}$$

$$B = 3,394.0 \text{ km}$$

$$C = 3,376.4 \text{ km}$$

$$\theta_A = 100.9^\circ \text{W}$$

$$f = 0.0060$$

$$x_o = -0.12 \text{ km}$$

$$y_o = -1.47 \text{ km}$$

$$z_o = -2.89 \text{ km}$$

$$d = \sqrt{x_o^2 + y_o^2 + z_o^2} = 3.245 \text{ km}$$

offset referred
to the
center of mass

Datum (6.1 mb pressure surface)

$$A = 3,394.6 \text{ km}$$

$$B = 3,393.3 \text{ km}$$

$$C = 3,376.3 \text{ km}$$

$$\theta_A = 105^\circ \text{W}$$

$$f = 0.00525$$

Figure 11-1.--Comparison between the parameters of the triaxial ellipsoid and the 6.1 mb gravity datum.--In the diagram the heavy line represents the triaxial ellipsoid and the thin line represents the 6.1 mb datum.

significantly different from the topographic datum. The length of the semi-major axis is different and there is a 3.245 kilometers shift in the center of mass of Mars as shown in figure 11-1. Therefore, the 1973

radar data from the Goldstone Observatory is suspected of being referred to the center of figure of the triaxial ellipsoid used. In order to convert the radar elevations, H_R , which are referred to the Standish triaxial ellipsoid, to the topographic datum triaxial ellipsoid at that radar point, R_{CF} has to be determined first, as:

$$R_{CF} = R_m \left[1 + f \left(\frac{1}{3} - \sin^2 \psi \right) + \frac{1}{2} f' \cos^2 \psi \cos 2(\lambda - \lambda_o) \right] \quad (11.1)$$

where

$$R_m = A' \left(1 - \frac{1}{3} f - \frac{1}{9} f'^2 \right) \quad (11.2)$$

$$A' = \sqrt{AB} \quad (11.3)$$

$$f' = \frac{A - B}{A} \quad \text{flattening of the equator} \quad (11.4)$$

ψ is areocentric latitude

$$\lambda_o = \theta_A$$

As shown in figure 11-2, the relationship between the center of figure and the center of mass is:

$$d = 3.245 \text{ kilometers} \quad (\text{distance})$$

$$\lambda_{CM} = \tan^{-1} \frac{1.47}{0.12} = -85.3^\circ = 274.7^\circ \quad (\text{difference of longitude})$$

$$\phi_{CM} = \tan^{-1} \frac{2.89}{\sqrt{0.12^2 + 0.147^2}} = 63^\circ \quad (\text{difference of latitude})$$

Figure 11-2.--Displacement of the center of mass from the center of figure.

Then, as shown in figure 11-3, to convert the radius referred to the center of figure, R_{CF} , to refer to the center of mass, R_{CM} , the following equation is used:

$$R_{CM}^2 = R_{CF}^2 + d^2 - 2 R_{CF} d \cos \gamma \quad (11.5)$$

where

$$\cos \gamma = \sin \psi_{CM} \sin \psi + \cos \psi_{CM} \cos \psi \cos (\lambda - \lambda_{CM}) \quad (11.6)$$

Then the radius, R_T , of the topography at that point is determined by

$$R_T = R_{CM} + H_R \quad (11.7)$$

Figure 11-3.--Relationship between the radii from a point P on the triaxial ellipsoidal datum to the center of figure and the center of mass.

Using equations (3.2), (3.3) and (3.4), the topographic datum, R_D , referred to the center of mass at the point can be determined and the converted elevation is obtained by

$$H_C = R_T - R_D \quad (11.8)$$

It should be noted that the areocentric latitude should be converted to areographic latitude in order to use equations (3.2) to (3.4).

As an example of the previous discussion, recent radar observations at 16.0°S and 120°W , and 16.0°S and 98°W of the Martian surface determined the elevations at these two points to be 4.5 km and 2.0 km respectively, which are referred to the center of figure of the triaxial ellipsoid. Following the conversion computation, they become 8.9 km and 7.8 km respectively, which are now referred to the center of mass of the adopted topographic datum. From the map in figure 7-1, the

elevations at those two points are found to be 9.0 km and 9.2 km respectively. The differences between the converted elevations and the map elevations are much smaller than the differences between the unconverted elevations and the map elevations.

11.2.2 Martian Flattening

The topographic contour map of Mars, produced from this experiment and shown in figure 7-1, does show a ring of high mountainous terrain along the equatorial belt as shown in figure 11-4. This may confirm the suspicions of H. C. Urey in 1950, that there may be high mountainous terrain along the equatorial zone which is isostatically compensated by a layer of less dense material beneath the mountains. Therefore, the Martian flattening determined by optical measurements is always larger than that determined dynamically.

11.3 Conclusions

The results from both the occultation and celestial mechanics experiments have shown that the long axis of the equatorial ellipse passes through the Tharsis region which has unusually high volcanoes. Tracking data has also shown that the great gravity anomaly is at this region and it is 17 times greater than any on Earth. This demonstrates that the gravity potential does reflect the Martian topography.

The Martian topography shows the largest circular feature, Hellas Planitia, which is about 2,500 kilometers in diameter, to be almost twice the size of the largest basin on the Moon - Mare Imbrium, and the volcanic feature, Olympus Mons, which is 27 kilometers high

Figure 11-4.--Topographic profile along the Martian equator.--The zero circle represents the topographic datum of Mars and the high peak of 27 kilometers elevation is at 113° of longitude, which is the top of Pavonis Mons.

above the datum is almost three times the width and height of the largest of the Hawaiian volcanoes, Mauna Loa. The discoveries of these huge volcanoes, indicates that Mars is still geologically active. The great equatorial canyon complex, Valles Marineris, is as much as 6 kilometers deep and extends more than 4,800 kilometers and is 200 kilometers wide at the widest place.

Another peculiar Martian topographic feature is that the entire southern hemisphere is about 4 kilometers higher than the northern hemisphere. This is due to the fact that the center of mass of Mars is shifted closer to the northern hemisphere. On the other hand, the topography at the south pole, as shown in figure 7-30, is low. This was determined by stereo compilation of a few models of very small scale photographs. For most of the time during the standard mission, the south pole was having its summer at which time the polar cap material was non-existent and therefore the terrain was clearly visible. This may be interpreted to mean that the cap deposit material may be a few kilometers of water ice crystals as indicated by G. Kuiper's infrared studies. The south pole at that time, was seen to be bright, indicating lowlands, where as the high volcanoes were seen to be dark, indicating high mountains.

The Mars topographic maps do not show any linear dark canal-like features. The linear dark marks observed in the past, have been interpreted to be the phenomenon of material transport by strong winds.

Except in a few locations, the Martian topography shows that elevations of most of the planet surface is above the triple-point pressure elevation. Therefore, the Martian atmospheric pressure is not dense enough to allow water to exist in the liquid state.

11.4 Recommendations

For improving the Mars topographic mapping, the following recommendations are offered for consideration.

11.4.1 Revision of the Mars Contour Maps

Due to the insufficient topographic information on Mars during the compilation conducted by this experiment, and because additional data will be acquired during the upcoming Viking Mars missions along with the continuing observations by the Earth-based radars, it would certainly be worthwhile to update and improve the Mars topographic maps. To do this, the previously developed techniques will probably be the most advantageous to use.

11.4.2 Compilation of Large Scale Mars Maps

Since more stereoscopic coverage of locations of scientific interest on the Martian surface will be photographed during the Viking Mars missions, large scale contour maps should be compiled by stereo photogrammetric methods. These large scale maps will be very useful for geological studies and will probably also be useful to other scientific studies of the Martian surface.

11.4.3 Publication of Topographic Data

The topographic contour maps produced from this experiment will be published. Hundreds of data points which have been adjusted to the common topographic datum of Mars and used for the compilation of the Mars maps are in tabulated form. These may be found useful to interested people. It is therefore recommended that this data be published in tabulated form to be made available to the scientific community.

11.4.4 Modification of the Mercator Projection

The scale ratio at latitude 65° , as listed in table 2.1, is 2.356 times as large as the scale at the equator. This range of scale variations is too large. It is recommended that the cylindrical surface be made secant at 43.33° north and south latitudes rather than tangent to the Martian equator. As in the case of the Lambert conic projection with two standard parallels this will reduce the scale variations significantly.

11.4.5 Primary Control Net

It is recommended that the Mars primary control net adjustment produced by Merton E. Davies of the Rand Corporation, be rerun using the elevation information from the Mars topographic maps as a strong constraint in the program. Useful elevation control from the adjustment can be expected, and not much additional work will be required, since all of the measurements (pixel count) have been done and are still available.

11.4.6 Mars Figure for Radar Observations

To maintain consistency, and also for the simplification of the data reduction, it is recommended that all Earth-based radar observations begin to use the adopted Mars figure (fourth order and fourth degree spherical harmonics gravity field with a 6.1 millibar pressure surface) for their observations and analyses.

APPENDIX A

DATUM AND CONTROL OF MARS TOPOGRAPHY

TABLE A1-1.--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	10°	20°	30°	40°	50°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	76.979	76.969	76.960	76.953	76.947
-70	78.413	78.397	78.387	78.381	78.378
-60	80.633	80.614	80.604	80.604	80.614
-50	83.386	83.360	83.349	83.356	83.384
-40	86.348	86.307	86.289	86.301	86.350
-30	89.158	89.097	89.066	89.079	89.149
-20	91.467	91.383	91.335	91.347	91.437
-10	92.979	92.875	92.814	92.824	92.932
0	93.498	93.384	93.315	93.327	93.449
10	92.956	92.842	92.777	92.795	92.925
20	91.420	91.318	91.265	91.291	91.420
30	89.087	89.004	88.968	89.000	89.117
40	86.251	86.189	86.167	86.199	86.294
50	83.263	83.217	83.203	83.227	83.292
60	80.480	80.447	80.434	80.444	80.477
70	78.229	78.204	78.190	78.186	78.192
80	76.764	76.749	76.737	76.128	76.721
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	60°	70°	80°	90°	100°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	76.943	76.939	76.936	76.934	76.932
-70	78.378	78.379	78.380	78.378	78.374
-60	80.630	80.650	80.668	80.678	80.677
-50	83.429	83.485	83.541	83.583	83.599
-40	86.434	86.545	86.662	86.759	86.811
-30	89.279	89.457	89.652	89.824	89.930
-20	91.613	91.861	92.140	92.394	92.562
-10	93.148	93.456	93.808	94.133	94.355
0	93.693	94.040	94.436	94.804	95.059
10	93.177	93.531	93.933	94.304	94.561
20	91.659	91.987	92.354	92.688	92.915
30	89.323	89.596	89.895	90.161	90.334
40	86.451	86.652	86.865	87.047	87.159
50	83.394	83.519	83.647	83.751	83.807
60	80.527	80.587	80.646	80.690	80.708
70	78.205	78.221	78.236	78.245	78.245
80	76.717	76.713	76.711	76.708	76.704
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	110°	120°	130°	140°	150°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	76.932	76.933	76.935	76.940	76.947
-70	78.366	78.358	78.350	78.345	78.348
-60	80.661	80.634	80.600	80.568	80.547
-50	83.581	83.530	83.455	83.375	83.307
-40	86.801	86.726	86.600	86.452	86.316
-30	89.939	89.844	89.662	89.435	89.214
-20	92.597	92.487	92.251	91.944	91.635
-10	94.417	94.296	94.016	93.642	93.258
0	95.136	95.009	94.703	94.287	93.854
10	94.637	94.509	94.198	93.775	93.333
20	92.976	92.849	92.559	92.166	91.754
30	90.370	90.252	90.002	89.671	89.327
40	87.169	87.069	86.875	86.625	86.370
50	83.779	83.723	83.591	83.428	83.266
60	80.693	80.646	80.572	80.486	80.404
70	78.233	78.211	78.182	78.152	78.126
80	76.700	76.696	76.691	76.689	76.690
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	160°	170°	180°	190°	200°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	76.957	76.970	76.985	77.001	77.019
-70	78.359	78.379	78.409	78.446	78.486
-60	80.544	80.562	80.602	80.659	80.724
-50	83.270	83.271	83.312	83.384	83.472
-40	86.222	86.189	86.219	86.299	86.406
-30	89.048	88.965	88.972	89.052	89.173
-20	91.390	91.251	91.229	91.303	91.433
-10	92.943	92.752	92.701	92.767	92.906
0	93.493	93.267	93.195	93.256	93.403
10	92.960	92.723	92.644	92.704	92.859
20	91.408	91.188	91.116	91.180	91.339
30	89.039	88.859	88.807	88.875	89.031
40	86.160	86.034	86.008	86.078	86.220
50	83.138	83.066	83.065	83.130	83.249
60	80.344	80.318	80.333	80.387	80.475
70	78.111	78.113	78.133	78.171	78.224
80	76.694	76.703	76.718	76.737	76.760
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	210°	220°	230°	240°	250°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	77.036	77.052	77.065	77.076	77.083
-70	78.527	78.564	78.595	78.619	78.635
-60	80.791	80.851	80.901	80.937	80.959
-50	83.563	83.645	83.709	83.755	83.784
-40	86.518	86.616	86.691	86.744	86.780
-30	89.302	89.414	89.499	89.558	89.602
-20	91.578	91.704	91.800	91.868	91.921
-10	93.066	93.211	93.322	93.403	93.467
0	93.581	93.746	93.878	93.976	94.052
10	93.053	93.240	93.394	93.512	93.600
20	91.542	91.745	91.919	92.054	92.152
30	89.232	89.438	89.621	89.765	89.869
40	86.404	86.596	86.771	86.912	87.014
50	83.400	83.560	83.710	83.834	83.925
60	80.583	80.699	80.809	80.904	80.975
70	78.288	78.356	78.422	78.479	78.525
80	76.785	76.812	76.838	76.861	76.881
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	260°	270°	280°	290°	300°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	77.087	77.087	77.084	77.078	77.069
-70	78.641	78.640	78.630	78.615	78.593
-60	80.969	80.967	80.954	80.932	80.902
-50	83.799	83.802	83.793	83.773	83.741
-40	86.804	86.820	86.825	86.817	86.792
-30	89.638	89.671	89.697	89.707	89.694
-20	91.971	92.022	92.067	92.094	92.093
-10	93.528	93.590	93.646	93.683	93.686
0	94.121	94.185	94.240	94.271	94.269
10	93.670	93.728	93.768	93.784	93.765
20	92.221	92.265	92.286	92.278	92.238
30	89.934	89.966	89.967	89.938	89.879
40	87.075	87.098	87.087	87.046	86.978
50	83.980	84.000	83.987	83.946	83.881
60	81.021	81.039	81.031	81.000	80.952
70	78.557	78.572	78.571	78.555	78.527
80	76.895	76.903	76.905	76.901	76.892
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	310°	320°	330°	340°	350°
Latitude	Radius (km)	Radius (km)	Radius (km)	Radius (km)	Radius (km)
-90°	3,376.492	3,376.492	3,376.492	3,376.492	3,376.492
-80	77.057	77.045	77.031	77.017	77.004
-70	78.568	78.540	78.511	78.482	78.456
-60	80.864	80.822	80.778	80.735	80.695
-50	83.698	83.645	83.587	83.529	83.474
-40	86.748	86.688	86.618	86.543	86.471
-30	89.654	89.589	89.508	89.417	89.325
-20	92.057	91.988	91.896	91.790	91.679
-10	93.649	93.576	93.475	93.356	93.230
0	94.225	94.144	94.035	93.909	93.773
10	93.708	93.618	93.503	93.372	93.233
20	92.166	92.066	91.947	91.817	91.682
30	89.794	89.689	89.570	89.445	89.319
40	86.889	86.784	86.672	86.557	86.445
50	83.800	83.707	83.608	83.510	83.416
60	80.889	80.817	80.741	80.665	80.593
70	78.490	78.446	78.398	78.349	78.303
80	76.879	76.862	76.842	76.822	76.801
90	76.249	76.249	76.249	76.249	76.249

TABLE A1-1 (cont.).--TOPOGRAPHIC DATUM OF MARS

(Gravity field in terms of fourth order and fourth degree spherical harmonics with respect to a 6.1 millibar atmospheric pressure surface.)

Longitude (West)	360°	
Latitude	Radius (km)	
-90°	3,376.492	
-80	76.991	
-70	78.432	
-60	80.661	
-50	83.425	
-40	86.404	
-30	89.237	
-20	91.569	
-10	93.102	
0	93.633	
10	93.092	
20	91.546	
30	89.197	
40	86.340	
50	83.331	
60	80.530	
70	78.262	
80	76.781	
90	76.249	

TABLE A1-2.--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
0X	63.4 ^o	287.0 ^o	3378.0	3380.106	-2.107
1N	-40.3	319.0	90.0	86.604	3.396
1X	63.6	109.6	78.2	79.717	-1.517
2N	-39.9	142.8	91.2	86.442	4.758
3N	-39.5	326.5	91.3	86.794	4.506
3X	63.8	114.8	79.7	79.649	0.051
*4N	-39.1	150.1	91.6	86.586	5.014
4X	63.8	297.9	79.0	79.964	-0.964
*5N	-38.6	325.2	90.9	87.075	3.825
5X	63.9	112.0	78.0	79.633	-1.633
6N	-38.2	140.4	90.4	87.001	-3.399
6X	64.0	286.0	77.7	79.957	-2.257
7N	-37.7	315.5	89.8	87.411	2.389
7X	64.1	100.0	78.0	79.602	-1.603
8N	-37.6	130.6	93.4	87.348	6.052
8X	64.2	273.9	77.6	79.924	-2.324
9N	-36.8	305.7	82.5	87.732	-5.232
9X	64.3	87.8	77.8	79.539	-1.739
10N	-36.3	120.8	92.5	87.900	4.600
10X	64.4	261.6	77.7	79.860	-2.160

TABLE A1-2 (cont.)--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
11N	-35.9 ⁰	295.8 ⁰	3383.7	3388.032	-4.332
11X	64.5	75.4	76.9	79.453	-2.553
12N	-35.4	110.9	94.4	88.275	6.125
12X	64.6	249.1	77.4	79.761	2.362
13N	-35.0	285.8	84.0	88.306	-4.306
13X	64.7	62.9	76.7	79.358	-2.659
14N	-34.5	100.8	97.3	88.567	8.733
14X	64.8	236.5	76.9	79.631	-2.731
15N	-34.0	275.8	88.0	88.584	-0.584
15X	64.8	50.2	76.3	79.295	-2.995
16N	-33.5	90.7	94.9	88.797	6.103
16X	64.9	223.8	76.7	79.501	-2.801
17N	-33.0	256.6	88.5	88.816	-0.316
18N	-32.5	80.5	95.9	88.946	6.954
18X	65.0	210.9	75.5	79.360	-3.860
19N	-31.9	255.4	91.8	89.114	2.686
19X	65.1	24.4	76.0	79.211	-3.211
20N	-31.4	70.3	95.3	89.077	6.223
20X	65.1	197.9	76.5	79.227	-2.727
21N	-30.9	245.2	92.5	89.344	3.155

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
21X	65.7 ⁰	11.4 ⁰	3376.6	3379.108	-2.508
22N	-30.3	60.1	93.1	89.201	3.899
22X	65.2	184.9	76.5	79.124	-2.624
23N	-29.8	235.0	93.1	89.583	3.517
24X	65.2	171.8	76.4	79.087	-2.687
24N	-29.2	49.9	92.3	89.354	2.946
24X	65.2	358.3	76.6	79.274	-2.674
25N	-28.7	224.9	93.8	89.792	4.007
25X	65.3	345.3	76.5	79.322	-2.822
26N	-28.1	39.7	92.0	89.558	2.442
26X	65.3	158.8	76.2	79.075	-2.876
27N	-27.5	214.7	93.0	89.988	3.012
27X	65.3	332.3	77.2	79.401	-2.201
28N	-27.0	29.7	92.5	89.815	2.685
28X	65.3	145.8	77.0	79.124	-2.124
29N	-26.4	204.7	93.6	90.125	3.475
29X	65.2	319.3	76.9	79.504	-2.605
30N	-25.8	19.7	91.8	90.139	1.661
30X	65.2	132.9	77.1	79.216	-2.116
31N	-25.2	194.8	95.1	90.271	4.829

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
31X	65.2 ⁰	306.5 ⁰	3377.2	3379.577	-2.377
32N	-24.6	9.9	93.3	90.489	2.811
32X	65.1	120.0	77.5	79.304	-1.804
33N	-24.0	185.0	93.0	90.436	2.564
33X	65.1	293.7	79.0	79.658	-0.659
34N	-23.4	0.1	93.6	90.852	2.748
34X	65.0	107.3	77.7	79.368	-1.668
35N	-22.8	175.3	94.3	90.659	3.641
35X	65.0	280.9	77.4	79.717	-2.317
36N	-22.1	350.4	94.9	91.238	3.662
36X	64.9	94.7	77.5	79.400	-1.900
37N	-21.5	165.5	94.6	90.997	3.603
37X	64.8	268.4	77.1	79.771	-2.671
38N	-20.9	340.8	95.1	91.597	3.503
38X	64.7	82.0	77.0	79.426	-2.426
39N	-20.3	156.0	94.1	91.416	2.684
40N	-19.6	331.2	96.1	91.964	4.136
40X	64.5	69.3	76.7	79.430	-2.730
41N	-19.0	146.4	95.8	91.948	3.852
41X	64.4	242.8	77.5	79.774	-2.274

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
42N	-18.3 ^o	321.6 ^o	3396.7	3392.309	4.391
42X	64.3	56.4	75.8	79.430	-3.630
43N	-17.6	136.9	96.6	92.541	4.059
43X	64.1	229.9	78.0	79.749	-1.749
44N	-16.9	312.1	95.5	92.637	2.863
44X	64.0	43.4	76.3	79.446	-3.166
45N	-16.2	127.2	99.3	93.118	6.182
45X	63.8	216.8	77.5	79.699	-2.199
46N	-15.5	302.4	96.8	92.919	3.881
46X	63.6	30.2	76.2	79.550	-3.350
47N	-14.8	117.6	3402.3	93.594	8.706
47X	63.4	203.6	3377.4	79.668	-2.268
48N	-14.1	292.8	96.9	93.148	3.752
48X	63.2	16.9	76.5	79.665	-3.165
49N	-13.3	107.8	3401.9	93.931	7.969
49X	63.0	190.2	3376.9	79.655	-2.755
50N	-12.5	282.9	96.8	93.351	3.449
50X	62.7	3.4	77.3	79.836	-2.536
51N	-11.7	98.0	3402.8	94.090	8.710
52N	-10.9	273.0	3398.1	93.505	4.595

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
53N	-10.1 ^o	88.1 ^o	3400.7	3394.065	6.635
54N	-9.2	263.1	3397.9	93.632	4.268
54X	61.5	336.0	79.1	80.305	-1.205
55N	-8.4	78.2	98.6	93.917	4.683
55X	61.1	149.1	78.4	80.126	-1.726
56N	-7.5	253.2	96.8	93.729	3.071
56X	60.7	322.2	78.6	80.614	-2.014
57N	-6.6	68.2	97.3	93.711	3.589
57X	60.3	135.3	78.8	80.445	-1.645
58N	-5.7	243.3	96.3	93.798	2.502
58X	60.0	308.3	78.7	80.900	-2.200
59N	-4.7	58.4	97.6	93.523	4.077
59X	59.5	121.4	80.0	80.778	-0.778
60N	-3.9	233.2	96.8	93.815	2.985
60X	58.9	294.1	78.9	81.287	-2.387
61N	-2.9	48.3	96.6	93.377	3.222
61X	58.4	107.2	79.6	81.164	-1.564
62N	-1.8	223.4	93.2	93.774	-0.754
63N	-0.8	38.6	94.3	93.318	0.982
64N	0.3	213.8	93.5	93.646	-0.147

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
64X	56.7 ^o	266.4 ^o	3379.4	3381.975	-2.575
65N	1.5	29.0	93.9	93.304	0.595
65X	56.1	79.5	81.1	81.761	-0.661
66X	55.4	252.6	79.7	82.307	-2.608
67N	3.8	19.7	93.9	93.303	0.596
67X	54.6	65.7	81.4	82.081	-0.681
68N	5.1	195.1	92.2	93.173	-0.973
68X	53.9	238.9	79.4	82.642	-3.242
69N	6.4	10.5	93.6	93.265	0.335
69X	53.0	52.0	79.7	82.426	-2.726
70N	7.7	186.0	92.0	92.884	-0.884
70X	52.1	225.1	80.3	83.007	-2.707
71N	9.1	1.6	93.3	93.161	0.139
71X	51.2	38.3	79.6	82.870	-3.270
72N	10.7	177.3	91.3	92.573	-1.273
72X	50.1	211.4	81.6	83.393	-1.793
73N	12.3	353.1	93.6	92.917	0.683
73X	48.9	24.4	81.5	83.530	-2.030
74N	14.1	168.9	91.2	92.223	-1.023
74X	47.6	197.4	82.0	83.920	-1.921

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
75N	16.0 ⁰	345.0 ⁰	3392.8	3392.483	0.317
75X	46.1	10.3	82.2	84.421	-2.221
76N	18.2	161.1	89.7	91.724	-2.024
76X	44.4	183.0	83.4	84.722	-1.322
77N	20.8	337.6	93.1	91.686	1.414
78N	24.1	154.7	88.5	90.681	-2.181
78X	39.4	167.2	84.4	86.237	-1.838
79N	29.4	333.4	90.3	89.688	0.611
352N	33.9	323.3	91.3	88.562	2.738
*354N	44.2	312.5	86.8	85.568	1.232
354X	-3.3	321.9	3400.1	94.059	6.041
358N	57.1	293.1	3381.7	81.803	-0.103
358X	-15.7	305.5	98.5	92.876	5.624
360N	62.2	284.0	79.1	80.427	-1.327
*360X	-20.5	296.6	94.1	91.994	2.106
362N	66.8	275.3	78.1	79.288	-1.188
*362X	-24.9	287.5	92.1	91.005	1.095
366N	75.0	260.5	72.2	77.610	-5.410
*366X	-32.3	268.7	90.0	89.045	0.955
368N	78.7	255.7	75.9	77.051	-1.151

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
*368X	-35.6 ⁰	259.0 ⁰	3391.6	3388.090	3.510
372X	-41.7	239.3	88.5	86.236	2.264
*374N	86.0	296.5	76.6	76.379	0.221
376N	84.7	326.6	76.8	76.439	0.360
376X	-47.0	219.3	88.5	84.528	3.972
378N	82.1	335.5	78.1	76.625	1.475
378X	-49.4	209.3	88.7	83.733	4.967
382N	76.4	330.5	80.6	77.297	3.303
382X	-54.0	189.1	86.7	82.245	4.455
386N	70.5	317.5	79.7	78.357	1.343
386X	-58.2	168.8	86.3	81.016	5.284
388N	67.7	310.1	78.8	78.980	-0.180
388X	-60.1	158.4	85.6	80.518	5.082
390N	64.8	302.3	79.3	79.695	-0.395
390X	-62.0	147.9	82.4	80.055	2.345
392N	61.9	294.3	80.2	80.470	-0.270
392X	-63.8	137.1	84.0	79.645	4.355
*394N	59.1	286.1	80.5	81.265	-0.765
394X	-65.6	126.0	83.4	79.255	4.145
398N	53.5	269.1	82.0	82.928	-0.929

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
400N	51.2 ^o	260.2 ^o	3384.4	3383.611	0.788
400X	-71.0	89.8	82.0	78.192	3.808
402N	48.4	251.4	82.9	84.430	-1.530
402X	-72.5	76.9	81.3	77.932	3.368
404N	45.2	242.7	84.1	85.346	-1.246
404X	-73.5	64.3	80.3	77.771	2.529
406N	42.4	233.7	85.7	86.097	-0.397
406X	-74.8	50.3	80.9	77.578	3.322
408N	39.5	224.8	86.5	86.833	-0.333
*408X	-76.1	35.6	81.5	77.405	4.095
410N	36.6	215.9	86.5	87.521	-1.022
*410X	-77.1	20.2	80.9	77.291	3.609
414N	30.9	198.2	92.1	88.761	3.339
*414X	-78.8	346.6	83.9	77.135	6.764
416N	27.8	189.5	90.4	89.430	0.970
416X	-79.3	329.5	79.4	77.106	2.294
*418N	24.9	180.9	88.5	90.067	-1.567
*418X	-79.6	311.0	79.8	77.099	2.701
420N	22.0	172.4	90.4	90.747	-0.348
420X	-79.7	292.3	79.9	77.109	2.791

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
422N	19.1 ^o	164.0 ^o	3391.1	3391.479	-0.379
*422X	-79.6	273.3	80.1	77.131	2.969
424N	16.1	155.6	91.0	92.270	-1.270
*424X	-79.2	255.1	80.0	77.177	2.823
*428N	10.1	139.2	94.0	93.800	0.199
*428X	-77.7	221.0	81.4	77.322	4.078
*430N	7.1	131.0	98.4	94.428	3.971
*430X	-76.6	204.7	81.9	77.430	4.470
432N	4.0	122.8	3403.5	94.884	8.616
*432X	-75.4	189.6	3380.6	77.556	3.044
434N	0.8	114.5	3417.1	95.109	21.991
434X	-74.0	175.1	3383.8	77.723	6.077
436N	-2.4	106.2	3403.3	95.067	8.232
438N	-5.8	97.9	7.1	94.756	12.344
*438X	-70.8	147.0	3381.9	78.202	3.698
442N	-13.1	81.4	3401.3	93.440	7.860
*442X	-66.9	120.1	3382.5	78.981	3.519
446N	-21.4	65.4	99.1	91.451	7.649
448N	-26.4	57.9	98.2	90.159	8.041
448X	-58.7	80.0	84.2	81.015	3.185

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
*450N	-32.6 ^o	51.2 ^o	3392.4	3388.469	3.931
638N	-56.5	337.5	86.4	81.678	4.722
640N	-58.8	321.4	84.9	81.132	3.768
642N	-60.1	306.8	84.6	80.851	3.749
644N	-61.6	292.9	83.6	80.511	3.089
646N	-61.9	279.4	83.2	80.465	2.735
648N	-62.6	266.3	84.4	80.303	4.097
648X	-34.2	314.8	91.8	88.447	3.353
652N	-63.5	240.9	84.3	80.055	4.244
652X	-30.2	297.7	88.1	89.645	-1.545
654N	-63.9	228.6	83.6	79.920	3.680
654X	-28.3	289.1	90.5	90.157	0.343
656N	-64.2	216.5	83.7	79.795	3.905
660N	-64.7	193.2	84.4	79.554	4.846
660X	-23.2	263.2	96.6	91.312	5.288
662N	-64.9	181.7	84.5	79.453	5.047
*662X	-21.6	254.4	95.5	91.617	3.883
666N	-65.3	159.2	82.2	79.300	2.900
666X	-18.5	236.8	96.2	92.133	4.067
668N	-65.4	147.9	82.9	79.273	3.627

TABLE A1-2 (cont.).--RADIO OCCULTATION DATA FROM MARINER MARS 9 MISSION

(N--Entry, X--Exit, *--Noisy data. Points with bad or missing data were excluded.)

Revolution	Latitude	Longitude (West)	Radius (observed) (km)	Radius at 6.1 mb datum (km)	Height at 6.1 mb datum (km)
670N	-65.5 ⁰	136.6 ⁰	3383.4	3379.260	4.139
*670X	-15.7	218.7	94.2	92.446	1.754
672N	-65.7	125.3	82.0	79.234	2.766
*672X	-14.3	209.4	95.3	92.528	2.772
674N	-65.8	113.9	82.9	79.231	3.669
674X	-12.9	200.0	93.9	92.573	1.327
676N	-65.9	102.4	83.9	79.223	4.676
676X	-11.5	190.6	93.1	92.613	0.487
678N	-66.0	90.9	81.8	79.207	2.593
680N	-66.1	79.3	82.6	79.184	3.416
682N	-66.2	67.7	81.7	79.155	2.545
690N	-66.4	21.8	84.2	79.114	5.086
694N	-66.5	359.4	82.6	79.135	3.465
694X	0.0	104.9	2.5	95.122	7.378
696N	-66.6	348.4	82.9	79.144	3.756
696X	1.6	95.7	3401.0	94.969	6.031

APPENDIX B

ASSOCIATED LEGENDRE FUNCTION $P_{nm}(\sin \phi)$

$$P_{00} = P_0 = 1$$

$$P_{10} = P_1 = \sin \phi$$

$$P_{11} = \cos \phi$$

$$P_{20} = P_2 = \frac{1}{2} (3 \sin^2 \phi - 1)$$

$$P_{21} = 3 \cos \phi \sin \phi$$

$$P_{22} = 3 \cos^2 \phi$$

$$P_{30} = P_3 = \frac{1}{2} (5 \sin^3 \phi - 3 \sin \phi)$$

$$P_{31} = \cos \phi \left(\frac{15}{2} \sin^2 \phi - \frac{3}{2} \right)$$

$$P_{32} = 15 \cos^2 \phi \sin \phi$$

$$P_{33} = 15 \cos^3 \phi$$

$$P_{40} = P_4 = \frac{1}{8} (35 \sin^4 \phi - 30 \sin^2 \phi + 3)$$

$$P_{41} = \cos \phi (35 \sin^3 \phi - 15 \sin \phi) / 2$$

$$P_{42} = \cos^2 \phi (105 \sin^2 \phi - 15) / 2$$

$$P_{43} = 105 \cos^3 \phi \sin \phi$$

$$P_{44} = 105 \cos^4 \phi$$

SELECTED BIBLIOGRAPHY

- ANDERSON, J. D., EFRON, L., and WONG, S. K. (1969) Celestial mechanics, in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 127-134.
- BARTH, C. A., FASTIA, W. G., HORD, C. W., PEARCE, J. B., KELLY, K. K., STEWART, A. I., THOMAS, G. E., ANDERSON, G. P., and RAPER, O. F., (1969) Ultraviolet spectroscopy in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 97-104.
- BARTH, CHARLES A., and HORD, CHARLES W. (1971) Mariner ultraviolet spectrometer: Topography and polar cap: Science, vol. 173, no. 3993, pp. 197-201.
- BARTH, CHARLES A., HORD, CHARLES W., STEWART, A. IAN, and LANE, ARTHUR L. (1972) Mariner 9 ultraviolet spectrometer experiment: Initial results: Science, vol. 175, no. 4019, pp. 309-312.
- BARTH, C. A., STEWART, A. I., HORD, C. W., and LANE, A. L. (1972) Mariner 9 ultraviolet spectrometer experiment: Mars airglow spectroscopy and variations in Lyman Alpha: Icarus, vol. 17, no. 2, pp. 457-468.
- BATSON, R. M. (1973a) Cartographic products from the Mariner 9 mission: Jour. of Geophys. Research, vol. 78, no. 20, pp. 4424-4435.
- ____ (1973b) Television cartography: U.S. Geol. Survey Interagency Report: Astrogeology 58, 34 p.
- BATSON, R. M., and DWORNIK, S. E. (1974 Mapping the planet Mars by Mariner 9: U.S. Geol. Survey Interagency Report: Astrogeology 61, Presented at the Seventh Internat. Conf. of the Internat. Cartography Assoc., Madrid, Spain, 36 p.
- BLASIUS, KARL R. (1973) Study of Martian topography by analytical photogrammetry: Jour. of Geophys. Research, vol. 78, no. 20, pp. 4411-4423.
- BOMFORD, G. (1962) Geodesy: second edition, Oxford Univ. Press, Amen House, London E.D.A., 561 p.
- BRADBURY, RAY, CLARKE, ARTHUR C., MURRAY, BRUCE, SAGAN, CARL, and SULLIVAN, WALTER (1972) Mars and the mind of man: Harper & Row Publishers, 143 p.

- BROWN, DUANE C., DAVIS, RONALD G., and JOHNSON, FREDERICK C. (no d.)
The practical and rigorous adjustment of large photogrammetric nets
in Final report-research in mathematical targeting: D. Brown
Assoc., Inc., prepared for Rome Air Devel. Center, Griffiss Air
Force Base, N.Y., contr. no. AF30(602)-3007, 157 p.
- CAIN, D. L., KLIORÉ, A. J., SEIDEL, B. C., and SYKES, M. J. (1972) The
shape of Mars from the Mariner 9 occultations: Icarus, vol. 17,
no. 2, pp. 517-524.
- CAIN, D. L., KLIORÉ, A. J., SEIDEL, B. L., SYKES, M. J., and
WOICESHYN, P. M. (1973) Approximations to the mean surface of Mars
and Mars atmosphere using Mariner 9 occultations: Jour. of Geophys.
Research, vol. 78, no. 20, pp. 4352-4354.
- CARR, M. H. (1974) Giant volcanoes of Mars in Mars as viewed by
Mariner 9: Natl. Aeron. and Space Admin., NASA SP-329, p. 5.
- CHASE, S. C., JR., HATZENBELER, H., KIEFFER, H. H., MINER, E.,
MUNCH, G., and NEUGEBAUER, G. (1972) Infrared radiometry experiment
on Mariner 9: Science, vol. 175, no. 4019, pp. 308-309.
- CHASE, S., JR., MINER, E., MUNCH, G., and NEUGEBAUER, G. (1970) Infrared
radiometry experiment for Mariner Mars 1971: Icarus, vol. 12,
no. 1, pp. 46-47.
- CHRISTENSEN, EDWARD J. (1975) Martian topography derived from
occultation, radar, spectral and optical measurements: Jour. of
Geophys. Research, vol. 80, no. 20, pp. 2909-2913.
- CONRATH, B., CURRAN, R., HANEL, R., KUNDE, V., MAGUIRE, W., PEARL, J.,
PIRRAGLIA, J., and WALKER, J. (1973) Atmospheric and surface
properties of Mars obtained by infrared spectroscopy on Mariner 9:
Jour. of Geophys. Research, vol. 78, no. 20, pp. 4267-4278.
- CROSBY, DENNIS (1974) Mariner Mars 1971 television picture catalog:
Experiment design and picture data: Jet Propulsion Laboratory,
Tech. Memo. 33-585, vol. 1, addendum 1, prepared for Natl. Aeron.
and Space Admin., 49 p.
- CUNNINGHAM, N. W., and SCHURMEIER, H. M. (1969) Introduction in Mariner
Mars 1969: A preliminary report: Natl. Aeron. and Space Admin.,
NASA SP-225, pp. 1-36.
- CUTTS, JAMES A. (1974) Mariner Mars 1971 television picture catalog:
Experiment design and picture data: Jet Propulsion Laboratory,
Tech. Memo. 33-585, vol. 1, prepared for Natl. Aeron. and Space
Admin., 422 p.

- CUTTS, JAMES A., SODERBLOM, LAURENCE A., SHARP, ROBERT P., SMITH, BRADFORD A., and MURRAY, BRUCE C. (1971) The surface of Mars: Light and dark markings: Jour. of Geophys. Research, vol. 76, no. 2, pp. 343-356.
- DAVIES, MERTON E. (1972) Coordinates of features on the Mariner 6 and 7 pictures of Mars: Icarus, vol. 17, no. 1, pp. 116-167.
- DAVIES, MERTON E., and ARTHUR, DAVID W. G. (1973) Martian surface coordinates: Jour. of Geophys. Research, vol. 78, no. 20, pp. 4435-4404.
- DAVIS, RONALD G., JOHNSON, FREDERICK C., and RIDING, THOMAS J. (no d.) Description of computer programs for the rigorous analytical adjustment of aerial photogrammetric nets on the ACIC IBM 7094-11 computer in Final report, item 4, vol. 1: D. Brown Assoc., Inc., prepared for Rome Air Devel. Center, Griffiss Air Force Base, N.Y., Contr. no. AF 30-602-3809, 148 p.
- DE VAUCOULEURS, GERARD (1965) Charting the Martian surface: Sky and Telescope, vol. 30, no. 4, p. 196.
- DE VAUCOULEURS, GERARD, DAVIES, MERTON E., and STURMS, FRANCIS M., JR. (1973) Mariner 9 aerographic coordinate system: Jour. of Geophys. Research, vol. 78, no. 20, pp. 4395-4404.
- DOLLFUS, AUDOUIN (1972) New optical measurements of planetary diameters part IV: Planet Mars: Icarus, vol. 17, no. 2, pp. 525-539.
- DOWNS, G. S., GOLDSTEIN, R. M., GREEN, R. R., and MORRIS, G. A. (1971) Mars radar observations: A preliminary report: Science, vol. 174, no. 4016, pp. 1324-1327.
- DOWNS, G. S., GOLDSTEIN, R. M., GREEN, R. R., MORRIS, G. A., and REICHLEY, P. E. (1973) Martian topography and surface properties as seen by radar: The 1971 opposition: Icarus, vol. 18, no. 1, pp. 8-21.
- DOWNS, G. S., REICHLEY, P. E., and GREEN, R. R. (1975) Radar measurements of Martian topography and surface properties: The 1971 and 1973 oppositions: Icarus, vol. 26, no. 3, pp. 273-312.
- FERRARI, A. J., and CHRISTENSEN, E. J. (1973) Mars gravity derived from long period motion of Mariner 9: NASA Mariner Mars 9 final report-science results, JPL Tech. Report 32-1550, vol. 4, pp. 401-406.
- FIRSOFF, V. A. (1969) The world of Mars: Oliver & Boyd, Edinburgh, Ltd., 128 p.

- GLASSTONE, SAMUEL (1968) The book of Mars: Natl. Aeron. and Space Admin., NASA SP-179, 315 p.
- GOLDSTEIN, R. M., and GILLMORE, W. F. (1963) Radar observations on Mars: Science, vol. 141, no. 3386, pp. 1171-1172.
- GOLDSTONE, R. M., MELBOURNE, W. G., MORRIS, G. A., DOWNS, G. S., and O'HANDLEY, D. A. (1970) Preliminary radar results of Mars: Radio Science, vol. 5, no. 2, pp. 475-478.
- HANEL, R., CONRATH, B., HOVIS, W., KUNDE, V., LOWMAN, P., MAGUIRE, W., PEARL, J., PIRRAGLIA, J., PRABHKARA, C., SCHLACHMAN, B., LEVIN, G., STRAAT, P., and BURKE, T. (1972a) Investigation of the Martian environment by infrared spectroscopy on Mariner 9: Icarus, vol. 17, no. 2, pp. 423-442.
- HANEL, R. A., CONRATH, B. J., HOVIS, W. A., LOWMAN, P. D., PEARL, J. C., PRABHAKARA, C., and SCHLACHMAN, B. (1972b) Infrared spectroscopy experiment on the Mariner 9 mission: Preliminary results: Science, vol. 175, no. 4019, pp. 305-308.
- HANEL, R. A., CONRATH, B. J., HOVIS, W. A., KUNDE, V., LOWMAN, P. D., PRABHAKARA, C., and SCHLACHMAN, B. (1970) Infrared spectroscopy experiment for Mariner Mars 1971: Icarus, vol. 12, no. 1, pp. 48-62.
- HARTMANN, WILLIAM K., and RAPER, ODELL (1974) The new Mars: The discoveries of Mariner 9: Natl. Aeron. and Space Admin., NASA SP-179, 315 p.
- HEISKANEN, W. A., MEINESZ, F. A. VENING (1958) The Earth and its gravity: McGraw-Hill Book co., Inc., 470 p.
- HEISKANEN, WEIKKO A., and MORITZ, HELMUT (1967) Physical geodesy: W. H. Freeman and Co., San Francisco and London, 364 p.
- HERR, KENNETH C., HORN, DIETER, MC AFEE, JOHN M., and PIMENTEL, GEORGE C. (1970) Martian topography from the Mariner 6 and 7 infrared spectra: Astron. Jour., vol. 75, no. 8, pp. 883-894.
- HERR, K. C., and PIMENTEL, G. C. (1969) Infrared spectroscopy in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 83-96.
- HORD, CHARLES W. (1972) Mariner 6 and 7 ultraviolet spectrometer experiment: Photometry and topography of Mars: Icarus, vol. 16, no. 2, pp. 253-280.
- HORD, C. W., BARTH, C. A., and PEARCE, J. B. (1970) Ultraviolet spectroscopy experiment for Mariner Mars 1971: Icarus, vol. 12, no. 1, pp. 63-77.

- HORD, C. W., BARTH, C. A., STEWART, A. I., and LANE, A. L. (1972) Mariner 9 ultraviolet spectrometer experiment: Photometry and topography of Mars: *Icarus*, vol. 17, no. 2, pp. 443-456.
- HOSMER, GEORGE L. (1946) *Geodesy*: John Wiley and Sons, Inc., N.Y., 461 p.
- HOTINE, MARTIN (1969) *Mathematical geodesy*: U.S. Dept. of Commerce, Environ. Sci. Service Admin., 416 p.
- HUTTON, R. E. (1975) *Surface model of Mars*: Natl. Aeron. and Space Admin., NASA SP-8020, 79 p.
- INGE, J. L., and BRIDGES, P. M. (1975) Applied photo-interpretation for airbrush cartography: Proc. Amer. Soc. Photogramm./Amer. Cong. Surveying and Mapping Fall Convention, Phoenix, Arizona, pp. 244-265.
- JAFAR, ARKANI HAMED (1975) Geophysical implications of the Martian gravity field: *Icarus*, vol. 26, no. 3, pp. 313-320.
- JET PROPULSION LABORATORY (1973a) Project development through launch and trajectory correction maneuver in the Mariner Mars 1971 project final report: Natl. Aeron. and Space Admin. Tech. Rept. 32-1550, vol. 1, 76 p.
- ____ (1973b) The many faces of Mars: 53 p.
- JORDAN, J. F., HYLKEMA, R. K., and REINBOLD, S. J. (1973) Determination of normal points for the relativity test of the celestial mechanics experiment: NASA Mariner Mars 1971 project final report-science results: JPL Tech. Rept. 32-1550, vol. 4, pp. 415-422.
- JORDAN, J. F., and LORELL, J. (1975) Mariner 9: An instrument of dynamical science: *Icarus*, vol. 25, no. 1, pp. 146-165.
- KIEFFER, H. H., CHASE, S. C., MINER, E., MUNCH, B., and NEUGEBAUER, G. (1973) Preliminary report on infrared radiometric measurements from Mariner 9: *Jour. of Geophys. Research*, vol. 78, no. 20, pp. 4291-4312.
- KLIORE, A. J., CAIN, D. L., FJELDBO, G., and SEIDEL, B. L. (1972a) Mariner 9 S-band Martian occultation experiments: Initial results on the atmosphere and topography of Mars: *Science*, vol. 175, no. 4019, pp. 313-317.
- KLIORE, ARBYDAS J., CAIN, DAN L., FJELDBO, GUNNAR, SEIDEL, BORIS L., SYKES, MICHAEL J., and RASOOL, S. I. (1972b) The atmosphere of Mars from Mariner 9 radio occultation measurements: *Icarus*, vol. 17, no. 2, pp. 484-516.

- KLIORE, A., CAIN, D. L., SEIDEL, B. L., and FJELDBO, G. (1970) S-band occultation experiment for Mariner Mars 1971: *Icarus*, vol. 12, no. 1, pp. 82-90.
- KLIORE, A., FJELDBO, G., SEIDEL, B., and RASOOL, S. I. (1969) S-band occultation in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 111-126.
- KLIORE, A. J., FJELDBO, G., SEIDEL, B. L., SYKES, M. J., and WOICESHYN, P. M. (1973) S-band radio occultation measurements of the atmosphere and topography of Mars with Mariner 9: Extended mission coverage of polar and intermediate latitudes: *Jour. of Geophys. Research*, vol. 78, no. 20, pp. 4331-4351.
- KOSKELA, P. E. (1973) Mariner Mars 1971 television picture catalog: Sequence design and picture coverage: Jet Propulsion Laboratory Tech. Memo. 33-585, vol. 2, addendum 1, prepared for Natl. Aeron. and Space Admin., 97 p.
- KOSKELA, P. E., HELTON, M. R., SEELEY, L. N., and ZAWOCKI, S. J. (1972) Mariner Mars 1971 television picture catalog: Sequence design and picture coverage: Jet Propulsion Laboratory Tech. Memo. 33-585, vol. 2, prepared for Natl. Aeron. and Space Admin., 552 p.
- LEIGHTON, R. B., HOROWITZ, N. H., MURRAY, B. C., SHARP, R. P., HERRIMAN, A. G., YOUNG, A. T., SMITH, B. A., DAVIES, M. E., and LEOVY, C. B. (1969) Television observations from Mariners 6 and 7 in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 37-82.
- LEIGHTON, R. B., and MURRAY, BRUCE C. (1971) The surface of Mars: *Jour. of Geophys. Research*, vol. 76, no. 2, pp. 293-296.
- LEVINTHAL, E. C., GREEN, W. B., CUTTS, J. A., JAHELKA, E. D., JOHANSEN, R. A., SANDER, M. J., SEIDMAN, J. B., YOUNG, A. T., and SODERBLOM, L. A. (1973) Mariner 9 image processing and products: *Icarus*, vol. 18, no. 1, pp. 75-101.
- LEOVY, C. B., BRIGGS, G. A., YOUNG, A. T., SMITH, B. A., POLLACK, J. B., SHIPLEY, E. N., and WILDEY, R. L. (1972) The Martian atmosphere: Mariner 9 television experiment progress report: *Icarus*, vol. 17, no. 2, pp. 373-393.
- LORELL, J., ANDERSON, J. D., and SHAPIRO, I. I. (1970) Celestial mechanics experiment for Mariner Mars 1971: *Icarus*, vol. 12, no. 1, pp. 78-81.

- LORELL, J., BORN, G. H., JORDAN, J. F., LAING, P. A., MARTIN, W. L., SJOGREN, W. L., SHAPIRO, I. I., REASENBERG, R. D., and SLATER, G. L. (1972) Mariner 9 celestial mechanics experiment: Gravity field and pole direction of Mars: *Science*, vol. 175, no. 4019, pp. 317-320.
- LORELL, J., and SHAPIRO, I. I. (1973) The Mariner 9 celestial mechanics experiment: A status report: *Jour. of Geophys. Research*, vol. 78, no. 20, pp. 4327-4329.
- MASURSKY, HAROLD (1973) An overview of geologic results from Mariner 9: *Jour. of Geophys. Research*, vol. 78, no. 20, pp. 4009-4030.
- MASURSKY, HAROLD, BATSON, R. M., BORGESON, W., CARR, M., MC CAULEY, J., MILTON, D., WILDEY, R., WILHELMS, D., MURRAY, B., HOROWITZ, N., LEIGHTON, R., SHARP, R., THOMPSON, W., BRIGGS, G., CHANDEYSSON, P., SHIPLEY, E., SAGAN, C., POLLACK, J., LEDERBERG, J., LEVINTHAL, E., HARTMANN, W., MC CORD, T., SMITH, B., DAVIES, M., DE VAUCOULEURS, G., and LEOVY, C. (1970) Television experiment for Mariner Mars 1971: *Icarus*, vol. 12, no. 1, pp. 10-45.
- MASURSKY, HAROLD, BATSON, R. M., MC CAULEY, J. F., SODERBLUM, L. A., WILDEY, R. L., CARR, M. H., MILTON, D. J., WILHELMS, D. E., SMITH, B. A., KIRBY, T. B., ROBINSON, J. C., LEOVY, C. B., BRIGGS, G. A., DUXBURY, T. C., ACTION, C. H., JR., MURRAY, B. C., CUTTS, J. A., SHARP, R. P., SMITH, SUSAN, LEIGHTON, R. B., SAGAN, C., VEVERKA, J., NOLAND, M., LEDERBERG, J., LEVINTHAL, E., POLLACK, J. B., MOORE, J. T., JR., HARTMANN, W. K., SHIPLEY, E. M., DE VAUCOULEURS, G., AND DAVIES, M. E. (1972) Mariner 9 reconnaissance of Mars and its satellites: Preliminary results: *Science*, vol. 175, no. 4019, pp. 294-305.
- MASURSKY, HAROLD, SMITH, B. A. (1974) Introduction in Mars as viewed by Mariner 9: *Natl. Aeron. and Space Admin., NASA SP-329*, pp. 1-3.
- MC CAULEY, J. F., CARR, M. H., CUTTS, J. A., HARTMANN, W. K., MASURSKY, HAROLD, MILTON, D. J., SHARP, R. P., and WILHELMS, D. E. (1972) Preliminary Mariner 9 report on the geology of Mars: *Icarus*, vol. 17, no. 2, pp. 289-327.
- MC CAULEY, J. F., HIPSHER, H. F., and STEINBACHER, R. H. (1974) Preface in Mars as viewed by Mariner 9: *Natl. Aeron. and Space Admin., NASA SP-329*.
- MOORE, PATRICK, and CROSS, CHARLES A. (1973) *Mars*, Crown Publishers Inc., N.Y., 48 p.

- MURRAY, BRUCE C., SODERBLOM, LAURENCE A., CUTTS, JAMES A., SHARP, ROBERT P., MILTON, DANIEL J., and LEIGHTON, ROBERT B. (1972) Geological frame work of the south polar region of Mars: *Icarus*, vol. 17, no. 2, pp. 328-345.
- MURRAY, BRUCE C., SODERBLOM, LAURENCE A., SHARP, ROBERT P., and CUTTS, JAMES A. (1971) The surface of Mars cratered terrains: *Jour. of Geophys. Research*, vol. 76, no. 2, pp. 313-330.
- NATIONAL SPACE SCIENCE DATA CENTER (1971) Mariner 6 and 7 photographic data: Data users note: NSSDC 71-09, ID no. 69-014A-01 and 69-030A-01, 309 p.
- NEUGEBAUER, G., MUNCH, G., CHASE, S. C., JR., HATZENBELER, H., MINER, E., and SCHOFIELD, D. (1969) Infrared radiometry in Mariner Mars 1969: A preliminary report, Natl. Aeron. and Space Admin., NASA SP-225, pp. 105-109.
- OTTICO MECCANICA ITALIANA S.P.A. (1964) The AS-11A photogrammetric analytical plotter; 81 Via Della Vasca Navale, Rome, Italy, 108 p.
- ____ (1966) Analytical plotter-model AP/C OMI 66-An, 18x7; 81 Via Della Vasca Navale, Rome, Italy, 77 p.
- PARKINSON, T. D., and HUNTER, D. M. (1972) Martian dust storm: Its depth on November 25, 1971: *Science*, vol. 175, no. 4019, pp. 323.
- PETTENGILL, G. (1964) Some current programs at Arecibo: *Sky and Telescope*, vol. 28, no. 1 and no. 2.
- PETTENGILL, G. H., CHANDLER, J. F., CAMPBELL, D. B., DYCE, R. B., and WALLACE, D. M. (1974) Martian surface properties from recent radar observations: *Bull. Amer. Astron. Soc.*, vol. 6, no. 3, part 2, p. 372.
- PETTENGILL, G. H., COUNSELMAN, C. C., RAINVILLE, L. P., and SHAPIRO, I. I. (1969) Radar measurements of Martian topography: *Astron. Jour.*, vol. 74, no. 3, pp. 461-482.
- PETTENGILL, G. H., ROGERS, A. E. E., and SHAPIRO, I. I. (1971) Martian craters and a scarp as seen by radar: *Science*, vol. 174, no. 4016, pp. 1321-1324.
- PETTENGILL, G. H., and SHAPIRO, I. I. (1973) Topography and radar scattering properties of Mars: *Icarus*, vol. 18, no. 1, pp. 22-28.

- POLLACK, J. B., VEVERKA, J., NOLAND, M., SAGAN, C., DUXBURY, T. C., ACTION, C. H., JR., BORN, G. H., HARTMANN, W. K., and SMITH, B. (1973) Mariner 9 television observations of Phobos and Deimos 2: Jour. of Geophys. Research, vol. 78, no. 20, pp. 4313-4326.
- POLLACK, J. B., VEVERKA, J., NOLAND, M., SAGAN, CARL, HARTMANN, W. K., DUXBURY, T. C., BORN, G. H., MILTON, D. J., and SMITH, B. A. (1972) MARINER 9 television observations of Phobos and Deimos: Icarus, vol. 17, no. 2, pp. 393-407.
- RICHARDUS, PETER, and ADLER, RON K. (1972) Map projections: North Holland Publishing Co., Amsterdam, 174 p.
- ROGERS, A. E. E., ASH, M. E., COUNSELMAN, C. C., SHAPIRO, I. I., and PETTENGILL, G. H. (1970) Radar measurements of the surface topography and roughness: Radio Sci., vol. 5, no. 2, pp. 465-673.
- RUNCORN, S. K. (1973) On the implications of the shape of Mars: Icarus, vol. 18, no. 1, pp. 109-112.
- SAGAN, CARL, VEVERKA, JOSEPH, FOX, PAUL, DUBISCH, RUSSELL, LEDERBERG, JOSHUA, LEVINTHAL, ELLIOT, QNAN, LYNN, POLLACK, JAMES B., and SMITH, BRADFORD A. (1972) Variable features on Mars: Preliminary Mariner 9 television results: Icarus, vol. 17, no. 2, pp. 346-372.
- SEIDMAN, JOEL B., GREEN, WILLIAM B., JEPSEN, PAUL, RUIZ, REUBEN, M., and THORPE, THOMAS E. (1973) A user's guide to the Mariner 9 television reduced data record: Jet Propulsion Laboratory Tech. Memo. 33-628, prepared for Natl. Aeron. and Space Admin., 62 p.
- SHARP, ROBERT P., MURRAY, BRUCE C., LEIGHTON, ROBERT B., SODERBLOM, LAURENCE A., and CUTTS, JAMES A. (1971a) The surface of Mars-south polar cap: Jour. of Geophys. Research, vol. 76, no. 2, pp. 357-368.
- SHARP, ROBERT P., SODERBLOM, LAURENCE A., MURRAY, BRUCE C., and CUTTS, JAMES A. (1971b) The surface of Mars-uncratered terrains: Jour. of Geophys. Research, vol. 76, no. 2, pp. 331-342.
- SJOGREN, W. L., LORELL, J., REINBOLD, S. J., and WIMBERLY, R. N. (1973) Mars gravity field via the short data arcs: Jour. of Geophys. Research, vol. 78, no. 20.
- SNYDER, L. M. (1971) Mariner 9 TV subsystem calibration report: Jet Propulsion Laboratory 610-202, 133 p.
- STANDISH, E. MYLES, JR. (1973) The figure of Mars and its effect on radar-ranging: Astron. & Astrophys., vol. 26, pp. 463-466.

- STEINBACHER, R. H., and GUNTER, S. I. (1970) Introduction in the Mariner Mars 1971 experiments: Icarus, vol. 12, no. 1, pp. 3-9.
- STEINBACHER, R. H., and HAYNES, N. R. (1973) Mariner 9 mission profile and project history: Icarus, vol. 18, no. 1, pp. 64-74.
- STEINBACHER, R. H., KLIORE, A., LORELL, J., HIPSHER, H., BARTH, C. A., MASURSKY, HAROLD, MUNCH, G., PEARL, J., and SMITH, B. (1972) Mariner 9 science experiments: Preliminary results: Science, vol. 175, no. 4019, pp. 293-294.
- STEWART, A. I., BARTH, C. A., HORD, C. W., and LANE, A. I. (1972) Mariner 9 ultraviolet spectrometer experiment: Structure of Mars' upper atmosphere: Icarus, vol. 17, no. 2, pp. 469-474.
- THE U.S. GEOLOGICAL SURVEY MARS MAPPING GROUP (1975) Atlas of Mars: Topographic series: U.S. Geol. Survey Interagency Report: Astrogeology 68.
- THOMAS, PAUL D. (1964) Conformal projections in geodesy and cartography: U.S. Dept. of Commerce, Coast and Geodetic Survey, Spec. Publ. no. 251, 142 p.
- THORPE, T. E. (1972) Mariner 9 television imaging performance evaluation (Mariner 9 subsystem calibration report): Jet Propulsion Laboratory 610-237, vol. 2, 74 p.
- ____ (1973) Verification of performance of the Mariner 9 television cameras: NASA Mariner Mars 9 final report-science results, JPL Tech. Rept. 32-1550, vol. 4, pp. 499-510.
- UOTILA, U. A. (1962a) Harmonic analysis of world-wide gravity material: Suomalainen Tiedeakatemia, Helsinki, 24 p.
- ____ (1962b) Corrections to gravity formula from direct observations and anomalies expressed in lower degree spherical harmonics: The Ohio State Univ., Tech. Paper no. 1058-9, contr. no. AF19(604)-6201, 18 p.
- WATTS, RAYMOND N., JR. (1965) Mariner 4 completes Mars mission: Sky and Telescope, vol. 30, no. 4, p. 136.
- WELLS, R. A. (1972) Analysis of large-scale Martian topography variations: Geophys. Jour. of Research Astro. Soc., vol. 27, p. 101-133.
- WHITEHEAD, A. BRUCE (1973) The photomosaic globe of Mars: Internat. Colloq. on Mars at the Jet Propulsion Laboratory, Pasadena, California.

- WONG, KAM W. (1968) Photogrammetric quality of television pictures:
Univ. of Illinois, Civil Engineering Studies, photogrammetry
series, no. 17, 257 p.
- WU, S. S. C. (1976) Effect of illumination on the precision of
photogrammetric measurements using Apollo metric camera photographs:
Photogrammetric Engineering and Remote Sensing (in press).
- WU, S. S. C., SCHAFER, F. J., NAKATA, G. M., and JORDAN, RAYMOND (1973)
Photogrammetric evaluation of Mariner 9 photography: Jour. of
Geophys. Research, vol. 78, pp. 4405-4410.