CCSDS SPACE LINK EXTENSION (SLE) SERVICES -- OVERVIEW AND PROGRESS REPORT

Fred Brosi
Global Science & Technology, Inc.
Greenbelt, MD 20770

ABSTRACT

CCSDS Space Link Extension (SLE) Services enable the ground segment assets of space agencies to interoperate, allowing for ground stations and space data users to interact without the need for ad hoc, complicated gateways designed specifically for each new mission. Their goal is to reduce the development, management, and operational costs of providing cross support between space organizations for exchange of tracking, telemetry, and command (TT&C) data. SLE services are actively supporting over a dozen spacecraft, with many more planned over the next few years.

This paper first presents an overview of the underlying SLE architecture, as defined in the SLE Reference Model. The SLE data transfer services, which move data between mission facilities and ground stations are defined, along with the management services that enable missions to make requests for ground station services. Next, up-to-date status of the testing, prototyping, and implementation of SLE services over the past few years is presented, as well as plans for adoption of SLE services by a number of space networks and space mission organizations. Finally, efforts to adapt SLE services to support legacy missions are briefly described.

KEYWORDS

TT&C, CCSDS, Space Link Extension, telemetry, telecommand, service management.

INTRODUCTION

The Consultative Committee for Space Data Systems (CCSDS) was formed in 1982 by major space agencies of the world to provide a forum for discussion of common problems of space data systems. It is currently composed of ten member agencies, twenty-three observer agencies, and over 100 industrial associates. Since its establishment, it has been actively developing recommendations for data and information systems standards to:

- Reduce the cost to the various agencies of performing space missions
- Enable cross support for space missions
- Improve understanding of space related data

- Ensure preservation of archived space related data.

After CCSDS recommendations are approved by member agencies, they become international data standards through the International Standards Organization (ISO). Over 100 worldwide space missions have used CCSDS communications protocols to communicate with their spacecraft.

The Space Link Extension services are the result of an effort undertaken by CCSDS in the early 1990's to standardize cross support services that transfer spacecraft command and telemetry data among ground stations, mission operations centers, data processing facilities, and other parties that communicate with the spacecraft. That effort produced the *Cross Support Reference Model* [CCSDSa], which provides an architectural framework for definition of the SLE cross support services.

THE CROSS SUPPORT REFERENCE MODEL

The focus of SLE services, and thus of the Cross Support Reference Model, is the interface between ground stations and the mission data systems that they support (Figure 1).

Figure 1: Cross Support Services Extend the Space-Ground Link

A Space Data System (Figure 2) has two primary elements: a space element and a ground element. The space element and ground element are linked by space link communications services, which carry return data and forward data. Return data is sent from the space element to the ground element (e.g., telemetry). Forward data is sent from the ground element to the space element (e.g., telecommand).

Figure 2: Space Data System

The ground element of a Space Data System includes an SLE System and a Mission Data Operation System (MDOS). It may also contain other components, but these are outside the scope of the Reference Model.

The SLE System extends the transfer and delivery of forward and return data between a space link ground termination point and the MDOS. The set-up and use of the SLE System by a mission is managed by the MDOS (e.g., by mission operators or systems in a control center).

The space link services are extended on the ground using the Space Link Extension services. In addition to extension over the distance between ground station and data users, SLE services add annotation to the data, and may provide delayed delivery through off-line services.

The SLE services include two major elements:

SLE transfer services that move space link data units between ground stations, control centers and end-user facilities; and

SLE management services that control the scheduling and provision of the SLE transfer services.

The SLE services are used both for set-up and for data operations. During set-up, SLE management services are used to specify the configuration parameters needed to support a mission during an upcoming spacecraft contact. During execution, SLE transfer services are provided to the mission over ordinary ground networks. SLE management services are used to monitor progress during the contact. Off-line SLE transfer services may also be provided, outside periods of contact with the spacecraft.

The Reference Model defines transfer services for all types of CCSDS data units that can transverse the space link, but, in practice, only a few are used for cross support. These are:

- Forward Command Link Transmission Unit (F-CLTU) service, which enables users to provide CLTUs for uplink to the spacecraft [CCSDSb].
- Return All Frames (RAF) service, which provides the stream of telemetry frames from a single space link symbol stream to spacecraft operators and other users who might need all the frames [CCSDSc].
- Return Channel Frames (RCF) service, which provides a Master Channel (MC) or specific Virtual Channels (VCs) extracted from a particular RAF channel, as specified by the RCF service user [CCSDSd].

- Return Space Packet (R-SP) service, which enables a user to receive packets with selected Application Process Identifiers from a Virtual Channel [CCSDSe].

BENEFITS OF SLE SERVICES

SLE services further the goal of interoperability by establishing a standard for services to be used in the area where most cross support activity occurs - between the tracking stations or ground data handling systems of various organizations and the mission-specific components of a mission ground system. The SLE services are applicable to routine, contingency and emergency operations. Since the SLE protocols run over existing communications infrastructure, they help integrate Space Data Systems into the global communications network.

The advantages of SLE services are that:

- space organizations are able to provide Cross Support to one another more efficiently;
- ground station owners are able to provide standard services to operators of CCSDS-compliant spacecraft;
- users of spacecraft data are able to command their payloads and access their data through a familiar interface, using widely available underlying telecommunications technology such as the internet or ISDN lines;
- the standardization of ground station, control center and end user interfaces permits re-use of systems for successive missions and eliminate the costs and risks associated with mission-specific implementations;
- a truly global market for standard telemetry, tracking and command (TT&C) commercial off the shelf (COTS) products will be created, driving down the cost of these systems;
- SLE services are scalable, so only the services actually required by a service user or a service provider need to be implemented.
-

SPACE LINK EXTENSION (SLE) SERVICES – STATUS

Several ground networks are already providing SLE transfer services to operational space missions, and more will do so over the next few years. All of these systems use TCP/IP communications between the SLE Provider and User facilities. Summaries of current and planned SLE-related activities are provided below.

Europe-ESA

Currently, there are three ESA mission using SLE services. These are:

INTEGRAL, ESA's International Gamma-Ray Astrophysics Laboratory, was launched in October 2002 on a Proton rocket from Baikonour, Kazakhstan. INTEGRAL will pinpoint and study gamma-ray sources in unprecedented detail. The INTEGRAL Science Data Centre

(ISDC), located near Geneva, is supported and funded by a dozen institutes in Europe and the United States.

Mars Express was launched from Russia by a Soyuz Fregat in June 2003, and will arrive at Mars in December. The mission's main objective is to search for sub-surface water from orbit and to drop a lander on the Martian surface. The lander, called Beagle 2, will perform exobiology and geochemistry research. Mars Express will also provide relay communication services between the Earth and landers deployed on the surface by other space agencies.

Rosetta will be launched in February 2004 by an Ariane-5 from Kourou, French Guiana. Rosetta will study the nucleus of comet Wirtanen and its environment in great detail for a period of nearly two years, with far-observation leading ultimately to close observation from about one kilometer.

For each of these missions the following SLE services are provided:

- Return All Frames (RAF) online/timely, online/complete and off-line for Telemetry
- Return Channel Frames (RCF) online/timely, online/complete and off-line for Telemetry
- CLTU service for commanding uplink

These SLE services are implemented cooperatively between ESA's European Space Operations Center (ESOC) and NASA/JPL, with ESA in the role of "service user" and JPL as the "service provider". SLE Service Management for these missions is implemented as a private (ad hoc) management scheme to support SLE operational set-up, based on predefined tables that describe frequencies, bit rates, and other parameters. Any changes needed during a pass are handled over a voice loop.

ESA has begun deployment of SLE to its Ground Station Network, with completion scheduled for 2005. Thereafter all ESA missions will be supported by SLE services. These are expected to include:

Metop-1 (launch July 05)

Venus Express (launch November 05)

Herschel Plank (launch February 07)

Smart-2 (launch September 07)

ADM (launch October 07).

Germany-DLR

The German Space Agency (DLR) is planning to use SLE services in its German Spacecraft Operations Center (GSOC) in Oberpfaffenhofen, Germany to support future missions. The first two missions to use SLE services are:

TerraSAR, scheduled for launch in 2005. TerraSAR is a 2-satellite earth observation system with both X-band and L-band radars having a ground resolution of 1 meter. It is a joint venture by DLR (Germany), the British National Space Centre, Matra Marconi Space U.K., and DaimlerChrysler Aerospace (Germany).

SARLupe is a Space-based reconnaissance system. The Space segment consists of monofunctional radar satellites providing high resolution images under all weather conditions.

Prototyping of SLE services is underway at GSOC as part of the DLR modernization program. SLE services will be implemented between the GSOC Control Center and the ground station in Weilheim, Germany, and will also be used as the interface from the Control Center to external agencies. DLR's SLE implementation will be based on the ESA API.

Japan-ISAS & NASDA

In Japan, both the Institute of Space and Astronautical Science (ISAS) and the National Space Development Agency (NASDA) are using SLE services to support their missions.

The following are the ISAS and NASDA missions that plan to use SLE in the near future:

Hayabusa (formerly MUSES-C), launched on May 9, 2003, is designed to investigate an asteroid, and to bring back samples of its surface. The target asteroid is 1989ML, about 400 meters in diameter, and is unusual in that it sometimes closely approaches Earth. Hayabusa is an ISAS mission and is being supported by NASA/JPL's Deep Space Network.

Solar-B is a Japanese Institute of Space and Astronautical Science (ISAS) mission consisting of a coordinated set of optical, extreme ultraviolet, and X-ray instruments that will investigate the interaction between the Sun's magnetic field and its corona. Instruments from investigators from the U.K. and U.S. will fly on Solar-B. The Solar-B spacecraft is scheduled for launch in the fall of 2005, into a sun-synchronous orbit about the Earth. Solar-B will be supported by SLE services from NASDA.

Both ISAS and NASDA are developing gateways that perform protocol conversion between SLE and their internal protocols.

U.K.-BNSC

QinetiQ has installed a prototype SLE system in their ground station at West Freugh in Scotland. This system was developed by VEGA Group (UK), and provides Return All Frames (RAF) and Forward CLTU (F-CLTU) transfer services, as well as a web-based SLE service management interface [Ref. 6].

The Rutherford Appleton Laboratory (RAL) are planning to install a similar system in their ground station next year, so that this facility can provide SLE services cooperatively with the QinetiQ ground station to near-earth, deep space, and communications spacecraft.

Future plans include interoperability demonstrations with ESA and NASA networks.

U.S.-NASA/JPL

JPL has developed new interfaces to its Deep Space Network (DSN) to provide SLE transfer services, in preparation for support of a number of U.S. and international missions. ESA's INTEGRAL mission was the first for which SLE services were planned, but NASA's CONTOUR mission, developed by the Johns Hopkins University Applied Physics Laboratory, was the first to launch (July, 2002) using SLE services. By that time, JPL had already transitioned to using SLE Forward CLTU service for transfer of command uploads from Pasadena to DSN stations for support of all JPL flight projects (approximately one dozen currently flying). Those include Mars

Exploration Rover ("Opportunity" and "Spirit"), SIRTf, Mars Odyssey, Mars Global Surveyor, Cassini, Galileo, Stardust, Genesis, and Voyager.

All future missions supported by DSN are expected to use SLE transfer services, for both forward and return data traffic.

JPL is also using SLE services for mission critical cross-support operations:

ESA's INTEGRAL and Mars Express missions use F-CLTU, RAF, and RCF services. The Rosetta mission will also use those services.

Missions led by John Hopkins University's Applied Physics Lab and sponsored by NASA have used F-CLTU service in the past (CONTOUR) and are expected to use F-CLTU, RAF, and RCF services in the future (MESSENGER, STEREO, New Horizons).

ISAS's Hayabusa mission (aka MUSES-C) uses F-CLTU and RAF services.

NASA and ESA recently signed a Letter of Agreement such that JPL flight projects will be able to obtain support from ESA's New Norcia tracking station under certain conditions. SLE services will be used for all telemetry and command interfaces. This capability is proposed to be operational by December 2003.

U.S.-NASA/GSFC

NASA, through its CSOC contract, is developing a NASA-wide Ground Data Service Specification to provide CCSDS SLE Services at all NASA and commercial ground tracking stations serving NASA missions. A study team was formed to investigate the phasing out of NASA ground communications services based on Nascom blocks and to propose a replacement data service for all NASA ground facilities and commercial ground facilities that support NASA missions. The study team concluded that CCSDS Space Link Extension (SLE) meets the objectives for future science missions (based on CCSDS space links) for Space Network (SN--i.e., TDRSS), the Ground Network (GN), and the Deep Space Network (DSN). A proposal to implement SLE Services in these networks is under evaluation.

ADAPTATIONS OF SLE SERVICES

A uniform interface for arranging for and providing TT&C services is attractive even for systems that do not use CCSDS data structures on the space link. The SLE concept can be adapted to handle these legacy data streams. The United States Air Force (USAF) is investigating use of SLE Services in the Air Force Satellite Control Network (ASFCN) to ease transition from circuit-switched to packet-switched networking, and to provide interoperability with NASA ground sites. Global Science and Technology Inc. (GST) has developed prototype adaptations of SLE Services to demonstrate that SLE transfer services can support serial bit stream delivery in support of ASFCN legacy missions. An extension of this effort is prototyping adaptation of the SLE Service Management approach to manage non-CCSDS missions [Pietras].

OUTLOOK—WHERE IS SLE GOING?

The Interagency Operations Advisory Group (IOAG), at its fourth meeting in December 2001, reached agreement to proceed with CCSDS Space Link Extension (SLE) as the prime data service for future science missions. Also at this meeting, The French space agency, CNES, and the Italian space agency, ASI, reported plans for use of SLE Services in their new ground stations. At its fifth meeting in May 2003, the IOAG Cross-Support Mission Model listed more than twenty international missions that are using or plan to use SLE services.

NASA is developing a NASA-wide Ground Data Service Specification to implement CCSS SLE Services at all NASA ground tracking stations.

ESA's new 34 meter ground station in New Norcia, Australia, will provide Space Link Extension (SLE) services, including Telemetry (RAF, RVC) and Telecommand (CLTU, FSP), before December 2005.

SLE SERVICE MANAGEMENT

CCSDS is developing a specification [CCSDSf, CCSDSg] written in the eXtensible Markup Language (XML), based on the CCSDS SLE service management framework. This specification will enable the automation of service request exchanges using XML-based tools and technology. In parallel with writing of the specification, several prototypes are being developed to demonstrate the XML Service Request capability [Pietras].

ACKNOWLEDGEMENTS

The author would like to thank the following for information on the SLE implementations and user missions reported on in this paper: Wolfgang Hell and Mario Merri of ESA, Takihiro Yamada of ISAS, Manfred Drexler of DLR, Peter Allen of BNSC, and Susan Kurtik and Michael Stoloff of NASA/JPL. Funding for the author's participation in the CCSDS Space Link Extension activities has been provided by the NASA Goddard Space Flight Center Data Standards Program Office.

REFERENCES

[CCSDSa], Cross Support Reference Model, Part 1: Space Link Extension Services, Recommendation for Space Data System Standards, CCSDS 910.4-B-1, CCSDS, Washington, DC: May 1996.

[CCSDSb], Space Link Extension – Forward CLTU Service Specification, Recommendation for Space Data System Standards, CCSDS 912.1-B-1, Washington, DC: CCSDS, April 2002.

[CCSDSc], Space Link Extension – Return All Frames Service Specification, Recommendation for Space Data System Standards, CCSDS 911.1-B-1, Washington, DC: CCSDS, April 2002.

[CCSDSd], Space Link Extension – Return Channel Frames Service Specification, Draft Recommendation for Space Data System Standards, CCSDS 911.2-R-2, Washington, DC: CCSDS, September 2002.

[CCSDSe], Space Link Extension – Forward Space Packet Service Specification. Recommendation for Space Data System Standards, CCSDS 912.3-R-1. Red Book. Issue 1. Pasadena, CA: CCSDS, November 1997.

[CCSDSf], Space Link Extension - Service Management - Service Request - Service Specification, Recommendation for Space Data System Standards, CCSDS 910.11, CCSDS (working group draft).

[CCSDSg], Space Link Extension - Service Management - Service Request – XML Schema Specification, Recommendation for Space Data System Standards, CCSDS 910.15, CCSDS (working group draft).

[CCSDSh], Orbit Data Messages, Draft Recommendation for Space Data System Standards, CCSDS 502.0-R-2, Washington, DC: CCSDS, June 2002.

[Pietras], Pietras, John, “CCSDS Space Link Extension Service Management Standards and Prototyping Activities”, International Telemetry Conference Proceedings, paper number 044, International Telemetry Conference, Las Vegas, NV, October 2003.