PROCEEDINGS OF SPIE

SPIDigitalLibrary.org/conference-proceedings-of-spie

Simulation of a submarine to submarine QKD system

John Gariano, Ivan B. Djordjevic, Yi Xiang

John Gariano, Ivan B. Djordjevic, Yi Xiang, "Simulation of a submarine to submarine QKD system," Proc. SPIE 10803, Quantum Information Science and Technology IV, 1080304 (8 October 2018); doi: 10.1117/12.2325808

SPIE.

Event: SPIE Security + Defence, 2018, Berlin, Germany

Simulation of a Submarine to Submarine QKD System

John Gariano^{1,*}, Ivan B. Djordjevic¹, and Xiang Yi^{1,2}

¹Department of Electrical and Computer Engineering, University of Arizona, 1230 E Speedway Blvd, Tucson, Arizona 85721, USA

²State Key Laboratory of Integrated Service Networks, Xidian University, No. 2 Taibai South Road, Xi'an 710071, China

ABSTRACT

Due to the absorption of water, communication between two parties submersed below the water is normally performed with acoustic waves. However, with the need for higher data rates, the use of RF or optical frequencies is needed. Currently optical wavelengths have been demonstrated for classical communication over short distances. For these short distances, if a large amounts of data needs to be transmitted securely, it is not feasible for both parties to return to the surface to exchange, and it can be assumed that a third party Eve, is located in the channel trying to gather information. The solution is to use quantum key distribution (QKD) to generate the secure key, allowing the parties to continuously encrypt and transmit the data. It is assumed the BB92 protocol using pairs of entangled photons generated from a spontaneous parametric down conversion (SPDC) source of Type-II. By using entangled photons, Eve is not able to gain information without being detected. In this work, the beam propagation through a horizontal oceanic channel is studied for various distances ranging from 10m to 100m at visible wavelengths. The secure key rates are then calculated assuming that a low-density parity check (LDPC) error correction code is used for information reconciliation, as well as the maximum distance that a QKD protocol can be implemented for a submarine environment.

Keywords: Entanglement Quantum Key Distribution, Oceanic Turbulence, Type II SPDC source, Underwater Communication, Underwater Beam Propagation

1. INTRODUCTION

To perform communication between two parties underwater there are several options depending on the distance between the parties as well as the desired communication rate. Possible solutions for underwater communication are acoustic or electromagnetic waves. Using acoustic waves, data rates of ~ 600 bps can be achieved at distances of 1000 km, while data rates of ~ 30 kbps can be achieved for distances between 0.1 and 1 km. For the electromagnetic waves, in the radio frequency (RF) range, as the frequency is increased the attenuation also increases. This results in only being able to achieve data rates on the order of Mbps at distances of ≈ 10 m. Using optical frequencies, data rates on the order of Gbps can be achieved for distances up to 100 m.¹ When using acoustic waves and RF frequencies, the transmission is not highly directional introducing a security vulnerability, however the optical frequencies are highly directional. Not only does this reduce the security vulnerability, but less power is now required for transmission. In underwater optical communication, links are also not limited to direct line of sight (LOS) but can also include reflective LOS by using total internal reflection at the water-air boundary.¹

In any link the ability to transmit data securely between two parties is a desirable property, however conventional methods for encrypting data are designed using computational complexity. If an adversary is provided enough time or adequate computational power, the encrypted data is no longer secure.² The solution to this security loophole is through the use of one-timepad keys for encryption, where after the key has been used it is discarded. To generate a secret key between the two authenticated parties, Alice and Bob, at a distance quantum key distribution (QKD) can be used.³⁻⁵ QKD can be implemented using either single photons or entangled photons, of which this work considers the use of entangled photons.^{6,7} It has been shown that an underwater quantum channel has very limited depolarization and disentanglement, implying that QKD is feasible.⁸

*E-mail: Jagariano@email.arizona.edu

Figure 1: a) QKD System model with an entangled photon source located at an arbitrary position in the channel. The channel can be broken into multiple segments, the source to Alice (SA), the source to Eve (SE), and Eve to Bob (EB) b) The detection apparatus used to implement the BB84 protocol, consisting of two mutual unbiased basis, each containing two orthogonal polarizations

Considering secure communication between two submarines, it is not feasible for them to return to the ocean surface to generate a new shared key as this will be time consuming and may reveal their position to an adversary. To mitigate this, our work considers the use of QKD at depths of 100, 150 and 200 m in South Atlantic ocean at 35°S for various distances ranging from 10m to 100m. This paper will first describe the various channels being considered, then give a description of the QKD system that is implemented, and finally show the resulting secure key rates that were able to be achieved for each channel.

2. QKD SYSTEM

To implement an entanglement assisted QKD system that is capable of operating in an underwater channel, photons need to be generated in the blue-green wavelength region and will be explained in Section 3. In the work of Sciarrino *et al*, the generation of polarization entangled photons at a wavelength of 532 nm with high purity and fidelity using the SPDC process is described.⁹ Additionally, the work of Li *et al*, showed that superconducting nanowire single photon detectors (SNSPDs) operating at a 532 nm, with detection efficiency of 75% and dark count rate of <0.1 Hz.¹⁰ The SNSPDs have a sensitive area diameter of 42 μm and a full recovery time of 300 ns, thus the system will be assumed to operate at a rate of 300 MHz. This also implies that the probability of a detector clicking due to a dark count is $P_{\text{Dark}} = 3 \times 10^{-7}$.

In a polarization entanglement assisted QKD system the source is not required to be located at either Alice or Bob, however in our system it will be located at Alice's side. An eavesdropper, Eve, is assumed to be located in the channel between Alice and Bob with the ability to correct all distortions to the wavefront caused by the channel and the ability to detect how many photons were transmitted without measuring the photons. By using entangled photons, Eve is not able to gain any information due to the generation of multiple entangled photon pairs.¹¹ Eve is not actively simulated to perform the intercept-resend attack, however all errors are assumed to be generated by Eve. Eve however is passively listening to all of the communication on the public channel, and gains knowledge of the final key when Alice and Bob perform error reconciliation. To implement the BB84 protocol using polarization entangled photon, Alice and Bob will both have similar detection apparatuses. A 50:50 beam splitter (BS) will sort the photons into one of two arms. Using a half wave-plate (HWP) the photons are put into mutually unbiased polarization basis, HV or AD, then a polarizing beam splitter (PBS) determines the orientation they are to be measured in. In Figure 1, a system model is presented showing the channel configuration and the detection apparatus.

The source is assumed to be a Type-II periodically poled LiNbO_3 (PPLN) nonlinear crystal, and the probability that n entangled photon pairs are generated is given by

$$P_S(n) = \frac{(n+1)(\mu/2)^n}{(1 + (\mu/2))^{n+2}}, \quad (1)$$

where μ is the mean number of entangled photon pairs generated.¹² In this work only μ will be considered, however by definition μ is dependent on the coupling efficiency. To calculate the total amount of information that Eve gains, the security proof by Koashi *et al* is used.¹³ For a given bit error rate δ , the rate of generating a secure key is given as

$$R_{SKR} = P_{Key} [1 - f(\delta)H_2(\delta) - H_2(\delta)], \quad (2)$$

where P_{Key} is the probability a time slot being included in the unsecured key, $H_2(\delta)$ is the binary entropy function, and $f(\delta)$ is the error reconciliation efficiency. If an ideal error correction code is used, $f(\delta) = 1$, in this work practical LDPC codes are considered and can be found in the work of Elkouss *et al*.¹⁴

3. UNDERWATER OPTICAL CHANNEL

Similar to a free-space optical channel, and underwater channel will have attenuation, from absorption and scattering, as well as beam wander and degradation due to turbulence. For pure water the absorption spectrum is known and dependent on the wavelength used, with a minimum absorption of $a_w(\lambda) = 0.00442 \text{ m}^{-1}$ for $\lambda = 417.5 \text{ nm}$.¹⁵ Additionally the size and type of particles in the water can also impact the channel loss. In an oceanic underwater channel, scattering from particles can be classified into either small or large particles, each with a different statistical distribution. For absorption, factors such as the concentration of chlorophyll-a, fulvic and humic acids.¹⁶ Chlorophyll-a is the main substance of phytoplankton (photosynthesizing microorganisms), while fulvic and humic acids act as nutrients as phytoplankton. The concentration of the particles has been modeled using the chlorophyll concentration at a depth d , $C_c(d)$, and the total channel attenuation is given by:^{16,17}

$$\alpha(\lambda, d) = a(\lambda, d) + b(\lambda, d), \quad (3)$$

where $a(\lambda, d)$ and $b(\lambda, d)$ are the absorption and scattering coefficients. $C_c(d)$ is modeled using a Gaussian curve that is dependent upon the depth, depth of the euphotic layer Z_{eu} , average column-integrated content of total chlorophyll a within euphotic layer $\overline{Chla}_{Z_{eu}}$ (mg m^{-3}), background chlorophyll concentration at the sea surface C_b , the vertical gradient s (m^{-1}),¹⁸

$$C_c(d) = \overline{Chla}_{Z_{eu}} \left(C_b - s \times \frac{d}{Z_{eu}} + C_{Max} \exp \frac{-(d/Z_{eu} - \zeta_{Max})^2}{\Delta\zeta^2} \right), \quad (4)$$

where C_{Max} is the maximum concentration, $\Delta\zeta$ is the width of the Gaussian peak, and $\zeta_{Max} = Z_{Max}/Z_{eu}$ is the dimensionless depth of the maximum concentration. This leads to the concentrations of the fulvic acid C_f , humic acid C_h , small particles C_s and large particles C_l at depths d as follows,

$$C_f(d) = 1.74098 C_c(d) \exp(0.12327 C_c(d)), \quad (5)$$

$$C_h(d) = 0.19334 C_c(d) \exp(0.12343 C_c(d)), \quad (6)$$

$$C_s(d) = 0.01739 C_c(d) \exp(0.11631 C_c(d)), \quad (7)$$

$$C_l(d) = 0.76284 C_c(d) \exp(0.03092 C_c(d)). \quad (8)$$

Now using the chlorophyll-based model, the absorption spectrum is given as

$$a(\lambda, d) = a_w(\lambda) + a_f C_f(d) \exp(-k_f \lambda) + a_h^0 C_h(d) \exp(-k_h \lambda) + a_c^0 C_c(d)^{0.602}, \quad (9)$$

where the specific absorption coefficients and exponential coefficient for the fulvic acid and humic acid and chlorophyll are $a_f = 35.959 \text{ m}^2/\text{mg}$, $a_h = 18.828 \text{ m}^2/\text{mg}$ and $k_f = 0.0189 \text{ nm}^{-1}$, $k_h = 0.01105 \text{ nm}^{-1}$. The

absorption coefficient for chlorophyll can be found in the work of Bricaudi *et al.*¹⁹ The scattering spectrum can similarly be defined as

$$b(\lambda, C_c(d)) = b_w(\lambda) + b_s^0(\lambda)C_s(d) + b_l^0(\lambda)C_l(d), \quad (10)$$

where the scattering spectrum for pure water $b_w(\lambda)$, small particles $b_s(\lambda)$, and large particles $b_l(\lambda)$ are

$$b_w(\lambda) = 0.005826(400/\lambda)^{4.3222}, \quad (11)$$

$$b_s^0(\lambda) = 0.11513(400/\lambda)^{1.7}, \quad (12)$$

$$b_l^0(\lambda) = 0.3411(400/\lambda)^{0.3}. \quad (13)$$

Similar to the concentration of chlorophyll, the oceanic turbulence strength can also vary with depth and geographic location. In general the ocean can be broken into the following layers; the mixed surface layer extending up to 200m, the upper waters ranging from 200m to 1000m, and deep water which is below 1000m. The surface layer is well mixed by the wave, currents, and tides. The upper waters is a layer where there are rapid changes in the density, temperature, and salinity. The deep water is cold and very dense. In this work, beam propagation in the surface layer of the Southern Atlantic ocean around 35°S is considered. The oceanic turbulence induce changes in the index of refraction resulting in beam wander, intensity fluctuations, and increased dispersion. The power spectrum of the oceanic turbulence is defined by Yi *et al.*²⁰

$$\Phi_n(\kappa) = (4\pi)^{-1}A^2\beta\chi_T\epsilon^{-1/3}\kappa^{-11/3}\left[g(\kappa\eta, Pr_T) + \frac{d_r}{\omega^2}g(\kappa\eta, Pr_S) - \frac{(1-d_r)}{\omega}g(\kappa\eta, Pr_{TS})\right], \quad (14)$$

where ϵ is the dissipation rate of turbulent kinetic energy per mass of fluid, χ_T is the diffusive dissipation rate of the mean-square temperature fluctuations, ω is the relative strength of temperature and salinity fluctuations, A is the thermal expansion coefficient and d_r is the ratio of saline eddy diffusivity to thermal eddy diffusivity. κ is the magnitude of the wavenumber vector, and β is the Oboukhov-Corrsin constant. $g(\kappa\eta, Pr)$ is a universal function defined as

$$g(x, Pr) = \left[1 + \sum_{n=1}^n a_n x^n\right] \exp(-\delta x), \quad (15)$$

with constants defined in.²⁰ Pr is known as the Prandtl number and it relates the Kolmogorov and Batchelor length scales. ϵ and χ_T are found by considering the wind stress at the surface, heat flux at the surface, density, temperature, salinity and specific heat at constant pressure. Both ϵ and χ_T are inversely proportional to the depth.²¹ For the South Atlantic ocean around 35°S in June, these constants values can be found in the works of Klinger *et al*, Dong *et al*, Jamieson *et al*, and Goes *et al*.²²⁻²⁵

To model the effect of oceanic turbulence on an optical beam, beam propagation simulations are ran using the split step beam propagation method.^{26,27} The simulation space consisted of 4096×4096 grid, with side lengths of 1 m. Using the turbulence power spectrum in Equation (14), phase screens are generated corresponding to a 1m thick slab of turbulence. The transmit and receive apertures are assumed to be 5cm in diameter with focal lengths of 10 cm, and a plane wave is transmitted. The region that is being considered is a subtropical region, and the parameter for the turbulence profile are shown in Table 1. The probability that a photon lands on a circular detector with a diameter of 42 μm is shown in Figure 2 a). With the increase in the depth, the strength of the turbulence decreases, resulting in a higher probability that a photon will land on the detector. However, as the distance increases the beam spreads and more phase distortions are added to the wavefront causing the focused spot to blur and the probability that a photon lands on the detector to decrease.

The chlorophyll concentration at the surface is estimated to be between 0.12 and 0.2 for the month of June at 35°S, so parameters from data set S4 in Uitz *et al* are used.^{18,28} The constant values are $\overline{Chla}_{Z_{eu}} = 0.250$, $Z_{eu} = 80.2$, $C_b = 0.570$, $s = 0.173$, $C_{max} = 0.766$, and $\Delta\zeta = 0.814$.¹⁸ The resulting attenuation profile vs the depth is shown in Figure 2 b). The highest attenuation is above the depths considered, resulting in lower attenuation as the depth increases. This allows for transmission at longer distances to occur. Additionally, the attenuation profile as a function of depth allows us to calculate the total attenuation of the background light

Table 1: Channel Conditions

d	Salinity	Temp	A	χ_T	ϵ	α	α_{Davg}	P_{Back}
100	36.4 PPT	23	2.824×10^{-4}	1.30×10^{-7}	4.50×10^{-8}	0.1047	0.1162	1.167×10^{-2}
150	35.55 PPT	15.0	2.123×10^{-4}	1.06×10^{-7}	3×10^{-8}	0.0678	0.1063	1.895×10^{-4}
200	35.3 PPT	13.0	1.9230×10^{-4}	8.43×10^{-8}	2.25×10^{-8}	0.0579	0.0953	8.841×10^{-6}

Figure 2: a) Probability that a photon propagating a distance L underwater lands on a $42 \mu\text{m}$ diameter circular detector for depths of 100m and 200m. b) The attenuation profile as a function as underwater depth.

that enters the receive aperture. At the surface of the ocean, the background irradiance is $E_{sol} = 1440 \text{ W/m}^2$, the number of background photons landing on the detector, N_{Back} is calculated as follows^{29,30}

$$L_{Sol} = \frac{E_{sol} R L_{fac}}{\pi} \exp(-\alpha_{Davg} D) \quad (16)$$

$$N_{Background} = \frac{\lambda}{hc} \tau_s L_{Sol} \frac{\pi \Theta^2}{4} \frac{\pi D_{rx}^2}{4} \Delta \lambda \eta_r \eta_\lambda. \quad (17)$$

where the factor describing the direction of underwater irradiance $L_{fac} = 2.9$, the underwater reflectance $R = 1.25\%$, and the average attenuation of the water column from the surface to a depth D is α_{Davg} in m^{-1} . To calculate α_{Davg} , the numerical integral of $a(\lambda, d)$ is taken with respect to d is calculated from 0 to D , then divided by D . To calculate N_{Back} , the transmittance of the receiver optics $\eta_r = 0.1881$, the narrow band filter spectral bandwidth $\Delta \lambda = 10 \text{ \AA}$, the narrow band filter transmission $\eta_\lambda = 1$, the detector diametrical field of view Θ , and $hc = 1.986 \times 10^{-23}$ is Planck's constant times the speed of light. The values for α , α_{Davg} , as well as the probability of a background photon landing on a detector, P_{Back} , are summarized in Table 1.

4. QKD SIMULATION RESULTS

To simulate the QKD system that has been described above, we use a simulation that steps through values of μ with a step size of 0.005.³¹ The maximum SKR and optimal value of μ are shown in Figure 3. The first trend to notice, is that as you increase the distance between the submarines, both the SKR and optimal value μ decreases. This decrease is due to the increased loss introduced into the channel. With the noise level remaining constant, higher loss results in a larger portion of the un-secure key bits being generated from noise and increasing the bit error rate. With the channel at a depth of 100 m having the highest attenuation and background noise irradiance, no positive SKR can be achieved. For the channels at depths of 150 m and 200 m, the difference in the SKR is minimal for a distance of 10 m. As the distance increases the SKR decreases, and after 50m the SKR goes to zero for a depth of 150m. The faster decrease in the SKR at a distance of 150m is due to the probability of noise being approximately 20 times great than for a depth of 200m. This can be seen easier by considering the optimal value for μ . As the channel is attenuated more, fewer of the transmitted photons reach Bob's detectors, while all the transmitted photons reach Alice's detectors. In the time slots where a photon has been lost due to channel attenuation, if Bob detects a click due to noise in the correct basis, the probability of error is 0.5. By

Figure 3: a) Optimum SKR at various distances for depths of 100m and 200m. b) Optimum μ at various distances for depths of 100m and 200m.

reducing μ , Alice's detector will click in fewer time slots, and reducing the probability that both a click due to noise is recorded by Bob and that Alice has detected a photon that was transmitted.

5. CONCLUDING REMARKS

As underwater optical communication starts to be implemented the ability to communicate securely will also be needed. It has been shown that for various depths the use of quantum key distribution operating at a wavelength of 532 nm is feasible for generating a secure key. As the distance is increased the generation rate decreases due to the channel attenuation. Additionally, oceanic turbulence causes distortions in the wavefront, further increasing the loss in the channel. In the surface layer, as the depth increase the turbulence strength decreases, resulting in more reliable channels for optical communication. The depth of the maximum concentration of chlorophyll-a determines the amount of attenuation in the channel, as well as the amount of background light that reaches the system. As the maximum concentration moves closer to the surface less background light will be introduced into the system allowing for a secret key to be generated at higher depths and longer channel. Additionally as the distance of the channel increases, the optimum value of μ decreases.

Funding Information

ONR MURI program (N00014-13-1-0627)

REFERENCES

- [1] Kaushal, H. and Kaddoum, G., "Underwater optical wireless communication," *IEEE Access* **4**, 1518–1547 (2016).
- [2] Schneier, B., [*Applied cryptography: protocols, algorithms, and source code in C*], Wiley-India (2007).
- [3] Bennett, C. H. and Brassard, G., "Quantum cryptography: public key distribution and coin tossing int," in [*Conf. on Computers, Systems and Signal Processing (Bangalore, India, Dec. 1984)*], 175–9 (1984).
- [4] Ekert, A. K., "Quantum cryptography based on bell's theorem," *Physical Review Letters* **67**(6), 661–663 (1991).
- [5] Bennett, C. H., Brassard, G., and Mermin, N. D., "Quantum cryptography without bell's theorem," *Physical Review Letters* **68**(5), 557–559 (1992).
- [6] Zhang, H.-F., Wang, J., Cui, K., Luo, C.-L., Lin, S.-Z., Zhou, L., Liang, H., Chen, T.-Y., Chen, K., and Pan, J.-W., "A real-time qkd system based on fpga," *Journal of Lightwave Technology* **30**(20), 3226–3234 (2012).
- [7] Poppe, A., Fedrizzi, A., Ursin, R., Böhm, H. R., Lorünser, T., Maurhardt, O., Peev, M., Suda, M., Kurt-siefer, C., Weinfurter, H., Jennewein, T., and Zeilinger, A., "Practical quantum key distribution with polarization entangled photons," *Optics Express* **12**, 3865–3871 (8 2004).

- [8] Ji, L., Gao, J., Yang, A.-L., Feng, Z., Lin, X.-F., Li, Z.-G., and Jin, X.-M., "Towards quantum communications in free-space seawater," *Optics Express* **25**, 19795–19806 (Aug. 2017).
- [9] Sciarrino, F., Vallone, G., Milani, G., Avella, A., Galinis, J., Machulka, R., Perego, A. M., Spasibko, K. Y., Allevi, A., Bondani, M., and Mataloni, P., "High degree of entanglement and nonlocality of a two-photon state generated at 532 nm," *The European Physical Journal Special Topics* **199**, 111–125 (Nov. 2011).
- [10] Li, H., Chen, S., You, L., Meng, W., Wu, Z., Zhang, Z., Tang, K., Zhang, L., Zhang, W., Yang, X., Liu, X., Wang, Z., and Xie, X., "Superconducting nanowire single photon detector at 532 nm and demonstration in satellite laser ranging," *Optics Express* **24**, 3535–3542 (Feb. 2016).
- [11] Bettelli, S., Lorunser, T., Peev, M., Querasser, E., Dusek, M., Bartuskova, L., Blauensteiner, B., Huebel, H., Poppe, A., and Zeilinger, A., "Effect of double pair emission to entanglement based qkd," in [2007 European Conference on Lasers and Electro-Optics and the International Quantum Electronics Conference], 1–1 (June 2007).
- [12] Ma, X., Fung, C.-H. F., and Lo, H.-K., "Quantum key distribution with entangled photon sources," *Physical Review A* **76**, 012307 (7 2007).
- [13] Koashi, M. and Preskill, J., "Secure quantum key distribution with an uncharacterized source," *Physical Review Letters* **90**, 057902 (2 2003).
- [14] Elkouss, D., Leverrier, A., Alleaume, R., and Boutros, J. J., "Efficient reconciliation protocol for discrete-variable quantum key distribution," in [2009 IEEE International Symposium on Information Theory], 1879–1883 (6 2009).
- [15] Pope, R. M. and Fry, E. S., "Absorption spectrum (380–700 nm) of pure water. ii. integrating cavity measurements," *Appl. Opt.* **36**, 8710–8723 (Nov. 1997).
- [16] Johnson, L. J., Green, R. J., and Leeson, M. S., "Underwater optical wireless communications: depth dependent variations in attenuation," *Appl. Opt.* **52**, 7867–7873 (Nov. 2013).
- [17] Haltrin, V. I., "Chlorophyll-based model of seawater optical properties," *Appl. Opt.* **38**, 6826–6832 (Nov. 1999).
- [18] Uitz, J., Claustre, H., Morel, A., and Hooker, S. B., "Vertical distribution of phytoplankton communities in open ocean: An assessment based on surface chlorophyll," *Journal of Geophysical Research: Oceans* **111**(C8) (2005).
- [19] Bricaud, A., Babin, M., Morel, A., and Claustre, H., "Variability in the chlorophyll-specific absorption coefficients of natural phytoplankton: Analysis and parameterization," *Journal of Geophysical Research: Oceans* **100**(C7), 13321–13332 (1995).
- [20] Yi, X. and Djordjevic, I. B., "Power spectrum of refractive-index fluctuations in turbulent ocean and its effect on optical scintillation," *Optics Express* **26**, 10188–10202 (4 2018).
- [21] Lombardo, C. P. and Gregg, M. C., "Similarity scaling of viscous and thermal dissipation in a convecting surface boundary layer," *Journal of Geophysical Research: Oceans* **94**(C5), 6273–6284 (1989).
- [22] Klinger, B. A., Huang, B., Kirtman, B., Schopf, P., and Wang, J., "Monthly climatologies of oceanic friction velocity cubed," *Journal of Climate* **19**(21), 5700–5708 (2006).
- [23] Dong, S., Sprintall, J., Gille, S. T., and Talley, L., "Southern ocean mixed-layer depth from argo float profiles," *Journal of Geophysical Research: Oceans* **113**(C6) (2008).
- [24] Jamieson, D., Tudhope, J., Morris, R., and Cartwright, G., "Physical properties of sea water solutions: heat capacity," *Desalination* **7**(1), 23–30 (1969).
- [25] Goes, M., Christophersen, J., Dong, S., Goni, G., and Baringer, M. O., "An updated estimate of salinity for the atlantic ocean sector using temperature-salinity relationships," *Journal of Atmospheric and Oceanic Technology* **0**(0), null (2018).
- [26] Voelz, D. G., [Computational Fourier optics: a MATLAB tutorial], vol. TT89;v. TT 89., SPIE, Bellingham, Wash. (1000 20th St. Bellingham WA 98225-6705 USA) (2011).
- [27] Schmidt, J. D., [Numerical simulation of optical wave propagation: with examples in MATLAB], vol. 199;199., SPIE (2010).
- [28] NASA Earth Observatory, "Chlorophyll & sea surface temperature," (2018).

- [29] Jaruwatanadilok, S., “Underwater wireless optical communication channel modeling and performance evaluation using vector radiative transfer theory,” *IEEE Journal on Selected Areas in Communications* **26**, 1620–1627 (Dec. 2008).
- [30] Burk, B. D. and Marshall, W. K., “Received optical power calculations for optical communications link performance analysis,” tech. rep., NASA (1986).
- [31] Gariano, J. and Djordjevic, I. B., “PPLN-waveguide-based polarization entangled QKD simulator,” in [*Quantum Communications and Quantum Imaging XV*], Meyers, R. E., Shih, Y., and Deacon, K. S., eds., *Proc.SPIE* **10409**, SPIE (aug 2017).